



# ***P-STAT***<sup>®</sup>

## ***Master Index***



## ***P-STAT: Master Index***

Second Edition: October 2013

This publication corresponds to **P-STAT Release 5 July 2013**. This publication provides a master index to the 10 volume P-STAT User's Manual

Please direct any questions to:

**P-STAT, Inc.**  
230 Lambertville-Hopewell Rd.  
Hopewell, New Jersey 08525-2809  
U.S.A.

**Telephone: 609-466-9200**

**Fax: 609-466-1688**

**Internet: support@pstat.com**

**Web Page URL: <http://www.pstat.com>**

All rights reserved. Except as permitted under the United States Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, electronic or mechanical, including photocopying, recording, or any information storage and retrieval system without the prior written permission of P-STAT, Inc.

P-STAT is a registered trademark of P-STAT, Inc. Windows is a registered trademark of MicroSoft Corp. Copyright © 1972-2013 P-STAT, Inc. Printed in the US. Published by P-STAT, Inc.

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

## Symbols

S-2.13  
 ( ) MATCHES meta-character P-9.21  
 \* MATCHES meta-character P-9.21  
 \* PPL numeric operator P-2.12, P-2.28  
 \*\* PPL numeric operator P-2.12, P-2.28  
 \*/ comment ending P-2.23, P-3.20  
 / PPL numeric operator P-2.12, P-2.28  
 /\* comment beginning P-2.23, P-3.20  
 // concatenate P-9.4, P-9.31  
 /// squeeze concatenate P-9.5, P-9.31  
 \\ MATCHES meta-character P-9.21  
 & MACRO substitution P-12.4  
 && concatenation of character constants  
     P-9.23, P-9.31  
 # MATCHES meta-character P-9.21  
 # scratch variables P-8.3  
 + MATCHES meta-character P-9.21  
 + PPL numeric operator P-2.12, P-2.28  
 < > MATCHES meta-character P-9.21  
 \$ MATCHES meta-character P-9.21  
 - MATCHES meta-character P-9.21  
 - PPL numeric operator P-2.12, P-2.28  
 ? MATCHES meta-character P-9.21  
 ? variable name wildcard P-2.9, P-2.23  
 [ ] MATCHES meta-character P-9.21  
 ^ MATCHES meta-character P-9.21  
 \_ MATCHES meta-character P-9.21  
 | MATCHES meta-character P-9.21  
 0 1 MATCHES meta-character P-9.21  
 0 + MATCHES meta-character P-9.21  
 1 1 MATCHES meta-character P-9.21  
 1 + MATCHES meta-character P-9.21

## System Variables

.ALL. P-3.8, P-3.11, P-11.14, P-11.34  
 .CDATE. P-6.26, S-11.5  
 .CHARACTER. I-9.5, P-2.8, P-6.17, P-6.24  
 .CHECKCASES. I-9.5, I-9.9, F-12.1,  
     F-12.16  
 .CHECKFILE. F-12.1, F-12.16  
 .CHECKFILE., I-9.5, I-9.9  
 .CHECKVARS. F-12.1, F-12.16

.CHECKVARS., I-9.5, I-9.9  
 .COLLECTIONS. I-9.6, I-9.10, P-8.27,  
     P-8.30  
 .COLLECTMAX. I-9.6, I-9.10, P-8.27,  
     P-8.30  
 .COLLECTMIN. I-9.6, I-9.10, P-8.27,  
     P-8.30  
 .COLLECTSIZE. I-9.6, I-9.10, P-8.23,  
     P-8.27, P-8.30  
 .COLLECTSUM. I-9.6, I-9.10, P-8.27,  
     P-8.30  
 .CTIME. P-6.26, S-11.5  
 .DATE. I-9.5, W-2.6, P-6.19, P-6.24  
 .DUPMAX. F-10.18, F-10.23  
 .E. I-9.5  
 .e. P-6.14, P-6.24  
 .FILE. I-9.4, P-6.18, P-6.24, P-8.2  
 .G. I-9.5, P-2.14, P-6.14, P-6.24  
 .HERE. I-9.5, P-3.6, P-6.16, P-6.24  
 .INQUIRE. P-12.23, P-12.31  
 .M1., .M2., .M3. P-6.15, P-6.25  
 .M. I-9.5, P-2.14, P-6.15, P-6.24  
     system variable P-2.27  
 .N. I-9.5, P-3.6, P-6.16, P-6.25  
 .NDATE. P-6.19, P-6.26, S-11.5  
 .NEW. P-2.8, P-6.5, P-6.25  
 .NTIME. P-6.19, P-6.26, S-11.5  
 .NUMERIC. I-9.5, P-2.8, P-6.17, P-6.25  
 .NV. I-9.5, P-6.15, P-6.25  
 .ON. I-9.5, P-2.3, P-6.25  
 .OTHERS. I-9.5, P-2.8, P-6.25  
 .PAGE. I-6.27, P-6.19, P-6.25, S-1.18,  
     S-5.23, S-10.4  
     in titles in listings I-6.16  
 .PI. I-9.5, P-6.14, P-6.25  
 .PUT. I-9.5, P-3.9, P-6.18, P-6.25  
     with system variables P-8.11  
 .RDATE. P-6.26, S-11.5  
 .RESPONSE. P-12.21, P-12.31, U-2.12  
 .RPAGE. I-6.27, S-5.23, S-10.4  
     in titles in listings I-6.16  
 .RTIME. P-6.26, S-11.5  
 .SUBFILECASES. P-12.26  
 .SUBFILEMAX. P-12.26

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

.SUBFILEPASS. P-12.26  
 .TIME. I-9.5, P-6.19, P-6.25  
 .USED. I-9.5, P-6.16, P-6.26  
 .XDATE. P-6.26, S-11.5  
 .XINQUIRE. P-12.22, P-12.31, U-2.18  
 .XTIME. P-6.26, S-11.5

**PUT and TEXTWRITER Controls**

@  
 in PUT and PUTL P-3.9, P-3.19  
 in TEXTWRITER command P-11.9,  
 P-11.33

@ MATCHES meta-character P-9.21

@BEFORE  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.10,  
 P-11.33

@COMMAS  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.11,  
 P-11.34

@EQUAL  
 in PUTL P-3.11, P-3.19  
 in TEXTWRITER command P-11.13,  
 P-11.34

@INDENT  
 in TEXTWRITER command P-11.10,  
 P-11.34

@JUST  
 in TEXTWRITER command P-11.10,  
 P-11.34

@LABEL  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.14

@MINUS  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.9,  
 P-11.35

@MISS  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.14,  
 P-11.34

@NEXT  
 in PUT and PUTL P-3.11, P-3.13, P-3.19

in TEXTWRITER command P-11.10,  
 P-11.35

@PAGE  
 in PUT and PUTL P-3.13  
 in TEXTWRITER command P-11.10,  
 P-11.35

@PARA  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.10,  
 P-11.35

@PLACES  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.12,  
 P-11.35

@PLUS  
 in PUT and PUTL P-3.19  
 in TEXTWRITER command P-11.8,  
 P-11.9, P-11.35

@SKIP  
 in PUT and PUTL P-3.13, P-3.19  
 in TEXTWRITER command P-11.8,  
 P-11.35

@SPREAD  
 in TEXTWRITER command P-11.13,  
 P-11.35

@TRIM  
 in PUT AND PUTL P-3.19  
 in TEXTWRITER command P-11.10,  
 P-11.35

@WIDTH  
 in TEXTWRITER command P-11.10,  
 P-11.36

**A**

A11  
 in SJOIN command A-1.8

A12  
 in SJOIN command A-1.8

ABBREVIATION S-1.6  
 in SURVEY command S-1.6, S-1.27

ABS  
 PPL function P-6.2, P-6.20

ABSENT  
 in UPDATE command F-11.3, F-11.11

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- Absolute value function P-6.2
- ABSORB
  - in ANOVA command A-6.44
- ACOS
  - PPL function P-6.3, P-6.20
- Active files W-2.2
- Actuarial method in survival analysis
  - see LIFE.TABLE
- ADD
  - in NEW.EDIT.FILE command U-3.5
  - in OLD.EDIT.FILE command U-3.5
  - in SURVEY command S-3.6, S-9.1
- Add dates and times P-10.21
- Add variables F-1.3
  - see GENERATE
- Adding cases F-1.2
- Addition operator + P-2.12
  - in ANOVA command A-6.6, A-6.41
  - MATCHES meta-character P-9.21
- Adjusted R squared
  - in REGRESSION command B-4.5
- AGAIN U-3.3, U-5.4
  - EDITOR instruction U-6.8
  - in EDA command B-6.3
  - in PLOT command O-3.6
  - in REGRESSION command B-4.7
  - in SURVEY command S-2.22
  - summary U-3.7
- AGGREGATE W-2.4, **F-10.1**
  - collecting statistics F-10.5
  - identifiers
    - ALLGROUPS F-10.22
    - BY F-10.1, F-10.21
    - CARRY F-10.22
    - COLLECT F-10.5, F-10.22
    - COUNT F-10.3, F-10.7, F-10.22
    - MAX F-10.3, F-10.22
    - MEAN F-10.3, F-10.7, F-10.21
    - MIN F-10.4
    - NO IDENTIFY F-10.23
    - OUT F-10.3, F-10.21
    - PREFIX F-10.8, F-10.23
    - SDEV F-10.4, F-10.7, F-10.22
    - SUFFIX F-10.5, F-10.9, F-10.23
    - SUM F-10.4, F-10.22
    - WEIGHT F-10.2, F-10.21
  - missing data F-10.2
  - multiple output files F-10.7
  - selecting statistics F-10.9
  - summary F-10.21
- Aggregation
  - commands to use F-1.4
- ALIKE
  - in PLOT command O-3.15
- ALL
  - in COUNTS command I-7.11
  - in DUPLICATES command F-10.13, F-10.24
  - in HIST command O-7.5
  - PPL operator P-2.19, P-2.26
- All possible subset regression B-4.21
- ALL.CASES
  - in COUNTS command I-7.17
- ALL.POSSIBLE
  - in REGRESSION command B-4.14
- ALLCAT
  - in FREQ command B-1.6
- ALLGROUPS
  - in AGGREGATE command F-10.22
- ALLGRP
  - in FREQ command B-1.7
- ALPHABET, with CHARACTERS
  - in PLOT command O-3.11
- Alternative hypothesis
  - in nonparametric statistics B-5.2
- AMONG
  - PPL operator P-2.18, P-2.26, P-9.31
- Analysis of variance
  - in Q.CLUSTER command A-3.4
  - in REGRESSION command B-4.5
- AND
  - PPL operator P-2.15, P-2.27
- Anderson-Darling test of normality I-7.1, I-7.13
- ANOVA **A-6.1**
  - @ symbol A-6.21
  - ABSORB A-6.44
  - BLOCK A-6.7, A-6.21, A-6.44

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- comparisons, multiple pre-planned A-6.27
- confounding A-6.17
- contrasts A-6.27
- COVARIATE A-6.44
- crossing A-6.10
- DENOMINATOR A-6.44
- DEPENDENT A-6.10, A-6.20, A-6.23, A-6.44
- design A-6.19
  - components A-6.19
  - expansion A-6.19, A-6.24
  - modification A-6.24
  - specification A-6.19
  - statements A-6.19
- effects A-6.19
  - balance of A-6.9
  - deleting A-6.22
  - grouping A-6.41
  - interaction A-6.4, A-6.6, A-6.7, A-6.9
  - main A-6.6
  - repeating A-6.21
  - subtraction of A-6.22
- ERROR.TERM A-6.11, A-6.20, A-6.44
  - completely randomized design A-6.4
  - default A-6.24
  - factorial design A-6.6
  - Latin square design A-6.10
  - randomized block design A-6.7
  - split-plot design A-6.13
  - stratum A-6.7
- experimental error
  - reduction of A-6.7
- factorial design
  - incomplete A-6.8
  - with repeated measures A-6.14
- factors A-6.19
- GROUPING.FACTORS A-6.44
- HYPOTHESIS A-6.44
- identifiers
  - BARTLETT A-6.36
  - DUNCAN A-6.36
  - DUNNETT A-6.37
  - LABELS A-6.49
  - LSD A-6.36
  - MOD.LSD A-6.36
  - SCHEFFI A-6.36
  - SNK A-6.36
  - TUKEY.A A-6.36
  - TUKEY.B A-6.36
- indexing factors
  - with nesting A-6.26
- least squares analysis A-6.17
- matching A-6.13
- MEANS A-6.20, A-6.44
- MODEL A-6.20, A-6.23, A-6.24, A-6.44
  - alternate specification A-6.10
- multiple dependent variables A-6.22
- nested design
  - implicit nesting A-6.26
  - partial nesting A-6.12
- NUMERATOR A-6.44
- one-way A-6.4
- operators
  - A-6.41
  - | A-6.6, A-6.41
  - | A-6.41
  - , A-6.19
  - ; A-6.3
  - ! A-6.6, A-6.41
  - ( A-6.11, A-6.41
  - \* A-6.6, A-6.41
  - / A-6.41
  - / A-6.11, A-6.41
  - // A-6.41
  - + A-6.6, A-6.19, A-6.41
  - = A-6.3, A-6.19
  - \$ A-6.4
- phrase A-6.19
- residual variance A-6.7, A-6.24
  - reduction of A-6.10
- RESPONSE A-6.44
- SHOW DESIGN A-6.20, A-6.44
- SHOW VARIABLES A-6.22, A-6.44
- SPLIT A-6.17
- stratum A-6.7, A-6.8
- subcommands
  - BLOCK A-6.51

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- BOX A-6.51
- COVARIATE A-6.51
- DEPENDENT A-6.50
- EDGES A-6.51
- ERROR.TERM A-6.51
- MEANS A-6.52
- MODEL A-6.50
- PLACES A-6.52
- SHOW A-6.52
- TREATMENT A-6.51
- V A-6.52
- Y.SUBSET A-6.52
- summary A-6.49
- synonyms A-6.44
- term A-6.19
- TREATMENT A-6.10, A-6.20, A-6.24,  
 A-6.44
- TRIAL.FACTOR A-6.44
- unbalanced data A-6.17
- variable arrangement  
 SPLIT A-6.17
- X A-6.44
- X.SUBSET A-6.44
- XY.SUBSET A-6.44
- Y A-6.22, A-6.44
- Y.SUBSET A-6.44
- ANY
  - PPL operator P-2.19, P-2.27
- Arc cosine function P-6.3
- Arc sine function P-6.3
- Arc tangent function P-6.3
- Arguments
  - defined I-2.15, **I-3.2**
  - in a macro P-12.3
- ARRAY
  - defining I-9.7
- ARRAY Commands
  - DEFINE.ARRAY P-8.7
  - DROP.ARRAY P-8.7
  - SHOW.ARRAYS P-8.7
  - summary P-8.28
- Arrays
  - multi-dimensional user-defined P-8.1
  - user defined P-8.7
- ASCENDING
  - in PLOT command O-3.10
- ASCII W-3.13
  - 5 character names F-2.17
- ASIN
  - PPL function P-6.3, P-6.21
- ASSIGN
  - in SURVEY command S-10.23, S-10.28
- Asterisk
  - in ANOVA command A-6.6, A-6.41
  - MATCHES meta-character P-9.21
  - multiplication operator P-2.12
- Asterisk, double
  - exponentiation operator P-2.12
- ATAN
  - PPL function P-6.3, P-6.21
- ATLEAST
  - in REGRESSION command B-4.16
- ATMOST
  - in REGRESSION command B-4.16,  
 B-4.17
- AUTOERASE **I-10.5**
  - summary I-10.10
- AUTOEXT **I-10.6**
  - summary I-10.10
- AUTOFILES **I-10.6**
  - summary I-10.10
- Autoregressive models
  - in REGRESSION command B-4.11
- AUTOSAVE I-10.1, I-10.3
  - directory I-10.7, I-10.9
  - introduction I-2.13
- AXIS
  - in BOX.PLOT B-6.5
- A22
  - in SJOIN command A-1.8
- B**
- B1 to B3
  - in TITLES command I-5.10, S-11.2
- Backslash
  - MATCHES meta-character P-9.21
- BACKUP
  - EDITOR instruction U-3.5

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

## BADINPUT

in F.COEF command A-5.6

## BALANCE I-1.3, W-1.3, S-1.21, **S-12.1**

identifiers

CONTROLS S-12.3

FREQS S-12.5

INITIAL.WEIGHT S-12.18

MARGINALS S-12.5

OUT S-12.3

PASSES S-12.5

THRESHOLD S-12.5

WEIGHT S-12.5

WEIGHT.NAME S-12.5

summary S-12.17

## BANNERS

in SURVEY command S-1.1, S-1.2,  
 S-1.27, S-3.27

resetting S-1.25

## Bar width

in BOXPLOT command O-6.5

## BAR.LIMITS

in HIST command O-7.4

## BAR.STEP

in HIST command O-7.5

## BARS

in HIST command O-7.4

## Bartlett

homogeneity of variance test A-6.36

## Bartlett's chi square

in CANONICAL.COR command A-2.4

## BASE

in COUNTS command I-7.8

in SURVEY command S-1.8, S-1.27,  
 S-5.20

## BASIC

in COUNTS command I-7.1

## BATCH I-1.5, I-1.11, U-2.1, **U-4.1**

computing I-1.5

error handling U-4.2, U-4.4

error processing I-3.12

output destination U-4.2

summary U-4.6

## Batch computing S-1.24

defined W-1.3

job processing W-5.13

## BEGINNING

EDITOR instruction U-6.6

Bernoulli distribution P-7.4

Between-group variance

in ANOVA command A-6.1

## BFONT

in SURVEY command S-7.5, S-7.14

Binary random number P-7.1

## BINOMIAL

in NP.TEST command B-5.4

summary B-5.45

Binomial distribution P-7.4

inverse P-7.5

Binomial test B-5.4

## BINS

in ROOTOGRAM B-6.11

## BISERIAL **B-3.9**, A-1.8

identifiers

NCV B-3.9, B-3.14

OUT B-3.9, B-3.14

ZERO B-3.9, B-3.14

summary B-3.14

## BLANK

in TITLES command I-5.10, S-11.2

PPL function P-9.10, P-9.24

## Blank

characters in input I-3.4

delimited input I-4.2

(space) delimited files W-2.10

## Blank lines in tables

controlling S-6.18

## BLANK.DELIMITER

in MAKE command I-4.10, F-3.6, F-3.8,  
 F-3.12

## BLANKS

in TEXTWRITER command P-11.7

## BLOCK

in ANOVA command A-6.7, A-6.21,  
 A-6.44

## Blocking

in ANOVA command A-6.6

latin square design A-6.10

## BODY



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in SURVEY command S-1.7, S-1.9,  
 S-1.27, S-5.12, S-5.24
- BORDER**
  - in BOXPLOT command O-6.5, O-6.11
  - in PLOT command O-5.3, O-5.13
  - in POSTSCRIPT command O-2.8,  
 O-2.11, O-2.19, O-2.20
  - in SURVEY command S-7.8, S-7.15
  - line width O-5.3
  - placement O-5.3
- BOTH**
  - in TTEST command B-2.5
- BOTTOM**
  - EDITOR instruction U-6.8
- Bottom titles
  - in TITLES command I-5.9, S-11.1
- BOTTOM.EDGE**
  - in BOXPLOT command O-6.12
  - in PLOT command O-5.1
  - in POSTSCRIPT.SETUP command  
 O-2.4, O-2.18
  - in SURVEY command S-6.24, S-7.3,  
 S-7.15
- Bounded Strings
  - in MAKE command F-3.9
- BOX**
  - in POSTSCRIPT command O-2.21
  - in POSTSCRIPT subcommands O-2.11
- BOX.PLOT**
  - EDA subcommand B-6.4
  - summary B-6.26
- Boxed format
  - in SURVEY command S-7.3
- BOXPLOT O-6.1**
  - bar width O-6.5
  - identifiers
    - BY O-6.2, O-6.11
    - LABELS O-6.2, O-6.11
    - PR O-6.1
  - subcommands
    - BORDER O-6.5, O-6.11
    - BOTTOM.EDGE O-6.12
    - BOX O-6.3, O-6.11
    - BY.LABEL O-6.12
    - COUNTS O-6.8, O-6.14
    - DIMENSION O-6.4
    - DIMENSION PAPER O-6.12
    - DIMENSION PLOT O-6.12
    - EDGES O-6.5, O-6.12
    - FOLD LABELS O-6.7, O-6.13
    - FONT O-6.7, O-6.13
    - FONT1 to FONT4 O-6.13
    - GRIDS O-6.6, O-6.14
    - GROUPS O-6.3, O-6.14
    - LEFT.EDGE O-6.12
    - LEGEND O-6.7, O-6.14
    - LEVELS O-6.3, O-6.14
    - LINE.WIDTH O-6.6, O-6.13
    - LOG10 O-6.3, O-6.14
    - MARGINS O-6.4, O-6.12
    - MAX.TICKS O-6.6, O-6.13
    - MEDIANS O-6.8
    - METHOD O-6.3, O-6.8, O-6.14
    - MINIMUM.CASES O-6.8, O-6.14
    - NOTCHES O-6.7, O-6.15
    - OMIT EMPTY PLOTS O-6.3, O-6.15
    - OUTLIERS O-6.3, O-6.15
    - PLOTS.PER.PAGE O-6.4, O-6.12
    - POSTSCRIPT O-6.12
    - RANGE O-6.9, O-6.13
    - RESET O-6.15
    - RESET RANGE O-6.9
    - RESET TICKS O-6.6
    - RIGHT.EDGE O-6.12
    - SCALE O-6.8, O-6.13
    - SCALE SEPARATE O-6.2, O-6.9,  
 O-6.13
    - SCALE TOGETHER O-6.9, O-6.13
    - SHOWPAGE O-6.4, O-6.12
    - SPACE O-6.5, O-6.12
    - SYMBOL O-6.8, O-6.13
    - TICKS O-6.6, O-6.14
    - TITLES O-6.8, O-6.15
    - TOP.EDGE O-6.12
    - WHISKERS O-6.7, O-6.14
- BPRINT B-3.6, A-5.5**
  - identifiers
    - DOTS B-3.6, B-3.15

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- LOWER B-3.15
- THRESHOLD B-3.6, B-3.15
- UPPER B-3.15
- summary B-3.15
- Brackets
  - MATCHES meta-character P-9.21
- BRANCH
  - conditional execution P-12.18
  - PPL instruction F-12.2
- BREAK
  - in COUNTS command I-7.15
  - in SPSS.OUT command F-2.8
  - in SURVEY command S-5.1, S-5.23
- Break characters
  - in SURVEY command S-1.15
- BUILD **F-5.1**
  - attributes
    - MUST F-5.7
  - formats
    - character F-5.2
    - numeric F-5.1
  - hierarchical data F-5.8
  - identifiers
    - BLANK.TABS F-5.12
    - COMPLETE F-5.13
    - DATA F-5.1
    - END.OF.DATA F-5.12
    - FILTER F-5.12
    - FIXED F-5.1
    - GROUPED F-5.5, F-5.6, F-5.13
    - LENGTH F-5.12
    - MINIMUM.GOOD F-5.13
    - NESTED F-5.8, F-5.13
    - PRINT F-5.3, F-5.13
    - PSTAT.FILE F-5.12
    - REPEATED.RECORDS F-5.7, F-5.13
    - REQUIRE F-5.7, F-5.13
    - SUB F-5.12
    - UNKNOWN.RECORDS F-5.7, F-5.13
    - VARF F-5.12
  - skipped records F-5.6
  - subcommands
- CASE.ID F-5.4
- GLOBAL F-5.4, F-5.14
- RECORD F-5.4, F-5.14
- RECORD.ID F-5.4
- VARF F-5.1
  - summary F-5.12
- BVAR.LABELS
  - in SURVEY command S-5.21, S-5.26
- BVAR.PER.PAGE
  - in SURVEY command S-3.1, S-3.28
- BY
  - in AGGREGATE command F-10.1, F-10.21
  - in BOXPLOT command O-6.2, O-6.11
  - in COLLATE command F-9.9, F-9.20
  - in COLLECT function P-8.20
  - in COMPARE command F-6.3, F-6.6, F-6.11
  - in COUNTS command I-7.9, I-7.17
  - in DUPLICATES command F-10.10, F-10.23
  - in LIST command I-6.13
  - in LOCATE.GROUPS command F-10.26, P-12.30
  - in MERGE command F-7.4, F-7.11
  - in PERCENTILES
    - command B-1.18
  - in PERCENTILES command B-1.11
  - in PLOT command O-3.19
  - in REGRESSION command B-4.8
  - in SAMPLE command S-12.11, S-12.19
  - in SEPARATE command F-6.8
  - in SORT command F-7.3, F-7.10
  - in SUBFILES command P-12.23, P-12.29
  - in SURVEY command S-10.7, S-10.28
  - in SURVIVAL command A-7.12
  - in UPDATE command F-11.3, F-11.11
- BY.LABEL
  - in BOXPLOT command O-6.12
- BY.N
  - in LIST command I-6.13
- BYPASS **U-2.13**
- Bytes
  - examine the bytes in an external file W-2.2

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

show the bytes in an external file. W-2.2

## C

C.TRANSPOSE I-6.5, P-2.23, A-1.1,  
 A-1.14, **A-1.15**

identifiers

COMMAS I-6.5, I-6.28

OUT I-6.5, I-6.28

CANONICAL.COR **A-2.1**

canonical coefficients A-2.6

canonical correlations A-2.4

identifiers

CARRY A-2.4, A-2.10

COR A-2.7, A-2.10

FULL A-2.7, A-2.10

LEFT A-2.2, A-2.10

LIMIT A-2.8, A-2.10

LIST A-2.5, A-2.11

OUT A-2.7, A-2.11

PREFIX A-2.7, A-2.11

RAW A-2.8, A-2.11

RIGHT A-2.2, A-2.11

STATS A-2.5, A-2.11

USE A-2.6, A-2.11

WEIGHT A-2.4, A-2.11

proportion of the total variance A-2.6

redundancy A-2.7

structure coefficients (loadings) A-2.6

summary A-2.10

CAPS

PPL function P-9.7, P-9.25

CARRY

in AGGREGATE command F-10.22

in CANONICAL.COR command A-2.4

in COLLECT function P-8.20

in Q.CLUSTER command A-3.3

in RANK command F-7.9

in SPLIT function P-8.13, A-6.17

in STANDARDIZE command B-1.14

Cascading files

in LOOKUP command F-9.15

CASE

in TEXTWRITER command P-11.6

Case selection

in LOOKUP command F-9.15

CASE.PERCENTAGES

in LIST command I-6.21

CASE.WEIGHTS

in TURF command I-8.29, W-5.10

CASES

in CONCAT command F-8.6, F-8.9

in LIST command I-6.21

in SAMPLE command S-12.11, S-12.19

PPL instruction P-2.1, P-2.3, P-2.24

Cases

defined W-2.5

CASES.PER.PAGE

in LIST command I-6.5

Case-wise deletion

in CORRELATE command B-3.6

Case, lower or upper I-3.2

CEILING

in SAMPLE command S-12.14, S-12.20

Ceiling function P-6.2

Cell contents

in SURVEY command S-1.9

CELL.CHI

in SURVEY command S-5.13, S-5.23

CELL.WIDTH

in SURVEY command S-1.13, S-1.27

Cells

per table S-10.13

CENTER

in LIST command I-6.4

in TITLES command I-5.11, S-11.3

PPL function I-6.4, P-9.25

Centering

labels S-5.6

variable names I-6.4

variable values I-6.4

CENTILES

in PERCENTILES command B-1.10

CHANGE

EDITOR instruction U-5.5, U-6.5

in MAKE command I-4.10, F-3.9, F-3.12

in MAKE.FIXED command F-4.5, **F-4.5**

PPL function P-9.10, P-9.25

CHARACTER

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- break point for labels S-1.16
- in SURVEY command S-6.22
  - BREAK S-1.16, S-1.27
  - NEWLINE S-6.7
  - PERCENTS S-6.8
  - SUBTOTALS S-6.4, S-7.11
  - TEST S-8.24
  - UNDERLINE S-6.10
  - VALUE.LABELS S-5.7
  - VARIABLE.LABELS S-6.6
  - ZERO S-5.12, S-6.6
- in TABFILE.IN command F-2.13
- in TEXTFILE.IN command I-4.2, I-4.13
- PPL function P-9.14, P-9.25
- Character constants
  - concatenation with && P-9.23, P-9.31
- Character data S-10.14
- Character to numeric
  - conversion of variables F-12.14
- Character variables
  - defining I-2.10
  - length I-2.1
- CHARACTER.SET
  - in POSTSCRIPT command O-2.20
  - in POSTSCRIPT.SETUP command O-2.17
  - in SURVEY command S-7.1
  - ISO O-2.5
- CHARACTERS FOR PLOT
  - in PLOT command O-3.11
- CHAREX
  - PPL function P-9.14, P-9.26
- CHARS
  - in XY.PLOT B-6.15
- CHECK I-9.5, I-9.9, I-10.4, **F-12.1**, P-1.3, P-1.6
  - identifiers
    - MAX I-9.9, F-12.16
    - RESET I-9.9, F-12.16
  - in JOIN command F-9.3, F-9.22
  - in SAVE.LABELS command I-5.8, S-11.10
  - summary F-12.16
- CHECK.ALL
  - in DUPLICATES command F-10.14, F-10.25
- CHECK.CL
  - in INTERLEAVE command F-7.7
- CHECK.LABELS I-5.1, S-11.10
  - identifiers
    - PSTAT.FILE I-5.9, I-5.16, S-11.11, S-11.15
    - summary I-5.16, S-11.14
- CHECK.RL
  - in INTERLEAVE command F-7.7
- CHECK.SOME
  - in DUPLICATES command F-10.14, F-10.25
- CHI
  - in NP.TEST command B-5.10, B-5.11
  - in SURVEY command S-8.11, S-8.24
- CHI.SQUARE
  - in NP.TEST command B-5.8
  - summary B-5.46
- Chi-square
  - contribution of cell S-5.13
  - distribution P-7.4
  - in FREQ command B-1.7
  - in SURVEY command S-8.11
  - inverse P-7.5
  - test B-5.8
- CHOLESKY **A-1.7**
  - identifiers
    - OUT A-1.7
    - summary A-1.10
- CHOP
  - in CONCAT command F-8.6, F-8.9
- CLAG
  - character function P-6.8
  - PPL function P-9.23
- CLEANCOR **A-5.3**
  - identifiers
    - OUT A-5.3
    - THRESHOLD A-5.3
    - summary A-5.7
- CLOSE **U-2.5**, U-2.8, U-2.13
- CLOSE command O-2.7
- Cluster analysis A-3.1

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- see Q.CLUSTER
- COARSE.GROUP
  - summary B-3.15
- COCHRAN
  - in NP.TEST command B-5.37
  - summary B-5.58
- Cochran Q test B-5.37
- CODED.TABLE
  - EDA subcommand B-6.19
  - summary B-6.26
- Coefficient
  - in REGRESSION command B-4.1, B-4.6
- Coefficient of variation B-1.2
  - in COUNTS command I-7.1, I-7.13
- COLLATE **F-9.5**
  - hierarchical files F-9.10
  - identifiers
    - BY F-9.9, F-9.20
    - DOWN F-9.6, F-9.20
    - FILL F-9.6, F-9.20
    - LEFT.EXTRA F-9.7, F-9.20
    - OUT F-9.7, F-9.20
    - REPEAT F-9.10, F-9.21
    - RIGHT.EXTRA F-9.7, F-9.21
    - SUBSET F-9.9, F-9.21
    - TOL F-9.9, F-9.21
    - UP F-9.6, F-9.21
    - USE.MISSING F-9.21
  - linking variables F-9.9
  - summary F-9.20
- COLLECT
  - in AGGREGATE command F-10.5, F-10.22
  - PPL function I-9.10, P-8.29
    - BY option P-8.20
    - CARRY option P-8.21
    - COLLECT counter P-8.20
    - complex usage P-8.22
    - example P-9.17
    - INDEX option P-8.21
    - SORT option P-8.21
- COLOR
  - in POSTSCRIPT command O-2.21
- Color
  - customizing O-2.21
  - for fonts and borders O-2.5
  - setting in plots O-5.5
- Column variables
  - in SURVEY command S-1.1
- COLUMN.VARIABLE
  - in CODED.TABLE B-6.20
  - in MEDIAN.POLISH B-6.22
- COLUMNS
  - in PLOT command O-3.4
- Columns per page
  - controlling S-3.1
  - size limitations S-10.13
- Combination size
  - TURF
    - maximum size I-8.26
- COMBINATIONS I-9.7
  - PC menus W-2.3
  - PPL function P-6.11, P-6.22
- Combinations
  - calculating W-5.10
- COMBINE
  - in COUNTS command I-7.6
  - in SURVEY command S-4.21
  - small values automatically S-4.14
  - with exceptions S-4.16
- Combining
  - cases F-1.2
  - variables F-1.3
- Comma delimited
  - files W-2.10
  - tables S-6.14
- Comma delimited input I-4.2
- COMMAND
  - EDITOR instruction U-6.3
  - in UNMAKE command F-2.10, F-2.16
- Command
  - continuation of I-2.5, I-2.15, I-3.4
  - files I-2.3
  - output I-3.8
  - print W-3.7, W-3.8
  - processing I-3.7
  - storage area limits S-10.13
  - summary I-2.15

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- summary for new users W-2.15
- syntax I-2.5, I-3.1, I-3.14
- Command files W-5.13
  - executing W-2.3
- Command.Print
  - file W-2.2
- COMMAND.WIDTH U-2.13
- COMMAS
  - in C.TRANSPOSE command I-6.5
  - in LIST command I-6.10
  - in SURVEY command S-6.11, S-6.23
- Commas
  - in commands I-2.15, I-3.4
- Comments P-3.20
  - in PPL clauses P-11.6
  - within or between commands P-3.14
- COMMON
  - in CONCAT command F-8.3, F-8.9
- COMPACT
  - in SURVEY command S-1.13, S-6.12, S-6.23
- COMPARE **F-6.2**, F-6.2, F-6.11, P-1.3, P-1.6
  - identifiers
    - BY F-6.3, F-6.6, F-6.11
    - EXACT F-6.6, F-6.11
    - FILL F-6.6
    - NO FILL F-6.11
    - OUT F-6.4, F-6.11
    - VERBOSITY F-6.5
  - P-STAT system files P-1.6
- Comparing files F-6.2
- COMPARISON.VALUES
  - in MEDIAN.POLISH B-6.23
- Comparisons
  - multiple pre-planned in ANOVA command A-6.27
- COMPLETE
  - in CORRELATE command B-3.6
  - in REGRESSION command B-4.9
- COMPRESS
  - PPL function P-9.11, P-9.26
- COMPRESS FORMAT
  - in SURVEY command S-7.12, S-7.15
- Compression of data files I-10.3
- COMPUTE S-8.24
  - in SURVEY command S-8.2, S-8.24
- CONCAT W-2.4, **F-8.1**
  - identifiers
    - CASES F-8.6, F-8.9
    - CHOP F-8.6, F-8.9
    - COMMON F-8.3, F-8.9
    - DES F-8.7, F-8.9
    - FILL F-8.1, F-8.9
    - MAX F-8.6, F-8.9
    - MIN F-8.6, F-8.9
    - ORIGIN F-8.7, F-8.9
    - OUT F-8.1, F-8.10
    - SAME F-8.3, F-8.10
    - TEMPLATE F-8.3, F-8.10
    - WEIGHT F-8.7, F-8.10
  - output file data types F-8.6
  - renaming variables F-8.2
  - summary F-8.9
  - variable lengths F-8.6
  - variable selection F-8.1
- Concatenation
  - of files on-the-fly P-3.4
  - operator // P-9.4
  - operator /// P-9.5
- Concomitant variance B-3.3
- CONCORDANCE
  - in NP.TEST command B-5.40
  - summary B-5.59
- Conditional execution
  - BRANCH P-12.18
- Confidence intervals
  - in COUNTS command I-7.1
- Confounding
  - in ANOVA command A-6.17
- Constant of proportionality
  - in REGRESSION command B-4.1
- CONSTRAIN
  - in TURF command W-3.12
- CONTAINS
  - PPL operator P-9.4, P-9.32
- CONTENTS
  - in SURVEY command S-10.28

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- Continuation of commands I-2.5, I-2.15,  
 I-3.4
- Contrast  
 in ANOVA command A-6.27
- CONTRASTS  
 in NP.TEST command B-5.35
- CONTROL COLUMN ORDER USING LABELS  
 in SURVEY command S-3.4, S-3.27
- CONTROL COLUMN RANK  
 in SURVEY command S-3.5, S-3.27
- CONTROL ROW ORDER  
 in SURVEY command S-2.6
- CONTROL ROW ORDER OFF  
 in SURVEY command S-2.6
- CONTROL ROW ORDER USING LABELS  
 in SURVEY command S-2.22
- CONTROL ROW RANK  
 in SURVEY command S-2.6, S-2.22
- Control words  
 in TEXTWRITER command P-11.8
- Controlling pagination O-5.2
- CONTROLS  
 in BALANCE command S-12.3
- CONVERGE  
 in Q.CLUSTER command A-3.8
- COPY  
 EDITOR instruction U-3.5, U-6.18
- COR  
 in CANONICAL.COR command A-2.7  
 in PROMAX command A-5.5
- COR.SIG B-3.11**  
 identifiers  
 LEVEL B-3.11, B-3.16  
 N B-3.11, B-3.16  
 NMAT B-3.11, B-3.16  
 OUTCOR B-3.11, B-3.16  
 OUTSIG B-3.11, B-3.16  
 OUTSIG1 B-3.11, B-3.16  
 summary B-3.15
- Corrected sum of squares  
 in COUNTS command I-7.1, I-7.13
- CORRELATE W-2.3, B-3.1, **B-3.5**, A-1.8  
 asymmetric files B-3.8
- biserial B-3.1, B-3.9
- canonical correlation A-2.1
- case-wise deletion B-3.6
- continuous variable B-3.1
- cross products B-3.6
- dichotomous variables B-3.1
- identifiers  
 COMPLETE B-3.6, B-3.13  
 COV B-3.6, B-3.13  
 CROSS B-3.6, B-3.13  
 DES B-3.6, B-3.13  
 MISSING B-3.13  
 NMAT B-3.6, B-3.13  
 NO LIST B-3.5, B-3.13  
 OUT B-3.14  
 ROWS B-3.8, B-3.14  
 STATS B-3.14  
 WEIGHT B-3.7, B-3.14
- missing data B-3.6
- pairwise deletion B-3.6
- partial A-1.7
- phi coefficient B-3.1, B-3.10
- point biserial B-3.1, B-3.10
- printing a matrix B-3.6
- replacing missing scores with mean  
 B-1.14
- significance level B-3.11
- Spearman B-3.1
- summary B-3.13
- tetrachoric B-3.1, B-3.10
- using complete data B-3.6
- variance/covariance matrix B-3.6
- weighting options B-3.6
- Corrupted files  
 CHECK I-10.4
- COS  
 PPL function P-6.3, P-6.20
- COSINE  
 in PROMAX command A-5.5
- Cosine function P-6.3
- COUNT  
 in AGGREGATE command F-10.3,  
 F-10.7, F-10.22  
 in ROOTOGRAM B-6.11

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in SURVEY command S-2.22, S-3.15
- COUNT.GOOD
  - PPL function P-6.7, P-6.23, P-9.3, P-9.30
- COUNT.MACROS **P-12.11**, P-12.28
- COUNTS I-7.1, **I-7.1**, W-1.3, W-2.3, W-5.1, F-12.11, S-8.21, S-10.15
  - changing percentage base I-7.8
  - computing percentiles I-7.14
  - identifiers
    - ALL I-7.11, I-7.22
    - ALL.CASES I-7.17, I-7.24
    - BASE I-7.8, I-7.22, I-7.24
    - BASIC I-7.1, I-7.22
    - BREAK I-7.15, I-7.23
    - BY I-7.17, I-7.24
    - COMBINE I-7.6, I-7.20
    - DOWN I-7.15, I-7.23
    - EXACT I-7.6, I-7.20
    - FREQUENCIES I-7.15, I-7.23
    - HARMONICS I-7.1, I-7.12, I-7.22
    - INTERLEAVE I-7.24
    - LABELS I-7.4, I-7.20
    - LIST I-7.3
    - LIST.BY I-7.3, I-7.21
    - MAX I-7.15, I-7.23
    - METHOD.DEFAULT I-7.14
    - METHOD.FIRST I-7.14
    - METHOD.GROUPED I-7.14
    - METHOD.NPLUS1 I-7.14
    - MISSINGS I-7.1, I-7.10, I-7.23
    - MOMENTS I-7.1, I-7.12, I-7.23
    - MR.GROUPS I-7.21
    - NO INTERLEAVE I-7.24
    - NO LIST I-7.20
    - NORM I-7.1, I-7.13
    - NORMALS I-7.23
    - NS I-7.1, I-7.23
    - OUT I-7.3, I-7.21
    - PCT.PLACES I-7.15, I-7.23
    - PERCENTILES I-7.1, I-7.13, I-7.23
    - PR I-7.21
    - RESET I-7.1, I-7.10, I-7.23
    - RESULTS I-7.24
    - SHOW.COMMAND I-7.21
- STATS I-7.1, I-7.10, I-7.23
- TITLES I-7.21
- UP I-7.15, I-7.23
- USE I-7.4, I-7.21
- VALUES I-7.1, I-7.10, I-7.23
- VERBOSE I-7.17, I-7.24
- W.FREQUENCIES I-7.15, I-7.23
- WEIGHT I-7.4, I-7.21
  - in BOXPLOT command O-6.8, O-6.14
  - in NP.TEST command B-5.5, B-5.7
  - printing the output I-7.4
  - summary I-7.19
  - table of codes I-7.25
  - titles I-7.4
- COV
  - in CORRELATE command B-3.6
- COVARIATE
  - in ANOVA command A-6.44
- Cramer's V S-8.13
- CREATE
  - in SPLIT function P-8.14
  - in ANOVA command A-6.17
  - in SURVEY command S-3.27
  - multiple response banner variables S-3.14
- Create
  - a new variable W-5.4
- CROSS
  - in CORRELATE command B-3.6
  - in TET command B-3.11
- Cross products
  - in CORRELATE command B-3.6
- CROSS.COMPARE
  - in SURVEY command S-3.19, S-3.28
- Crosstabulation I-1.3, W-1.2, W-2.2
- CR, LF and CRLF
  - in TABFILE.OUT command F-2.8
- CSV
  - PC/Windows extension I-4.2
- CTET
  - in TET command B-3.11
- CUBE
  - in EDA command B-6.3
- CUBE.ROOT
  - in EDA command B-6.3



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

## CUMULATIVE

in HIST command O-7.3

Currency sign I-2.15

## CURRENT

PPL instruction I-10.4, P-1.4, P-1.6

version of P-STAT system file I-10.14

CURRENT.DATE function P-10.4, P-10.20

Custom labelling S-6.1

## CVAL

PPL function P-9.14, P-9.26

CV, coefficient of variation B-1.2

## CYCLE

in SPLIT function P-8.17

C, comment command U-2.13

## D

### DASHES

in LIST command I-6.9

### DATA

EDITOR instruction U-6.3, U-7.1

in UNMAKE command F-2.10, F-2.16

### Data

appropriate for SURVEY command S-1.4

cleaning P-3.8, P-8.11

### DATA.ONLY

in LIST command I-6.4

### DATE.AXIS

in PLOT command O-4.7, O-4.8

DATE.LANGUAGE P-10.14, P-10.23

DATE.ORDER P-10.14, P-10.24

Dates P-10.1– P-10.13

adding P-10.9, P-10.21

changing P-10.11, P-10.23

difference between P-10.12, P-10.23

extracting P-10.10, P-10.22

logical operators P-10.16, P-10.24

simple functions P-10.3

DAY.MONTH.YEAR P-10.3

DAY.YEAR.MONTH P-10.3

MONTH.YEAR.DAY P-10.4

YEAR.DAY.MONTH P-10.4

YEAR.MONTH.DAY P-10.4

subtracting P-10.9, P-10.21

DAY.WITHIN.WEEK function P-10.7,

P-10.21

DAY.WITHIN.YEAR function P-10.7,  
 P-10.21

## DAYS

PPL function P-10.20

## DECILES

in PERCENTILES command B-1.10

Decimal places function P-6.10

## DECIMAL.COMMA

in SURVEY command S-6.22

in TABFILE.IN command F-2.13

in TABFILE.OUT command F-2.14

in TEXTFILE.IN I-4.13

## DECREASE

PPL instruction P-2.10, P-2.24

## DEF

in PLOT command O-5.13

in SURVEY command S-10.28

DEFAULT.SETTINGS I-9.3, S-1.20, **U-2.2**,  
 U-3.2

identifiers

ECHO U-2.2, U-2.14

LINES U-2.2, U-2.14

OUTPUT.WIDTH U-2.2, U-2.14

PAGE.CHARACTER U-2.2, U-2.14

UNDERLINE U-2.14

VBAR U-2.2, U-2.14

summary U-2.14

## DEFINE

in SURVEY command S-4.2, S-4.21,  
 S-6.4

subtotals S-4.5

DEFINE.ARRAY **P-8.7**, P-8.28

## DEFINE.NET

in SURVEY command S-4.2, S-4.22

Defining columns in SURVEY command  
 S-3.1

Definition file

in SURVEY command S-10.1

## DEFINITIONS

in MAKE command I-4.5, I-4.11, F-3.3,  
 F-3.11

in MAKE.FIXED command F-4.2, F-4.8

Degrees of freedom

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in REGRESSION command B-4.5
- DEL
  - in MAKE command I-4.12, F-3.12
- DELETE
  - EDITOR instruction U-5.5, U-6.8, U-7.5
  - in UPDATE command F-11.6, F-11.8, F-11.11
  - PPL instruction P-2.14, P-2.24
- DELETE.INSERT
  - in UPDATE command F-11.5
- DELIMITER
  - in MAKE command I-4.7, F-3.6
  - in TABFILE.IN command F-2.13
  - in TABFILE.OUT command F-2.8
  - in TEXTFILE.IN I-4.2
  - in TEXTFILE.IN command I-4.13
  - in UNMAKE command F-2.11, F-2.16
- DELTA
  - in POSTSCRIPT.SETUP command O-2.18
  - in TEXTWRITER.SETUP command O-2.6
- DENOMINATOR
  - in ANOVA command A-6.44
- DEPENDENT
  - in ANOVA command A-6.10, A-6.23, A-6.24, A-6.44
  - in REGRESSION command B-4.2, B-4.7
- Dependent variables
  - in ANOVA command A-6.1
  - multiple A-6.22
- DES
  - in CONCAT command F-8.7, F-8.9
  - in CORRELATE command B-3.6
  - in HIST command O-7.3
  - in MODIFY command F-6.1, F-6.12, P-3.2, B-1.2, B-1.16
  - in STANDARDIZE command B-1.14, B-1.18
- DES.1
  - in TTEST command B-2.5
- DES.2
  - in TTEST command B-2.5
- DESCENDING
  - in PLOT command O-3.10
- Description files W-2.3, F-6.1
  - combining B-1.3
  - weighting B-1.2
- Descriptive statistics I-7.1, B-1.1
  - for subgroups B-1.12
- Design
  - in ANOVA command expansion A-6.19 statements A-6.19
- DET
  - in INVERT command A-1.6
- DIALOG **P-12.19**, P-12.31, U-2.10
  - example U-2.10
- Dichotomous variables B-3.1
- DIF
  - PPL function P-6.8, P-6.22
- DIF function P-6.9
- Difference function P-6.8
- Digit extraction function P-6.10
- DIMENSION
  - in BOXPLOT command O-6.4, O-6.12
  - in PLOT command O-5.1, O-5.14
- Directory
  - for all files PSFILES W-2.3
  - for external data W-2.3
  - for P-STAT system files W-2.3
  - selection W-3.1
- DISCRETE
  - in NP.TEST command B-5.13
- DISCRIM **A-4.1**
  - defining groups A-4.2
  - forcing variables A-4.5
  - identifiers
    - F.DELETE A-4.5
    - FORCE A-4.5, A-4.11
    - FUN A-4.4, A-4.11
    - IN.FUN A-4.4, A-4.11
    - MAX A-4.5, A-4.11
    - MIN A-4.5, A-4.11
    - OUT A-4.4, A-4.11
    - PRIOR A-4.4, A-4.12
    - PROB A-4.5, A-4.12

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- STEP A-4.1
  - interactive options A-4.12
  - prior probabilities A-4.4
  - size constraints A-4.1
  - stepping A-4.4, A-4.5
  - summary A-4.11
  - types of runs A-4.1
- DISPLAY
  - in MEDIAN.POLISH B-6.23
- Display
  - PC Windows
    - menu W-2.2
- Distributed lag models
  - in REGRESSION command B-4.11, B-4.12
- Distribution functions P-7.4
  - inverse P-7.5
- Distributions, tests of B-5.11
- DIVIDE
  - in SURVEY command S-9.1
- Division operator / P-2.12
- DO loops P-5.1–P-5.11
  - PPL instruction P-5.22
- DOLLAR
  - in LIST command I-6.10
- Dollar sign I-2.15
- DOTS
  - in BPRINT command B-3.6
- DOUBLE
  - in LIST command I-6.10
  - in SURVEY command S-8.24
- Double slash
  - in ANOVA command A-6.41
  - PPL operator P-9.4
- DOWN
  - EDITOR instruction U-6.8
  - in COLLATE command F-9.6, F-9.20
  - in COUNTS command I-7.15
  - in LOCATE.GROUPS command F-10.26, P-12.30
  - in MERGE command F-7.4, F-7.11
  - in SORT command F-7.3, F-7.10
  - in SUBFILES command P-12.23, P-12.29
  - in SURVIVAL command A-7.9
    - in UPDATE command F-11.3, F-11.11
- DRIFT
  - in Q.CLUSTER command A-3.8
- DROOT
  - in FACTOR command A-5.3
- DROP
  - in MAKE command I-4.10, F-3.6, F-3.12
  - PPL instruction P-2.1, P-2.3, P-2.24
- DROP.ARRAY **P-8.7**, P-8.28
- DROP.LEAD.BLANKS
  - in MAKE command F-3.8, F-3.13
- DROP.P.VECTOR **P-8.29**
- Dummy variables S-2.13
  - creating P-6.4, P-6.15
  - in the banner S-10.25
  - recoding S-3.11
  - recoding into one variable P-6.5
- Dummy.variables
  - in the banner S-3.9
- DUNCAN
  - multiple range test A-6.36
- DUNNETT
  - comparing treatment means A-6.37
- DUPLICATES W-2.4, F-1.6, **F-10.9**
  - character variables F-10.17
  - identifiers
    - ALL F-10.13, F-10.24
    - BY F-10.10, F-10.23
    - CHECK.ALL F-10.14, F-10.25
    - CHECK.SOME F-10.14, F-10.25
    - FIRST F-10.24
    - FIRST.G F-10.12, F-10.24
    - HIGH.TEST F-10.14, F-10.25
    - LAST F-10.10, F-10.15, F-10.24
    - LAST.G F-10.12, F-10.24
    - LOW.TEST F-10.14, F-10.25
    - MAX F-10.17, F-10.26
    - MAX.G F-10.17, F-10.26
    - MEAN F-10.15, F-10.17, F-10.25
    - MEAN.G F-10.16, F-10.17, F-10.25
    - MIN F-10.17, F-10.25
    - MIN.G F-10.17, F-10.26
    - NO REPORT F-10.18
    - NONE F-10.12, F-10.15, F-10.24

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

NULL F-10.15, F-10.25  
 ONLY F-10.12, F-10.15, F-10.25  
 OUT F-10.10, F-10.18, F-10.23  
 PREFIX F-10.17, F-10.26  
 REPORT F-10.12, F-10.23  
 SEQUENCE F-10.13, F-10.24  
 SINGLE F-10.24  
 SIZE F-10.13, F-10.24  
 SUFFIX F-10.17, F-10.26  
 SUM F-10.17, F-10.25  
 SUM.G F-10.17, F-10.25  
 USE.MISSING F-10.15, F-10.24  
 summary F-10.23  
 system variable .DUPMAX. F-10.18  
 DURWAT B-4.1  
 identifiers  
   OUT B-4.26  
 summary B-4.26  
**E**  
 E.ADD **A-1.2**  
 identifiers  
   OUT A-1.2  
 summary A-1.10  
 E.DIVIDE **A-1.3**  
 identifiers  
   OUT A-1.2  
 summary A-1.11  
 E.MULTIPLY **A-1.3**  
 identifiers  
   OUT A-1.2  
 summary A-1.11  
 E.SUBTRACT **A-1.3**  
 identifiers  
   OUT A-1.2  
 summary A-1.12  
 EACH  
   in HIST command O-7.5  
 ECHO P-12.14, **U-2.14**  
   in DEFAULT.SETTINGS command  
     U-2.2  
   in PRINTER.SETTINGS command U-2.2  
   in SURVEY command S-1.28  
 Econometrics

LAG, DIF functions P-6.8  
 EDA **B-6.1**  
 identifiers  
   LABELS B-6.1, B-6.24  
   OUT B-6.1, B-6.24  
 subcommands  
   AGAIN B-6.3, B-6.24  
   BOX.PLOT B-6.26  
   CODED.TABLES B-6.26, B-6.27  
   CUBE B-6.3, B-6.25  
   CUBE.ROOT B-6.3, B-6.25  
   HELP B-6.3, B-6.24  
   LOG B-6.3, B-6.25  
   LOG10 B-6.3, B-6.25  
   MEDIAN.POLISH B-6.28  
   NO TRANSFORMATIONS B-6.3  
   POWER B-6.3, B-6.25  
   PRESERVE.ORDER B-6.3, B-6.25  
   RECIP.ROOT B-6.3, B-6.25  
   RECIP.SQUARE B-6.3, B-6.25  
   RECIPROCAL B-6.3, B-6.25  
   RESET B-6.3, B-6.25  
   RESISTANT.LINE B-6.29  
   RESISTANT.SMOOTH B-6.30  
   ROOTOGRAM B-6.30  
   SHOW.VARIABLES B-6.3, B-6.25  
   SQUARE B-6.3, B-6.25  
   SQUARE.ROOT B-6.3, B-6.26  
   STEM.AND.LEAF B-6.31  
   XY.PLOT B-6.32  
 subcommands: procedures  
   BOX.PLOT B-6.4  
   CODED.TABLE B-6.19  
   LETTER.VALUES B-6.7  
   MEDIAN.POLISH B-6.21  
   RESISTANT.LINE B-6.15  
   RESISTANT.SMOOTH B-6.17  
   ROOTOGRAM B-6.10  
   STEM.AND.LEAF B-6.8  
   XY.PLOT B-6.13  
 summary B-6.24  
 transformations B-6.2  
**EDGES**  
 in BOXPLOT command O-6.5, O-6.12

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in PERCENTILES command B-1.10
- in PLOT command O-3.10
- in POSTSCRIPT command O-2.20
- Edit file
  - changing U-3.4
  - saving and restoring U-6.15
  - structure U-5.4, U-6.1
- EDITOR **U-5.1**, U-6.1, U-6.21, U-7.1
  - building a run U-7.2
  - command U-7.2
  - full screen U-5.4
    - insert text U-5.7
    - replace text U-5.7
  - full screen mode U-5.6
  - input U-7.1
  - instructions
    - AGAIN U-6.8
    - BACKUP U-3.5
    - BEGINNING U-6.6
    - BOTTOM U-6.8
    - CHANGE U-5.5, U-6.5
    - COPY U-3.5, U-6.18
    - DATA U-6.3
    - DELETE U-5.5, U-6.8, U-7.5
    - DOWN U-6.8
    - EDITOR U-5.3, U-6.2
    - END U-6.6
    - EXECUTE U-5.4, U-6.6
    - EXPORT U-6.16
    - FIRST U-6.8, U-7.6
    - GET U-6.16
    - HELP U-5.1, U-7.1
    - IMPORT U-6.16
    - INPUT U-6.8, U-7.1
    - KEEP U-6.8
    - LAST U-6.8
    - LOCATE U-6.8
    - MOVE U-6.18
    - NEXT U-6.8
    - OLD U-6.5
    - QUIT U-5.4
    - REPLACE U-6.20
    - RESTORE U-3.5, U-6.16
    - RETURN U-7.6, U-7.8
- SQUEEZE U-6.18
- SYNTAX U-6.8, U-7.4
- TOP U-6.7, U-7.4
- TYPE U-6.8, U-7.6
- UP U-6.8
- VALIDATE U-6.20
- WHERE U-6.13, U-7.1, U-7.8
- X U-5.4, U-6.6
- Y1 U-6.15
- Y2 U-6.15
- Z full screen mode U-5.6
- interactive usage U-5.1
  - summary U-5.8
- mixed case entries U-5.7
- moving the pointer U-6.7
- prompt messages U-5.2, U-7.2
- single-letter controls U-6.7
- syntax checking U-7.4
- Z full screen mode U-6.24
- EF
  - in ROTATE command A-5.3
- EIGEN **A-1.8**
  - identifiers
    - ROOTS A-1.8
    - VECTORS A-1.8
  - summary A-1.10
- Eigenvalues
  - in CANONICAL.COR command A-2.4
- Empty tables
  - omitting from SURVEY output S-6.20
- EMPTY.TABLES
  - in SURVEY command S-6.20
- ENCAPSULATE
  - in POSTSCRIPT.SETUP O-2.6
  - in POSTSCRIPT.SETUP command O-2.18
- Encapsulated PostScript (EPS) O-2.13
- Enclosures
  - in MATCHES operator P-9.21
- END **I-2.5**, I-2.16, I-3.1, W-2.12, U-2.14
  - EDITOR instruction U-6.6
  - ending a P-STAT run I-2.5
  - summary I-10.10
- End of case character

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- see EOC
- END.OF.CASE
  - in UNMAKE command F-2.11, F-2.16
- ENDDO
  - PPL instruction P-5.23
- ENDIF
  - PPL instruction P-5.25
- ENDMACRO **P-12.1**, P-12.11, P-12.28
- ENDSUBFILES **W-5.15**, **P-12.23**, P-12.23
  - summary P-12.30
- Environment variable
  - PSTART U-2.10
- Environment variables
  - PSAUTO I-1.8, W-1.8
  - PSDATA I-1.8, W-1.8
  - PSFILES I-1.8, W-1.7
  - PSHELP I-1.7, W-1.7
  - PSKEY I-1.7, W-1.7
  - PSTART I-1.8, W-1.8
  - PSTEMP I-1.8, W-1.8
- EOC
  - in MAKE command I-4.9, I-4.12, F-3.6, F-3.12
  - in MAKE.FIXED command F-4.6, F-4.8
- EOF
  - in TABFILE.OUT command F-2.8
- EPS
  - encapsulated PostScript output O-2.18
- EQ
  - in NP.TEST command B-5.6
  - PPL operator P-2.14, P-2.26
- EQUALCAT
  - in FREQ command B-1.6
- EQUATE **I-10.8**
  - summary I-10.11
- ERASE **I-10.5**, W-2.3
  - summary I-10.11
- ERASE.AUTOSAVE **I-10.5**
  - summary I-10.11
- ERASE.CURRENT **I-10.5**, W-2.3
  - summary I-10.11
- ERASE.EDIT.FILE **U-3.4**, U-3.7
- ERASE.EXTERNAL I-10.6, W-2.3
  - summary I-10.11
- ERASE.PREVIOUS I-10.5, W-2.3
  - summary I-10.11
- ERROR **U-2.15**
  - general identifier U-2.6
- ERROR.TERM
  - in ANOVA command A-6.11, A-6.20, A-6.44
  - completely randomized design A-6.4
  - default A-6.24
  - factorial design A-6.6
  - latin square design A-6.9
  - nested design A-6.11
  - randomized block design A-6.7
  - split-plot design A-6.13
  - stratum A-6.7
  - within-cells variance A-6.4
- ERROR.UNIT **U-2.15**
- Errors
  - data correction
    - commands to use F-1.3
  - handling in PostScript run O-5.7
  - in batch run U-4.2, U-4.4
  - processing I-3.11
- Escape characters
  - in MATCHES operator P-9.21
- Escape codes, passing P-9.14
- ETR
  - in ROTATE command A-5.3
- EUCLIDEAN
  - in Q.CLUSTER command A-3.8
- European representation
  - see DECIMAL.COMMA F-2.13, F-2.14
- EXACT
  - in COMPARE command F-6.6, F-6.11
  - in COUNTS command I-7.6
  - in LOOKUP command F-9.19, F-9.23
  - in MAP command F-12.4
  - in MERGE command F-7.6, F-7.11
  - in PLOT command O-3.6
  - in SORT command F-7.2, F-7.10
  - in SURVIVAL command A-7.19
- Exact string comparisons P-2.14
- EXAMINE I-1.2, W-1.2, U-1.8, U-1.11
  - identifiers

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- EOC U-1.11
  - the bytes in a file W-2.2
- EXCEL W-1.5, W-3.1, F-2.1
- Excel I-1.1
  - Tab delimited files I-10.3
- EXCEPT
  - in SURVEY command S-4.15, S-4.22
- Exclamation point
  - in ANOVA command A-6.6, A-6.41
- EXCLUDE MISSING MEANS VALUES
  - in SURVEY command S-1.23, S-1.28
- EXCLUDE SMALL SUBTOTALS
  - in SURVEY command S-4.18, S-4.22
- EXCLUDE SOME STUB VALUES
  - in SURVEY command S-2.2, S-2.22
- EXECUTE
  - EDITOR instruction U-5.4, U-6.6
- Exit from
  - P-STAT W-2.2, W-2.12
- EXITDO
  - PPL instruction P-5.22
- EXP
  - PPL function P-6.3, P-6.20
- EXPAND
  - in LIST command I-6.3
  - PPL function P-6.11
- EXPECTED
  - in NP.TEST command B-5.10
- EXPECTED.VALUE
  - in SURVEY command S-5.13, S-5.23
- Exponentiation function P-6.3
- Exponentiation operator \*\* P-2.12
- EXPORT
  - EDITOR instruction U-6.16
- Export data
  - ASCII text
    - UNMAKE W-2.4
  - SPSS export format W-2.4
- Extended variable labels I-5.6, S-11.8
  - in LIST command I-6.8
  - in SURVEY command S-1.2, S-1.14
  - positioning S-5.25
  - using in SUBSTITUTE.XL command
    - F-12.11
- EXTENDED.LABELS
  - in TEXTFILE.IN I-4.3, I-4.13
- EXTRA
  - in SEPARATE command F-6.10
- EXTREMES
  - in CODED.TABLE B-6.21
- F**
- F distribution P-7.4
  - inverse P-7.5
- F test
  - in ANOVA command A-6.4
  - in DISCRIM command A-4.2
  - in FREQ command B-1.7
  - in REGRESSION command B-4.5
- F.CHI
  - in SURVEY command S-1.7
- F.COEF A-5.5**
  - identifiers
    - BADINPUT A-5.6
    - FACTOR A-5.5
    - FC A-5.6
    - MEAN A-5.6
    - PMULT A-5.6
    - SDATA A-5.5
  - size constraints A-5.6
  - summary A-5.8
- F.DELETE
  - in DISCRIM command A-4.5
  - in REGRESSION command B-4.17
- F.ENTER
  - in REGRESSION command B-4.17
- F.SCALE
  - in HIST command O-7.5
- F.TEST
  - in SURVEY command S-8.8, S-8.25
- FAC
  - in FACTOR command A-5.3
- FACTOR A-5.2**
  - coefficients (scores) A-5.5
  - identifiers
    - DROOT A-5.3
    - FAC A-5.3
    - LARGE A-5.3

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- MAXFAC A-5.2
- MINFAC A-5.2
- NFAC A-5.2
- ONE A-5.3
- PC A-5.2
- ROOTS A-5.3
- SF A-5.2
- TEST A-5.2
- VEC A-5.3
- ZERO A-5.3
- in F.COEF command A-5.5
- procedure A-5.1
- summary A-5.7
- Factor analysis
  - see FACTOR
- FACTORIAL
  - PPL function P-6.3, P-6.20
- Factorial design
  - in ANOVA command
    - incomplete A-6.8
    - with repeated measures A-6.14
- Factors
  - in ANOVA command A-6.1, A-6.19
  - fixed levels A-6.4
  - indexing A-6.17
- FC
  - in F.COEF command A-5.6
- FILE
  - in MAKE command I-2.8, I-4.4, I-4.5, I-4.11, F-3.4, F-3.11
  - in MAKE.FIXED command F-4.1, F-4.8
  - in SHOW.MACROS command P-12.11, P-12.29
  - in SPSS.IN command I-4.3, F-2.5
  - in SPSS.OUT command F-2.8
  - in TEXTFILE.IN I-4.2, I-4.13
- File management F-1.1
- File names W-2.15
  - rules for I-3.1, I-3.14, I-3.16
- FILE.IN P-1.1
- FILES I-2.16, **I-10.12**, P-12.15
  - summary I-10.12, U-3.7
- Files
  - active W-2.12
  - different types defined I-2.1
  - external
    - erasing W-2.3
  - how does P-STAT find them W-2.12
  - introduction I-2.13
  - labels I-2.3
  - listing large
    - MAX.PASSES I-6.22
  - modifying I-3.8
  - of P-STAT commands I-2.3
  - print I-2.4
  - P-STAT system I-2.2, I-10.1
  - P-STAT system files defined I-2.2
  - raw data I-2.1
- FILESIZE
  - in MAKE command I-4.10, F-3.4, F-3.12
- FILETYPE I-1.9, I-1.11, W-1.9
- FILL I-6.26
  - in COLLATE command F-9.6, F-9.20
  - in COMPARE command F-6.6
  - in CONCAT command F-8.1, F-8.9
  - in JOIN command F-9.3, F-9.22
  - in LIST command I-6.17
  - in LOOKUP command F-9.12, F-9.23
  - in SURVEY command S-2.1
  - in TITLES command I-5.11, S-11.3
- FILL COLUMNS
  - in SURVEY command S-3.3, S-3.28
- FILL ROWS
  - in SURVEY command S-2.22
- FILL SUBTOTALS
  - in SURVEY command S-4.13, S-4.22
- FILTER
  - in TURF command I-8.29
- Filtering a file using PPL P-2.13
- Finite population statistics S-8.24
- FIRST
  - EDITOR instruction U-6.8, U-7.6
  - in DUPLICATES command F-10.12, F-10.24
  - PPL function P-6.23, P-8.2, P-8.10, P-8.29
- FIRST.G
  - in DUPLICATES command F-10.12,



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- F-10.24
- FIRST.GOOD
  - PPL function P-6.7, P-6.23, P-9.3, P-9.30
- FISCAL.QUARTER function P-10.6, P-10.21
- FISCAL.YEAR function P-10.6, P-10.21
- Fisher 2-tail probability S-8.12
- FITTED.VALUES
  - in ROOTOGRAM B-6.11
- FIXED
  - in Q.CLUSTER command A-3.8
- FLAG
  - LIST identifier I-6.10
- FLOATING TITLES
  - in SURVEY command S-10.27, S-10.28
- FLOOR
  - in SAMPLE command S-12.15, S-12.20
- Floor function P-6.2
- FOLD
  - in LIST command I-6.11, P-2.23
- FOLD LABELS
  - in BOXPLOT command O-6.7, O-6.13
- FONT
  - in BOXPLOT command O-6.7, O-6.13
  - in PLOT command O-5.4, O-5.14
  - in POSTSCRIPT.SETUP command O-2.18
  - in SURVEY command S-7.2, S-7.14
  - in TEXTWRITER command P-11.21, P-11.36
- FONT1
  - basic font O-2.3
  - in BOXPLOT command O-6.7
- FONT1-FONT9
  - in TEXTWRITER command P-11.21
- Fonts O-2.2
  - changing
    - in TEXTWRITER P-11.22
  - names O-2.3
- FONT2
  - in BOXPLOT command O-6.7
  - labels font O-2.3
- FONT3
  - in BOXPLOT command O-6.7
- titles font O-2.3
- titles use O-2.12
- FONT4
  - in BOXPLOT command O-6.7
  - used in SURVEY and PLOT O-2.3
- FONT5 - FONT29
  - in TEXTWRITER O-2.2
- FORCE
  - in DISCRIM command A-4.5
- Forecasting
  - in REGRESSION command B-4.11, B-4.12
- FORGET.EXTERNAL
  - summary I-10.12
- FORMAT
  - in SURVEY command S-7.2, S-7.3, S-7.13
- FORMAT.DATE I-1.3, I-3.10, I-9.6
- FRAC
  - PPL function P-6.2, P-6.20
- Fractional portion function P-6.2
- Free-format
  - commands I-3.4
- FREQ
  - chi-square B-1.7
  - identifiers
    - ALLCAT B-1.6
    - ALLGRP B-1.7
    - DOWN B-1.6
    - EQUALCAT B-1.6
    - LINES B-1.6
    - NCAT B-1.6
    - SUB B-1.7
    - TRUE B-1.6
    - VERBOSITY B-1.7
    - WEIGHT B-1.5
  - summary B-1.15
- FREQ.RESULTS
  - in TURF command W-5.12
- FREQ.STATS
  - in TURF command I-8.29
- FREQS
  - in BALANCE command S-12.5
- FREQUENCIES

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in COUNTS command I-7.15, W-2.3
- in LOCATE.GROUPS command F-10.26, P-12.30
- in SUBFILES command P-12.24
- Frequency
  - in TURF command W-3.8
- FRIEDMAN
  - in NP.TEST command B-5.38
  - summary B-5.58
  - 2-way anova B-5.38
- FULL
  - general identifier I-3.15, I-5.18, I-6.28
  - general identifiers U-2.6
  - in CANONICAL.COR command A-2.7
- Full screen editing U-5.6
- FULL.MACRO.ARGS **P-12.11**, P-12.28
- FULL.OUTPUT
  - in TURF command I-8.23
- FULL.REPORT
  - in TURF command I-8.11
- FUN
  - in DISCRIM command A-4.4
- FUZZ
  - command P-7.8, P-7.12
- Fuzzy arithmetic P-7.6, P-7.12
- G**
- GAP
  - in LIST command I-6.2
  - in SURVEY command S-1.13, S-1.28
- GAUSSIAN
  - in LETTER.VALUES B-6.7
- GE
  - in NP.TEST command B-5.6
- General identifiers
  - ERROR U-2.6
  - FULL I-5.18, U-2.6
  - IDEN I-3.4, U-5.1
  - LINES U-2.2, U-2.6, U-3.3
  - OUTPUT.WIDTH U-2.2
  - OW I-6.27, U-2.6
  - PAGE U-2.6
  - PAGE.NUMBER I-5.13, I-6.27, S-11.5
  - PR I-6.27, U-2.4
  - RUN.PAGE.NUMBER I-5.13, I-6.27, S-11.5
  - SHORT I-5.18
  - SHORT.16 I-5.18, U-2.6
  - SHORT.OLD I-5.18, U-2.6
  - SHORT.TAGS U-2.6
  - TAGS U-2.6
  - TEMP U-2.6, U-3.4
  - TEXT I-5.18, U-2.6
  - TITLES I-5.13, S-11.5
  - VERBOSITY I-6.28
  - VERBOSITY (V) U-2.6
- GENERATE
  - in DO loop P-5.13, P-5.23
  - PPL instruction P-2.1, P-2.11, P-2.24, P-9.1
- Geometric mean
  - in COUNTS command I-7.1, I-7.12
- GET
  - EDITOR instruction U-6.16
- GET.PERCENTILES
  - in SURVEY command S-8.21, S-8.25
- GOOD
  - PPL operator P-2.14, P-2.27, P-9.32
- Good cases
  - in description file B-1.2
- Goodness-of-fit tests B-5.4
- GOTO
  - PPL instruction P-3.7, P-3.17
- GR.IDENTIFY
  - in SURVEY command S-2.10, S-2.22
- GRID.LINES
  - in PLOT command O-3.9
- GRIDS
  - in BOXPLOT command O-6.6, O-6.14
- GROUP
  - in BOX.PLOT B-6.4
  - in NP.TEST command B-5.14, B-5.30
- GROUP.STUBS
  - in SURVEY command S-2.9, S-2.21, S-3.19
  - summary tables S-2.10
- GROUPCOR **A-5.5**
  - identifiers

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- INCOR A-5.5
- INFAC A-5.5
- OUTCOR A-5.5
- OUTFAC A-5.5
- summary A-5.9
- GROUPING.FACTOR
  - in ANOVA command A-6.44
- GROUPS
  - in BOXPLOT command O-6.3, O-6.14
  - in LOCATE.GROUPS command P-12.25
  - in SUBFILES command P-12.25
- GRUMBLE
  - in UPDATE command F-11.4, F-11.6, F-11.11
- GRUMBLE.INSERT
  - in UPDATE command F-11.6, F-11.7
- GRUMBLE.SKIP
  - in UPDATE command F-11.6, F-11.7
- GT
  - in NP.TEST command B-5.6
- GT operator P-2.14
- H**
- Harmonic mean
  - in COUNTS command I-7.1, I-7.12
- HARMONICS
  - in COUNTS command I-7.1, I-7.12
- HEAD **U-2.15**
- HELP I-2.16, I-3.1, W-3.12, **U-2.15**, U-4.6, U-5.1
  - EDITOR instruction U-5.1, U-7.1
  - in batch runs U-4.5
  - in EDA command B-6.3
  - in PLOT command O-3.3
  - introduction I-2.13
- Help
  - PC Windows
    - menu W-2.2
- Help file I-10.9
  - using W-2.13
- HEX
  - PPL function P-7.7, P-7.11
- Hierarchical data
  - collating F-9.10
- Hierarchical files I-10.2
- High value
  - in COUNTS command I-7.1
  - in description file B-1.2
  - in SURVEY command S-5.20
- HIGH.TEST
  - in DUPLICATES command F-10.14, F-10.25
- HIGHS
  - in LIST command I-6.21
- HIST **O-7.1**, O-7.6
  - allocating ranges O-7.3
  - identifiers
    - ALL O-7.5
    - BAR.LIMITS O-7.5
    - BAR.STEP O-7.5
    - BARS O-7.4
    - CUMULATIVE O-7.3
    - DES O-7.3
    - EACH O-7.5
    - F.SCALE O-7.5
    - LINES O-7.1
    - RANGE O-7.3
    - SUB O-7.4
  - scaling O-7.4
  - subgroups O-7.4
  - summary O-7.6
- holding
  - controls scrolling on the screen I-9.2
- HOLDING message U-3.2
- HONOR.STRINGS
  - in MAKE command I-4.10, F-3.9, F-3.13
  - in MAKE.FIXED command F-4.7, F-4.9
  - in TEXTFILE.IN I-4.13
- HORIZONTAL
  - in PLOT command O-3.10
- Hypothesis
  - in ANOVA command A-6.44
    - null A-6.1
    - rejection criteria A-6.5
- I**
- IDEN
  - general identifier I-3.4, U-2.20, U-5.1

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

summary U-3.9  
 Identifiers I-3.2  
   defined I-2.10  
   general  
     FULL I-3.15  
     SHORT.16 I-3.15  
     SHORT.OLD I-3.15  
     TEXT I-3.15  
 IDENTIFY  
   in LIST command I-6.17  
 IF  
   PPL instruction P-2.1, P-2.13, P-2.19,  
     P-2.24, P-3.7, P-9.2  
 IF-THEN-ELSE P-5.14– P-5.18, P-5.24  
 IGNORE.STRINGS  
   in MAKE command I-4.10, F-3.9, F-3.13  
   in MAKE.FIXED command F-4.7, F-4.9  
   in TEXTFILE.IN I-4.2, I-4.13  
 IMPORT  
   EDITOR instruction U-6.16  
 IN.FUN  
   in DISCRIM command A-4.4  
 INCLUDE ALL STUB VALUES  
   in SURVEY command S-2.2, S-2.22  
 INCLUDE ALL SUBTOTALS  
   in SURVEY command S-4.18, S-4.22  
 INCLUDE files  
   in SURVEY command S-10.2, S-10.29  
 INCLUDE MISSING MEANS VALUES  
   S-1.22, S-1.28, S-3.7  
 INCOR  
   in GROUPCOR command A-5.5  
   in NEWFAC command A-5.6  
 INCREASE  
   PPL instruction P-2.10, P-2.25  
 INDENT  
   DEFINED VALUES S-4.13  
   in SURVEY command S-4.11, S-4.13,  
     S-4.22  
 Indenting subtotal/net levels S-6.4  
 Independence  
   testing for in SURVEY S-9.6  
 INDEPENDENT  
   in REGRESSION command B-4.7

## INDEX

  in ANOVA command A-6.17  
   in COLLECT function P-8.21  
   in SPLIT function P-8.16  
   in SURVEY command S-5.12, S-5.23  
 INFAC  
   in GROUPCOR command A-5.5  
   in NEWFAC command A-5.6  
   in PROMAX command A-5.5  
 INPUT  
   EDITOR U-7.1  
     location of pointer U-7.2  
   EDITOR instruction U-6.8, U-7.1  
 INQUIRE  
   determine existence of P-STAT system file  
     **P-12.23**, P-12.31  
 INQUIRE.EXTERNAL **P-12.22**, P-12.31  
 INRANGE  
   PPL operator P-2.19, P-2.27  
 INSERT  
   in UPDATE command F-11.6  
 Insert  
   text in full screen command editor U-5.7  
 Installation W-1.7  
   P-STAT installation I-1.7  
 INT  
   PPL function P-6.2, P-6.20  
 Integer function P-6.2  
 interaction with IF P-6.9  
 Interactions  
   in ANOVA command A-6.4, A-6.6  
     and Latin square design A-6.9  
     and nested designs A-6.11  
 INTERACTIVE I-1.5, I-1.11, **U-2.1**, U-3.7,  
   U-5.1  
   prompt messages U-5.2  
 Interactive usage I-1.5  
   EDITOR U-5.1  
     summary U-5.8  
   error processing I-3.12  
 Interfaces to other programs I-10.3  
 INTERLEAVE **F-7.6**, F-7.11  
   identifiers  
     CHECK.RL F-7.7

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- NO.CHECK.CL F-7.7
- NO.CHECK.RL F-7.7
- OUT F-7.6
- PATTERN F-7.6
- Interquartile range
  - in COUNTS command I-7.1
- Interval data B-5.4
- Introduction to using P-STAT W-2.1
- INVBIN
  - PPL function P-7.5, P-7.11
- INVCHI
  - PPL function P-7.5, P-7.11
- Inverse probability functions P-7.5
  - binomial distribution P-7.5
  - chi-square distribution P-7.5
  - F distribution P-7.5
  - normal distribution P-7.6
  - Poisson distribution P-7.6
  - t distribution P-7.6
- INVERT **A-1.6**, A-5.3
  - identifiers
    - DET A-1.6
    - OUT A-1.6
    - PAR A-1.7
    - RSQ A-1.7
  - summary A-1.12
- INVF
  - PPL function P-7.5, P-7.11
- INVNORM
  - PPL function P-7.6, P-7.11
- INVPOIS
  - PPL function P-7.6, P-7.11
- INVT
  - PPL function P-7.6, P-7.11
- ISO 8859-1
  - character set S-7.3
- ITEM.WEIGHTS
  - in TURF command I-8.29
- IVAL
  - PPL function P-9.14, P-9.27
- J**
- JOIN **F-9.1**
  - identifiers
    - CHECK F-9.3, F-9.22
    - FILL F-9.3, F-9.22
    - NO CHECK F-9.22
    - OUT F-9.1, F-9.21
  - joining titles in SURVEY output S-6.20, S-7.6
  - linking variables F-9.1
  - renaming linking variables F-9.3
  - summary F-9.21
  - to make longer titles S-6.24
- Join files
  - add cases with CONCAT W-2.4
  - add variables with LOOKUP W-2.4
- JOIN.POINTS
  - in PLOT command O-5.14
- Journal format
  - in SURVEY command S-7.3
- Justification of value labels S-5.8, S-5.24
- JUSTIFY
  - in TEXTWRITER command P-11.7
- K**
- Kaplan-Meier
  - survival function A-7.2
- KEEP
  - EDITOR instruction U-6.8
  - PPL instruction P-2.1, P-2.3, P-2.8, P-2.25
- KENDALL
  - in NP.COR command B-5.44
- Kendall
  - Coefficient of Concordance W B-5.40
  - rank correlation B-5.44
- Keywords
  - defined I-2.8
- Kolmogorov-Smirnov
  - 1-sample test B-5.11
  - 2-sample test B-5.17
- KRUSKAL.WALLIS
  - in NP.TEST command B-5.33
  - summary B-5.56
- Kruskal-Wallis 1-way anova B-5.33
- KS1
  - in NP.TEST command B-5.11

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- summary B-5.47
- KS2
  - in NP.TEST command B-5.17
  - summary B-5.50
- Kurtosis
  - in COUNTS command I-7.1, I-7.12
  - in PERCENTILES command B-1.9
- KW
  - in NP.TEST B-5.34
- L**
- Label files
  - multiple I-5.7, S-11.9
- LABEL.CHANGES I-4.13
  - in TEXTFILE.IN I-4.3, I-4.13
- LABELS I-7.4, **S-11.6**
  - echoing S-1.27
  - formatting S-1.16
  - in ANOVA command A-6.49
  - in BOXPLOT command O-6.2, O-6.11
  - in COUNTS command I-7.4, I-7.20
  - in EDA command B-6.2
  - in LIST command I-6.7
  - in MAP command F-12.6
  - in PLOT command O-4.3, O-4.15
  - in SPSS.IN command I-4.3, F-2.5
  - in SPSS.OUT command F-2.8
  - in SUBSTITUTE.VL command F-12.8, F-12.19
  - in SUBSTITUTE.XL command F-12.20
  - in SURVEY command S-1.2, S-1.13, S-5.6, S-6.1
  - in TABFILE.IN command command F-2.13
  - in TABFILE.OUT command F-2.8
  - in TABFILE.OUT command command F-2.14
  - in TEXTFILE.IN I-4.3, I-4.13
  - in TEXTWRITER command P-11.8, P-11.32
  - section of LAYOUT
    - in SURVEY command S-1.7
- Labels
  - for PPL statements P-3.7
- overview I-5.3
- LAG
  - in REGRESSION command B-4.11
  - PPL function P-6.8, P-6.22
- LAG function P-6.9
- Lagging function P-6.8
- Lambda
  - in DISCRIM command A-4.1
- LANDSCAPE
  - in BOXPLOT command O-6.4, O-6.12
  - in PLOT command O-5.13
  - in POSTSCRIPT.SETUP O-2.18
  - in SURVEY command S-7.2
  - in TEXTWRITER command P-11.21, P-11.36
  - orientation O-2.4, O-5.1
- LARGE
  - in FACTOR command A-5.3
- Large files
  - processing in batch mode U-4.4
- Laser printers
  - SURVEY command S-7.1
- LAST
  - EDITOR instruction U-6.8
  - in DUPLICATES command F-10.10, F-10.15, F-10.24
  - PPL function P-6.23, P-8.2, P-8.10, P-8.29
- LAST.G
  - in DUPLICATES command F-10.12, F-10.24
- LAST.GOOD
  - PPL function P-6.7, P-6.23, P-9.3, P-9.30
- LAYOUT
  - in SURVEY command S-1.7, S-1.28
  - of transposed table S-3.19
- LE
  - in NP.TEST command B-5.6
  - PPL operator P-2.14
- LEAD.BLANK and NO LEAD.BLANK
  - in SURVEY command S-6.21
- LEADBLANK
  - in TEXTWRITER command P-11.7, P-11.32

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

**LEADING**

in POSTSCRIPT command O-2.4  
 in POSTSCRIPT.SETUP command  
 O-2.4, O-2.18

**LEFT**

in CANONICAL.COR command A-2.2  
 in LIST command I-6.8  
 in TITLES command I-5.11, S-11.3  
 PPL function P-9.27

**LEFT.EDGE**

in BOXPLOT command O-6.12  
 in PLOT command O-5.1, O-5.14  
 in POSTSCRIPT.SETUP command  
 O-2.4, O-2.18  
 in SURVEY command S-6.16, S-6.24,  
 S-7.3, S-7.15  
 in TEXTWRITER command P-11.36

**LEFT.EXTRA**

in COLLATE command F-9.7, F-9.20

**LEFT.JUSTIFY**

in MAKE command I-4.10, F-3.8, F-3.13  
 in MAKE.FIXED command F-4.4, F-4.9

**Legal names** W-5.4

defined W-2.6  
 file W-2.15  
 rules for W-2.15  
 variables W-2.15

**LEGEND**

in BOXPLOT command O-6.7, O-6.14  
 in CODED.TABLE B-6.20  
 in PLOT command O-5.5, O-5.14, O-4.3

**LENGTH**

IN MAKE.FIXED command F-4.9  
 in MAKE.FIXED command F-4.7  
 PPL function P-9.8, P-9.27

**LETTER.VALUES**

EDA subcommand B-6.7  
 summary B-6.27

**LETTERS, with CHARACTERS**

in PLOT command O-3.11

**LEVEL**

in COR.SIG command B-3.11

**LEVELS**

in BOX.PLOT B-6.4

in BOXPLOT command O-6.3, O-6.14

**LFONT**

in SURVEY command S-7.6, S-7.14

**LIFE.TABLE A-7.12**

## identifiers

BY A-7.17  
 DOWN A-7.20  
 EXACT A-7.17  
 FAIL A-7.17  
 HIGH A-7.17  
 INTERVALS A-7.17  
 LOW A-7.20  
 NO LIST A-7.17  
 NO PLOT A-7.17  
 OUT A-7.17  
 STATUS A-7.12, A-7.17  
 STRATA A-7.17  
 TIME A-7.16  
 TIME.INTERVALS A-7.17  
 UP A-7.21  
 WIDTH A-7.17  
 WITHDRAWN A-7.17

summary A-7.19

**LIMIT**

in CANONICAL.COR command A-2.8

**Limitations**

command storage area S-10.13  
 in SAMPLE command S-12.16  
 in SURVEY command S-1.4, S-10.13  
 cells per table S-10.13  
 columns per page S-10.13  
 incompatible features S-10.14  
 subcommand storage S-10.13

**LINE.PLOT**

in PLOT command O-3.12

**LINE.TYPE**

in PLOT command O-5.4, O-5.14  
 in POSTSCRIPT command O-2.21  
 in POSTSCRIPT subcommands O-2.11

**LINE.WIDTH**

in BOXPLOT command O-6.6, O-6.13  
 in PLOT command O-5.14  
 in POSTSCRIPT command O-2.11,  
 O-2.22

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in SURVEY command S-7.8, S-7.15
- LINES I-9.2, I-9.10, **U-2.6**, U-2.16
  - command I-5.9, S-11.1
  - general identifier U-2.6, U-2.20, U-3.3
  - identifier I-5.9, S-11.1
  - in DEFAULT.SETTINGS command
    - U-2.2
  - in FREQ command B-1.6
  - in HIST command O-7.1
  - in LIST command I-6.5
  - in PLOT command O-3.4
  - in PRINTER.SETTINGS command U-2.2
  - in XY.PLOT B-6.15
  - used in SURVEY command S-5.1
- LINETO
  - in POSTSCRIPT command O-2.11, O-2.21
- LIST **I-6.1**, I-6.23, W-2.2, W-2.11, W-2.15, W-2.16, W-3.7
  - abbreviation I-2.11
  - data format options I-6.6
  - double spacing I-6.5
  - general control options I-6.21
  - identifiers
    - BY I-6.13, I-6.25
    - BY.N I-6.13, I-6.25
    - CASE.PERCENTAGES I-6.21, I-6.26
    - CASES I-6.21, I-6.26
    - CASES.PER.PAGE I-6.5, I-6.23
    - CENTER I-6.4, I-6.23
    - COMMAS I-6.10, I-6.24
    - DASHES I-6.9, I-6.24
    - DATA.ONLY I-6.4, I-6.23
    - DOLLAR I-6.10, I-6.24
    - DOUBLE I-6.10, I-6.24
    - EXPAND I-6.3, I-6.23
    - FILL I-6.17, I-6.26
    - FLAG I-6.10, I-6.24
    - FOLD I-6.11, I-6.24, P-2.23
    - GAP I-6.2, I-6.23
    - HIGHS I-6.21, I-6.26
    - IDENTIFY I-6.17, I-6.26
    - LABELS I-6.25
    - LEFT I-6.8, I-6.25
    - LINES I-6.5
    - LOWS I-6.21, I-6.27
    - MARGIN I-6.5, I-6.23
    - MAX.PASSES I-6.27
    - MAX.PLACES I-6.10, I-6.25, P-6.10
    - MAX.VL I-6.25
    - MEANS I-6.20, I-6.27
    - MIN.PLACES I-6.10, P-6.10
    - N I-6.13, I-6.24
    - NEWPAGE I-6.15, I-6.26
    - NO CASES I-6.26
    - NO FOLD.STUB I-6.17
    - OUTPUT.WIDTH I-6.11
    - PAGE.NUMBER I-6.16
    - PERCENTAGES I-6.21, I-6.27
    - PLACES I-6.10, I-6.25
    - PR I-6.21
    - PRINT.POSITIONS I-6.4, I-6.24
    - RE.IDENTIFY I-6.17, I-6.26
    - RUN.PAGE.NUMBER I-6.16
    - SKIP I-6.5
    - SKIP.COUNTER I-6.5, I-6.14, I-6.24
    - SKIP.OMIT I-6.14, I-6.26
    - SKIP.VAR I-6.26
    - SKIP.VARS I-6.13, I-6.14
    - STUB I-6.15, I-6.26
    - TITLES I-6.5, I-6.24
    - TOTALS I-6.21, I-6.27
    - TRIM.ZEROS I-6.10, I-6.25
    - USE.XL I-6.9, I-6.25
  - in CANONICAL.COR command A-2.5
  - in COUNTS command I-7.3
  - introduction I-2.11
  - numbering cases I-6.13
  - page changes I-6.15
  - page layout options I-6.1
  - print destination I-6.21
  - subgroup options I-6.12
  - summary I-6.23
  - summary statistics I-6.17
  - variable names I-6.2
- LIST.BY
  - in COUNTS command I-7.3



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- LOC  
 PPL function P-6.3, P-6.20
- LOCATE **I-10.7**  
 EDITOR instruction U-6.8  
 summary I-10.12
- LOCATE.GROUPS **F-10.18**, P-12.24  
 identifiers  
 BY F-10.26, P-12.30  
 DOWN F-10.20, F-10.26, P-12.30  
 EXACT F-10.26, P-12.30  
 FREQUENCIES F-10.19, F-10.26,  
 P-12.30  
 GROUPS F-10.19  
 OUT F-10.19, F-10.27, P-12.26,  
 P-12.31  
 UP F-10.20, F-10.27, P-12.31  
 summary F-10.26, P-12.30
- Location function P-6.3
- LOG  
 in EDA command B-6.3, B-6.25  
 in REGRESSION command B-4.10  
 PPL function P-6.3, P-6.20
- LOG10  
 in BOXPLOT command O-6.3, O-6.6,  
 O-6.9, O-6.14  
 in EDA command B-6.3  
 in PLOT command O-5.14  
 in REGRESSION command B-4.10  
 PPL function P-6.3, P-6.20
- Logarithm functions P-6.3
- Logical operators P-2.26  
 date/time P-10.16
- LONG  
 in PAIRED.TTEST command B-2.7  
 in PROMPT command U-5.3
- LOOKUP W-2.4, S-10.23  
 cascading files F-9.15  
 case selection F-9.15  
 identifiers  
 EXACT F-9.19, F-9.23  
 FILL F-9.12, F-9.23  
 OUT F-9.12, F-9.22  
 TABLE F-9.12, F-9.22  
 TIES F-9.19, F-9.23
- UNMATCHED F-9.19, F-9.23  
 recoding variables F-9.17  
 summary F-9.22
- Low value  
 in COUNTS command I-7.1  
 in description file B-1.2  
 in SURVEY command S-5.20
- LOW.TEST  
 in DUPLICATES command F-10.14,  
 F-10.25
- LOWER  
 PPL function P-9.7, P-9.27
- Lower case  
 data entry I-3.2  
 use of W-2.7
- LOWS  
 in LIST command I-6.21
- LPAD  
 PPL function P-9.27
- LRPAD  
 PPL function P-9.28
- LRTRIM  
 PPL function P-9.12, P-9.29
- LSD test A-6.36
- LT  
 in NP.TEST command B-5.6  
 PPL operator P-2.14
- LTRIM  
 PPL function P-9.12, P-9.29
- M**
- M1  
 in SPSS.OUT command F-2.9
- MACRO **P-12.1**, P-12.11, S-10.7  
 example S-10.10  
 for TURF analysis W-5.15  
 in stream S-10.3  
 open and run W-2.3  
 summary P-12.27  
 usage S-1.25
- MACRO.PAD **P-12.11**, P-12.29
- Macros W-1.4  
 activating P-12.2  
 arguments P-12.5

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- default values P-12.6
- keyword P-12.4
- positional P-12.4
- block P-12.2
  - executing P-12.2
- calling other macros P-12.7
- comments P-12.3
- correcting in editor P-12.11
- format of P-12.1
- in stream P-12.1
- in subcommands P-12.8
- in the editor P-12.11
- Scratch variable usage P-12.14
- storing P-12.2
- temporary files P-12.15
- using RUN P-12.14
- MACROS and SUBFILES
  - example with POSTSCRIPT O-2.10
- Mahalanobis D square
  - in DISCRIM command A-4.3
- MAKE I-1.2, I-2.16, **I-4.1**, **I-4.3**, I-4.11, W-1.5, W-3.13, **F-3.1**, P-1.1
  - identifiers
    - BLANK.DELIMITER I-4.10, F-3.6, F-3.8, F-3.12
    - CHANGE I-4.10, F-3.9, F-3.12
    - DEFINITIONS I-4.5, I-4.11, F-3.3, F-3.11
    - DEL F-3.12
    - DELIMITER I-4.7, F-3.6
    - DROP I-4.10, F-3.6, F-3.12
    - DROP.LEAD.BLANKS F-3.8, F-3.13
    - EOC I-4.9, I-4.12, F-3.6, F-3.12
    - FILE I-2.8, I-4.4, I-4.5, I-4.11, F-3.4, F-3.11
    - FILESIZE I-4.10, F-3.4, F-3.12
    - HONOR.STRINGS I-4.10, F-3.9, F-3.13
    - IGNORE.STRINGS I-4.10, F-3.9, F-3.13
    - LEFT.JUSTIFY I-4.10, F-3.8, F-3.13
    - MISSING I-4.9, I-4.12, F-3.7, F-3.12
    - NO DELIMITER I-4.10
    - NO MISSING F-3.7, F-3.12
    - NO STRIP F-3.9, F-3.13
    - NO.DEL I-4.12, F-3.6, F-3.12
    - NO.EOC I-4.9, I-4.12, F-3.6, F-3.12
    - NO.MISSING I-4.10
    - NV I-2.7, I-4.5, I-4.11, F-3.3, F-3.11
    - ONE.PASS I-4.10, F-3.5, F-3.13
    - OPTION F-3.9, F-3.13
    - STRING.BOUNDARY I-4.10, F-3.9, F-3.13
    - STRIP I-4.10, F-3.9, F-3.13
    - SUMMARY F-3.5, F-3.13
    - TEMPLATE I-4.5, I-4.11, F-3.3, F-3.12
    - VARs I-2.8, I-4.5, I-4.11, F-3.3, F-3.11
  - simple example I-2.8
  - subcommand records F-3.3
  - summary F-3.11
- MAKE.CHARACTER **F-12.14**, F-12.16, P-9.26
  - identifiers
    - OUT F-12.14, F-12.17
    - VARs F-12.14, F-12.17
- MAKE.DATE function P-10.4, P-10.20
- MAKE.FIXED I-1.2, W-3.13, **F-4.8**
  - identifiers
    - CHANGE F-4.5**
    - DEFINITIONS F-4.2, F-4.8
    - EOC F-4.6, F-4.8
    - FILE F-4.1, F-4.8
    - HONOR.STRINGS F-4.7, F-4.9
    - IGNORE.STRINGS F-4.7, F-4.9
    - LEFT.JUSTIFY F-4.4, F-4.9
    - LENGTH F-4.7, F-4.9
    - MAKE.FIXED F-4.5
    - NO.EOC F-4.6, F-4.8
    - NV F-4.8
    - STRING.BOUNDARY F-4.7
    - STRIP F-4.4
    - SUMMARY F-4.2, F-4.9
    - VARs F-4.8
  - open ended character variable F-4.3
- MAKE.NUMERIC **F-12.14**, F-12.17, P-9.27

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- identifiers
  - OUT F-12.14, F-12.17
  - VARS F-12.14, F-12.17
- Mallows' Cp B-4.14
- MANN.WHITNEY
  - in NP.TEST command B-5.16
  - summary B-5.49
  - U test B-5.16
- Manuals
  - list of I-1.7, W-1.6
- MAP **F-12.2**, S-10.20
  - identifiers
    - EXACT F-12.4, F-12.18
    - MR.GROUPS F-12.18
    - NEW.LABELS F-12.6, F-12.18
    - NO LIST F-12.18
    - OLD.LABELS F-12.18
    - OUT F-12.18
    - SUMMARY F-12.5, F-12.8, F-12.18
    - VAR F-12.18
  - label files F-12.6
  - summary F-12.17
- MARGIN
  - in LIST command I-6.5
  - in SURVEY command S-1.12, S-1.28
  - in SURVEY PostScript Output S-7.15
  - in TEXTWRITER command P-11.7, P-11.32
- MARGINALS
  - in BALANCE command S-12.5
- Marginals, tables of S-3.25
- MARGINS
  - in BOXPLOT command O-6.4, O-6.12
  - in POSTSCRIPT command O-2.20
  - in POSTSCRIPT.SETUP command O-2.2, O-2.4, O-2.18
- MASK
  - in case, variable selection P-2.8
  - in SPLIT instruction P-8.15
- Masks
  - Complex for GENERATE P-5.13
  - for RENAME and GENERATE P-5.24
- MATCHES
  - PPL operator P-9.18, P-9.32
- meta-characters P-9.20
- Matrix operations A-1.1
  - C.TRANSPOSE A-1.1
  - CHOLESKY A-1.7
  - E.ADD A-1.2
  - E.DIVIDE A-1.3
  - E.MULTIPLY A-1.3
  - E.SUBTRACT A-1.3
  - EIGEN A-1.7
  - INVERT A-1.6
  - MULTIPLY A-1.6
  - NORM.COL A-1.4
  - NORM.ROW A-1.4
  - SJOIN A-1.8
  - TRANSPOSE A-1.1
- MAX
  - in AGGREGATE command F-10.3, F-10.22
  - in CHECK command F-12.16
  - in CONCAT command F-8.6, F-8.9
  - in COUNTS command I-7.15
  - in DISCRIM command A-4.5
  - in DUPLICATES command F-10.17, F-10.26
  - in REGRESSION command B-4.14
  - in ROTATE command A-5.4
  - PPL function P-6.21
- MAX.BY
  - in PLOT command O-3.20
- MAX.G
  - in DUPLICATES command F-10.17, F-10.26
- MAX.GOOD
  - PPL function P-6.21
- MAX.GROUP
  - in SAMPLE command S-12.13, S-12.19
- MAX.INDEX
  - in SURVEY command S-5.12, S-5.23
- MAX.MISSING
  - in Q.CLUSTER command A-3.4
- MAX.PASSES
  - in LIST command I-6.22
- MAX.PLACES
  - in LIST command I-6.10

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

in SPSS.OUT command F-2.8  
**MAX.STRING**  
 in SPSS.OUT command F-2.9  
**MAX.TICKS**  
 in BOXPLOT command O-6.6, O-6.13  
 in PLOT command O-4.10  
**MAX.VALUE.LABEL**  
 in SPSS.OUT command F-2.9  
**MAX.VAR.LABEL**  
 in SPSS.OUT command F-2.9  
**MAX.VL**  
 in LIST command I-6.8  
**MAXERROR** I-3.12, U-4.4, **U-4.6**  
**MAXFAC**  
 in FACTOR command A-5.2  
**MAXIMUM**  
 in PLOT command O-3.15  
**MAXIMUMS**  
 in CODED.TABLE B-6.21  
**MCNEMAR**  
 in NP.TEST command B-5.26  
 summary B-5.53  
 test for changes B-5.26  
**MDATA**  
 in STANDARDIZE command B-1.14  
**MEAN**  
 in AGGREGATE command F-10.3,  
 F-10.7, F-10.21  
 in COUNTS command I-7.1  
 in description file B-1.2  
 in DUPLICATES command F-10.15,  
 F-10.17, F-10.25  
 in F.COEF command A-5.6  
 in PLOT command O-3.15  
 PPL function P-6.21  
 Mean of positive values  
 in COUNTS command I-7.1, I-7.12  
 Mean square  
 in ANOVA command A-6.4, A-6.22,  
 A-6.24  
 in REGRESSION command B-4.5  
**MEAN.G**  
 in DUPLICATES command F-10.16,  
 F-10.25

**MEAN.GOOD**  
 PPL function P-6.21  
**MEANS** A-6.44  
 in ANOVA command A-6.4, A-6.20,  
 A-6.44  
 in LIST command I-6.20  
 in SURVEY command S-1.8, S-1.28,  
 S-5.20, S-8.23, S-8.25  
 using another variable S-1.21, S-1.28  
 Means  
 of banner variables S-3.6  
 resetting between tables S-1.23  
 table of S-2.10, S-2.11  
**MEDIAN**  
 in COUNTS command I-7.1  
 in NP.TEST command B-5.14, B-5.30  
 in SURVEY command S-5.20, S-8.15,  
 S-8.25  
 summary B-5.48, B-5.55  
 Median test B-5.14, B-5.30  
**MEDIAN.POLISH**  
 EDA subcommand B-6.21  
 summary B-6.28  
 Medians  
 calculation of S-8.18  
 in BOXPLOT command O-6.8  
 in PERCENTILES command B-1.9,  
 B-1.10  
 in SURVEY command S-1.22  
 of banner variables S-3.6  
 in weighted tables S-8.19  
 limitations S-8.22  
**METHOD.DEFAULT**  
 in SURVEY command S-8.19, S-8.25  
**METHOD.FIRST**  
 in SURVEY command S-8.19, S-8.25  
**METHOD.GROUPED**  
 in SURVEY command S-8.19, S-8.26  
**MENUS**  
 PC Windows  
 File submenu W-2.1  
 using W-2.15  
**MERGE** **F-7.4**, F-7.11  
 checking sort order F-7.6

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- identifiers
  - BY F-7.4, F-7.11
  - DOWN F-7.4, F-7.11
  - EXACT F-7.6, F-7.11
  - OUT F-7.4, F-7.11
  - UP F-7.5, F-7.11
- Meta-characters
  - in MATCHES operator P-9.20, P-9.21
- METHOD
  - in BOXPLOT command O-6.3, O-6.14
- MIGRATE I-1.11
  - from P-STAT version 2 W-1.9
- MIN
  - in AGGREGATE command F-10.4, F-10.22
  - in CONCAT command F-8.6, F-8.9
  - in DISCRIM command A-4.5
  - in DUPLICATES command F-10.17, F-10.25
  - PPL function P-6.21
- MIN.G
  - in DUPLICATES command F-10.17, F-10.26
- MIN.GOOD
  - PPL function P-6.21
- MIN.GROUP
  - in SAMPLE command S-12.13, S-12.19
- MIN.PLACES
  - in LIST command I-6.10
- MINFAC
  - in FACTOR command A-5.2
- MINIMUM
  - in PLOT command O-3.15
- MINIMUM.CASES
  - in BOXPLOT command O-6.8, O-6.14
- MINIMUMS
  - in CODED.TABLE B-6.21
- MISSING
  - in MAKE command I-4.9, I-4.12, F-3.7, F-3.12
  - in REGRESSION command B-4.9
  - in SPSS.OUT command F-2.9
  - in SURVEY command S-1.7, S-5.16, S-5.24
  - in UNMAKE command F-2.11, F-2.16
  - PPL operator P-2.14, P-2.27, P-9.33
- Missing
  - to exclude cases S-5.17
- Missing data
  - defined I-2.2, I-3.5, W-2.6
  - printing in LIST command I-6.9
- Missing data and significance tests S-9.11
- Missing data in CORRELATE command
  - B-3.13
- Missing on Means Variable
  - identifying S-5.17
- MISSING1, MISSING2, MISSING3
  - PPL operators P-2.15
- MISSINGS
  - in COUNTS command I-7.1, I-7.10
- Mixed case
  - use of W-2.7
- MOD
  - PPL function P-3.6, P-6.9, P-6.22
- MOD.LSD
  - Bonferroni test A-6.36
- MODE
  - in COUNTS command I-7.1
  - in SURVEY command S-5.20
- MODEL
  - in ANOVA command A-6.2, A-6.23, A-6.24, A-6.44
  - alternate specification A-6.10
- MODIFY I-3.9, W-2.3, **F-6.1**, F-6.11, P-1.3, P-1.6, **P-3.2**
  - changing a P-STAT system file W-2.4
  - identifiers
    - DES F-6.1, F-6.12, P-3.2, B-1.2, B-1.16
    - OUT F-6.1, F-6.12, P-3.2, P-3.16, B-1.2, B-1.16
    - TEMPLATE F-6.2, F-6.12, P-3.3, P-3.16
    - WEIGHT F-6.2, F-6.12, B-1.17
  - summary P-3.16, B-1.16
- Modular function P-6.9
- MOMENTS
  - in COUNTS command I-7.1, I-7.12

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in PERCENTILES command B-1.10
- Monospace fonts O-2.3
- MONTH.CASE P-10.15, P-10.24
- MONTH.LENGTH P-10.24
- MONTH.NAMES P-10.15, P-10.24
- MONTH.YEAR.DAY P-10.3
- MOVE
  - EDITOR instruction U-6.18
- MOVETO
  - in POSTSCRIPT command O-2.11, O-2.22
- MQ.STUBS
  - in SURVEY command S-2.18, S-2.19, S-2.21
- MR.BANNERS
  - in SURVEY command S-3.28
- MR.STUBS
  - in SURVEY command S-2.14, S-2.21
- MULT.DELETE
  - in UPDATE command F-11.6
- MULT.DELETE.INS
  - in UPDATE command F-11.6
- MULT.OLD.MISS
  - in UPDATE command F-11.6
- MULT.REPLACE
  - in UPDATE command F-11.6
- MULT.USE.ALL
  - in UPDATE command F-11.6
- Multiple correlations A-1.7
- Multiple response
  - in banners S-3.10
  - interactions of banners and stubs S-3.14
  - means in the summary section S-8.20
  - paired variables S-3.14
- Multiple response variables S-2.12, S-2.14, S-2.21
  - how coded S-2.14
  - in COUNTS command I-7.1, I-7.6
  - labelling S-2.15
- Multiple tables per page S-2.7
- Multiplication operator \* P-2.12
  - MATCHES meta-character P-9.21
- MULTIPLY A-1.6**
  - identifiers
- OUT A-1.6
  - in SURVEY command S-9.1
  - summary A-1.13
- M2
  - in SPSS.OUT command F-2.9
- M3
  - in SPSS.OUT command F-2.9
- N**
- N**
  - in COR.SIG command B-3.11
  - in LIST command I-6.13
- NAMES
  - in SHOW.MACROS command P-12.28
- Names legal
  - rules for I-2.15
- Names, legal
  - rules for W-2.15
- NCAT
  - in FREQ command B-1.6
- NCOT
  - PPL function P-4.1, P-4.14, P-6.22
- NCV
  - in BISERIAL command B-3.9
- NE
  - in NP.TEST command B-5.6
  - PPL operator P-2.14, P-2.26
- NEAR
  - PPL logical operator P-7.8
- Nested design
  - in ANOVA command
    - partial nesting A-6.12
- Nesting
  - columns S-3.3
  - rows S-2.6
- NETS
  - defined S-4.22
  - in SURVEY command S-4.22
    - indenting S-5.13
- NEVER SKIP
  - in SURVEY command S-1.13, S-1.29
- NEW. I-9.5
- NEW.EDIT.FILE **U-3.4**, U-6.16
  - identifiers

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- ADD U-3.4, U-3.8
  - summary U-3.7
- NEW.LABELS
  - in MAP command F-12.6
- NEW.PAGE
  - in POSTSCRIPT command O-2.9, O-2.20
- NEWFAC **A-5.6**
  - identifiers
    - INCOR A-5.6
    - INFAC A-5.6
    - OUTFAC A-5.6
  - summary A-5.10
- NEWPAGE
  - in LIST command I-6.15
- NEWS I-2.14, W-2.14, **U-2.16**
- NEXT
  - EDITOR instruction U-6.8
  - in POSTSCRIPT command O-2.11, O-2.22
- NEXTDO
  - PPL instruction P-5.23
- NFAC
  - in FACTOR command A-5.2
- NG
  - in NP.TEST command B-5.30
- NMAT
  - in COR.SIG command B-3.11
  - in CORRELATE command B-3.6
- NO
  - in SURVEY command S-1.29
- NO CHECK
  - in JOIN command F-9.22
- NO DELIMITER
  - in MAKE command I-4.10
  - in UNMAKE command F-2.11, F-2.16
- NO END.OF.CASE
  - in UNMAKE command F-2.11, F-2.16
- NO FILL
  - in COMPARE command F-6.11
- NO FOLD.STUB
  - in LIST command I-6.17
- NO IDENTIFY
  - in AGGREGATE command F-10.23
- NO LEADBLANK
  - in TEXTWRITER command P-11.7
- NO LIST
  - in SURVIVAL command A-7.8
- NO MISSING F-2.17
  - in MAKE command F-3.7, F-3.12
  - in UNMAKE command F-2.11, F-2.17
- NO PLOT
  - in SURVIVAL command A-7.8
- NO PRINT
  - in SURVEY command S-10.12
- NO QUOTES F-2.17
  - in UNMAKE command F-2.11, F-2.17
- NO REPORT
  - in DUPLICATES command F-10.18
- NO SCIENTIFIC
  - in UNMAKE command F-2.11, F-2.17
- NO SHOWPAGE
  - in TEXTWRITER command P-11.21
- NO SPREAD
  - in SUBSTITUTE.XL command F-12.20
  - in TEXTWRITER command P-11.7
- NO STRIP
  - in MAKE command F-3.9, F-3.13
- NO TRANSFORMATIONS
  - in EDA command B-6.3
- NO.CHECK.RL
  - in INTERLEAVE command F-7.7
- NO.DEL
  - in MAKE command I-4.12, F-3.6, F-3.12
- NO.EOC
  - in MAKE command I-4.9, I-4.12, F-3.6, F-3.12
  - in MAKE.FIXED command F-4.6, F-4.8
- NO.MATCH
  - in TTEST command B-2.5
- NO.MISSING
  - in MAKE command I-4.10
- No-break character
  - in TEXT.WRITER command P-11.2
- NODELETE
  - in REGRESSION command B-4.16
- Nominal data B-5.3
- NONE
  - in DUPLICATES command F-10.12,

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

F-10.15, F-10.24  
 Nonlinear regression  
   linearizing transformations B-4.10  
 Nonparametric statistics B-5.1  
   Binomial test B-5.4  
   Chi-square test B-5.8  
   Cochran Q test B-5.37  
   compared with parametric B-5.2  
   Friedman two-way anova B-5.38  
   hypothesis testing B-5.2  
   Kendall Coefficient of Concordance W  
     B-5.40  
   Kendall rank correlation B-5.44  
   k-independent-sample tests B-5.1  
   Kolmogorov-Smirnov 1-sample test  
     B-5.11  
   Kolmogorov-Smirnov 2-sample test  
     B-5.17  
   k-paired-sample tests B-5.1  
   Kruskal-Wallis test B-5.33  
   Mann-Whitney U test B-5.16  
   McNemar test B-5.26  
   measurement scales B-5.3  
   Median test B-5.14, B-5.30  
   one-sample tests B-5.1  
   one-tailed tests B-5.3  
   Sign test B-5.24  
   Spearman rank correlation B-5.41  
   Squared Ranks test B-5.21, B-5.34  
   two-independent-sample tests B-5.1  
   two-paired-sample tests B-5.1  
   two-tailed tests B-5.3  
   Wald-Wolfowitz Runs test B-5.19  
   Wilcoxon Matched-Pairs test B-5.27  
 NORM  
   in COUNTS command I-7.1, I-7.13  
 NORM.COL **A-1.4**  
   identifiers  
     OUT A-1.4  
   summary A-1.13  
 NORM.ROW **A-1.4**  
   identifiers  
     OUT A-1.4  
   summary A-1.13

NORMAL  
   in NP.TEST command B-5.12  
 Normal distribution P-7.4  
   inverse P-7.6  
 Normal random number P-7.1  
 Normality tests  
   Anderson-Darling I-7.13  
   Kolmogorov-Smirnov B-5.11  
   Shapiro-Wilk I-7.13  
 Normalizing columns or rows of matrix A-1.4  
 NOSTEP  
   in REGRESSION command B-4.2,  
     B-4.16  
 NOTAMONG  
   PPL operator P-2.18, P-2.27, P-9.33  
 NOTCH  
   in BOX.PLOT B-6.5  
 NOTCHES  
   in BOXPLOT command O-6.7, O-6.15  
 NOTNEAR  
   PPL logical operator P-7.8  
 NP.COR B-5.1, **B-5.41**  
   identifiers  
     KENDALL B-5.44  
     OUT B-5.42, B-5.44  
   listing the output matrix B-5.42  
   Spearman rank correlation B-5.41  
   summary B-5.59  
 NP.TEST **B-5.1**  
   identifiers  
     BINOMIAL B-5.4  
     CHI B-5.10, B-5.11  
     CHISQUARE B-5.8  
     COCHRAN B-5.37  
     CONCORDANCE B-5.40  
     CONTRASTS B-5.35  
     COUNTS B-5.5  
     DISCRETE B-5.13  
     EQ B-5.6  
     EXPECTED B-5.10  
     FRIEDMAN B-5.38  
     GE B-5.6  
     GROUP B-5.14, B-5.30  
     KRUSKAL.WALLIS B-5.33



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- KS1 B-5.11
- KS2 B-5.17
- KW B-5.34
- LE B-5.6
- LT B-5.6
- MANN.WHITNEY B-5.16
- MCNEMAR B-5.26
- MEDIAN B-5.14, B-5.30
- NE B-5.6
- NG B-5.30
- NORMAL B-5.12
- POISSON B-5.13
- RUNS B-5.19
- SIGN B-5.24
- SQUARED.RANKS B-5.21, B-5.34
- U B-5.16
- UNIFORM B-5.13
- WEIGHT B-5.4, B-5.14, B-5.23,  
     B-5.36
- WILCOXON B-5.27
- Kolmogorov-Smirnov 1-sample test  
     B-5.11
- Kolmogorov-Smirnov 2-sample test  
     B-5.17
- NS  
     in COUNTS command I-7.1
- NTOKEN  
     PPL function P-9.10, P-9.29
- NULL **U-2.16**  
     in DUPLICATES command F-10.15,  
     F-10.25
- Null hypothesis  
     in ANOVA command A-6.1  
     rejection criteria A-6.5  
     in nonparametric statistics B-5.2
- NUMBER  
     PPL function P-9.13, P-9.27
- NUMBER.E  
     PPL function P-9.13
- NUMBER.W  
     PPL function P-9.13
- Numbering Pages  
     in SURVEY command S-5.2
- NUMERATOR  
     in ANOVA command A-6.44
- NUMERIC I-4.2  
     in TABFILE.IN command F-2.13  
     in TEXTFILE.IN I-4.2  
     in TEXTFILE.IN command I-4.13
- Numeric to character  
     conversion of variables F-12.8, F-12.14
- NUMEX  
     PPL function P-6.10, P-6.23
- NV  
     in MAKE command I-2.7, I-4.5, I-4.11,  
     F-3.3, F-3.11  
     in MAKE.FIXED command F-4.8
- O**
- Oblique rotations  
     PROMAX A-5.5
- OBSERVE  
     in PLOT command O-3.14
- OFF  
     in TITLES command I-5.12, S-11.4
- OLD  
     EDITOR instruction U-6.5
- OLD.EDIT.FILE **U-3.4**, U-6.16  
     identifiers  
         ADD U-3.5, U-3.8  
         summary U-3.8
- OLD.LABELS  
     in MAP command F-12.6
- OLD.MISSING  
     in UPDATE command F-11.5
- OMIT  
     in TURF command I-8.29
- OMIT EMPTY PLOTS  
     in BOXPLOT command O-6.3, O-6.15
- OMIT.PERCENTS  
     in SURVEY command S-8.4, S-8.26
- ON  
     in TITLES command S-11.4
- ONE  
     in FACTOR command A-5.3
- ONE.PASS  
     in MAKE command I-4.10, F-3.5, F-3.13
- One-tailed tests

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in nonparametric statistics B-5.3
- ONLY
  - in DUPLICATES command F-10.12, F-10.15, F-10.25
- Open-ended Character Variable
  - in MAKE.FIXED command F-4.3
- OPTION
  - in MAKE command F-3.9, F-3.13
- OPTION LABEL COMBINED SUBTOTALS
  - in SURVEY command S-4.18, S-4.22
- OPTION TEST SUBTOTALS
  - in SURVEY command S-4.18, S-4.23
- OR
  - PPL operator P-2.27
- ORDER
  - in REGRESSION command B-4.17
  - in SURVEY command S-2.3, S-2.22
- ORDER COLUMNS
  - in SURVEY command S-3.4, S-3.28
- Ordinal data B-5.3
- ORIGIN
  - in CONCAT command F-8.7, F-8.9
  - in REGRESSION command B-4.10
- OTHERS
  - in SAMPLE command S-12.10, S-12.19
- OUT
  - in AGGREGATE command F-10.21
  - in BISERIAL command B-3.14
  - in C.TRANSPOSE command I-6.28, A-1.15
  - in CANONICAL.COR command A-2.7, A-2.11
  - in CHOLESKY command A-1.10
  - in COLLATE command F-9.20
  - in COMPARE command F-6.11
  - in CONCAT command F-8.10
  - in CORRELATE
    - command B-3.14
  - in DUPLICATES command F-10.18, F-10.23
  - in E.ADD command A-1.11
  - in E.DIVIDE command A-1.11
  - in E.MULTIPLY command A-1.11
  - in E.SUBTRACT command A-1.12
  - in EDA command B-6.24
  - in INVERT command A-1.12
  - in JOIN command F-9.21
  - in LIFE.TABLE command A-7.17
  - in LOCATE.GROUPS command F-10.27, P-12.26, P-12.31
  - in LOOKUP command F-9.22
  - in MAKE.CHARACTER command F-12.14, F-12.17
  - in MAKE.NUMERIC command F-12.14, F-12.17
  - in MERGE command F-7.11
  - in MODIFY command F-6.12, P-3.16, B-1.16
  - in MULTIPLY command A-1.13
  - in NORM.COL command A-1.13
  - in NORM.ROW command A-1.14
  - in OVERALL.DES command B-1.17
  - in PERCENTILES command B-1.17
  - in Q.CLUSTER command A-3.11
  - in RANK command F-7.9
  - in REGRESSION command B-4.22
  - in SAMPLE command S-12.10
  - in SORT command F-7.10
  - in SUBSTITUTE.VL command F-1.6, F-12.8, F-12.19
  - in SUBSTITUTE.XL command F-12.20
  - in SURVEY command S-10.12, S-10.29
  - in SURVIVAL command A-7.7
  - in TET command B-3.17
  - in TEXTWRITER command P-11.8, P-11.32
  - in TRANSPOSE command A-1.14, A-1.15
  - in TTEST command B-2.8
  - in UPDATE command F-11.11
- OUT1
  - in SEPARATE command F-6.8
- OUTCOR
  - in COR.SIG command B-3.11
  - in GROUPCOR command A-5.5
- OUTFAC
  - in GROUPCOR command A-5.5
  - in NEWFAC command A-5.6

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in PROMAX command A-5.5
- OUTLIERS**
  - in BOXPLOT command O-6.3, O-6.8,  
O-6.9, O-6.15
- Output files
  - in SURVEY command S-10.12
- OUTPUT.WIDTH** I-9.2, **U-2.16**
  - general identifier U-2.20
  - in DEFAULT.SETTINGS command  
U-2.2
  - in LIST command I-6.11
  - in PLOT command O-3.4
  - in PRINTER.SETTINGS U-2.2
  - in SURVEY command S-1.12, S-1.29,  
S-1.30, S-7.2
- OUTRANGE**
  - PPL operator P-2.19, P-2.28
- OUTSIG**
  - in COR.SIG command B-3.11
- OUTSIG1**
  - in COR.SIG command B-3.11
- OVERALL.DES** **B-1.3**
  - identifiers
    - OUT B-1.4, B-1.17
  - size constraints B-1.4
  - summary B-1.17
- OVERALL.TOTALS**
  - in SURVEY command S-10.7, S-10.29
- OW** I-9.10
  - general identifier U-2.6
  - in LIST command I-6.27
  - See OUTPUT.WIDTH
- P**
- P**
  - in PLOT command O-3.1
- P vector P-1.2, P-8.5
- P.DELETE**
  - in REGRESSION command B-4.17
- P.ENTER**
  - in REGRESSION command B-4.17
- PAD**
  - PPL function P-9.27
- PAGE**
  - general identifier U-2.6, U-2.20
  - in SURVEY command S-5.1, S-5.24
- Page change character
  - PAGE.CHARACTER** U-2.3
- Page Controls
  - in SURVEY command S-5.1
- PAGE.CHARACTER** I-9.2, S-1.20, **U-2.3**,  
U-2.16
  - in DEFAULT.SETTINGS U-2.2
  - in PRINTER.SETTINGS U-2.2
- PAGE.NUMBER**
  - in LIST command I-6.16, I-6.27
  - in SURVEY command S-5.3, S-5.23,  
S-10.4, S-10.28
  - in TITLES command I-5.13, S-11.5
- PAIRED**
  - in SURVEY command S-3.14, S-3.28
- PAIRED.TTEST**
  - identifiers
    - LONG B-2.7
    - OUT B-2.7
    - SHORT B-2.7
  - summary B-2.9
- Pairwise deletion
  - in CORRELATE command B-3.6
- Paper size O-5.1, O-5.14
- PAPER.SIZE**
  - in POSTSCRIPT.SETUP command  
O-2.4, O-2.19
- PAR**
  - in INVERT command A-1.7
- Parentheses
  - MATCHES** meta-character P-9.21
- Partial correlations A-1.7
- PASSES**
  - in BALANCE command S-12.5
- PATCH** I-1.2, U-1.7, U-1.11
  - identifiers
    - AFTER U-1.8, U-1.12
    - AT U-1.12
    - AT END U-1.8
    - AT START U-1.8
    - OUT U-1.7, U-1.11, U-1.12
    - REMOVE U-1.8, U-1.12

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

PATHNAMES W-2.3, W-2.13, W-2.15

## PATTERN

in CODED.TABLE B-6.21  
 in INTERLEAVE command F-7.6  
 in MEDIAN.POLISH B-6.23

## PC

in FACTOR command A-5.2

## PCT.PLACES

in COUNTS command I-7.15

Pearson product-moment B-3.1

## PERCENT

in SAMPLE command S-12.11, S-12.19

Percent sign

replacing in SURVEY command S-6.8

## PERCENTAGES

in LIST command I-6.21

Percentages

cumulative in COUNTS command I-7.1

in COUNTS command I-7.1

## PERCENTILES W-1.3, **B-1.8**

identifiers

BY B-1.11

GE B-1.10

GET B-1.18

MOMENTS B-1.10, B-1.18

OPTION B-1.18

OUT B-1.9, B-1.17, B-1.18

SDATA B-1.19

WEIGHT B-1.18

in COUNTS command I-7.1, I-7.13

summary B-1.17

Percentiles

computing methods I-7.14

method in BOXPLOT command O-6.3

PERCENTILES command S-8.21

## PERCENTS

alternative layout S-3.8

in SURVEY command S-1.9, S-1.29,  
 S-8.26

Percents

printing selected S-8.4

Percents only table S-5.12

Permanent modifications W-5.3

Permanent vector

see P vector

Phi coefficient B-3.1, B-3.10

Phrases I-3.1, I-3.4

defined I-2.10

in ANOVA command A-6.19

PPL P-2.1

## PLACES

in LIST command I-6.10

in SURVEY command S-3.7, S-5.12,  
 S-6.16, S-6.24, S-8.1, S-8.26

PPL function P-6.10, P-6.23

PLOT O-5.1, O-4.1, O-3.1

abbreviations O-3.4

characters

for overlay plots O-3.18

identifiers

BY O-3.19

DEF O-5.13

LABELS O-4.3, O-4.15

MAX.BY O-3.20

POSTSCRIPT O-2.1

TITLES O-4.1

labeling axes O-4.3

multiple plot requests O-3.2

multivariable plots O-3.14

reversing axes values O-3.11

scatter plots, correlation B-3.2

single variable plots O-3.12

size O-5.1, O-5.14

sorted BY additional variable O-3.19

subcommands

AGAIN O-3.6

BORDER O-5.3, O-5.13

BOTTOM.EDGE O-5.1

CHARACTERS FOR PLOT O-3.11

COLUMNS O-3.4

DATE.AXIS O-4.7, O-4.8

DIMENSION O-5.1, O-5.14

EDGES O-3.10

EXACT O-3.6

FONT O-5.4, O-5.14

GRID.LINES O-3.9

HELP O-3.3

JOIN.POINTS O-5.14

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- LABEL O-4.3
- LEFT.EDGE O-5.1, O-5.14
- LEGEND O-5.5, O-5.14, O-4.3
- LINE.TYPE O-5.4, O-5.14
- LINE.WIDTH O-5.14
- LINES O-3.4
- LOG10 O-5.14, O-4.7
- MAX.TICKS O-4.10
- NO O-3.7
- OBSERVE O-3.14
- OVERLAY O-3.16
- P O-3.1
- PLOTS.PER.PAGE O-5.2, O-5.14
- POSITION LABELS O-5.6, O-5.15
- POSTSCRIPT O-5.1, O-5.13
- PR O-5.13, O-3.4
- RANGE O-3.4
- RESCALE O-5.15, O-4.5, O-4.6
- RESET O-3.6
- REVERSE O-3.11
- RIGHT.EDGE O-5.1
- SCALE O-5.3, O-5.15, O-3.12
- SHOW NAMES O-3.3
- SHOW SETTINGS O-3.3
- SHOW VARIABLES O-3.3
- SHOWPAGE O-5.2, O-5.15
- SPACE O-5.5, O-5.15
- SYMBOL O-5.3, O-5.15
- TICK.LABELS O-5.6, O-5.15, O-3.8
- TICKS O-3.8
- TITLES O-4.1
- TOP.EDGE O-5.1, O-5.16
- summary O-5.13, O-4.15, O-3.21
- symbols
  - ; subcommand ending O-3.1
  - \* by O-3.1
  - \* plot character O-3.2, O-3.11
  - \$ command ending O-3.2
  - \$ plot character O-3.11, O-3.14
- turning off options O-3.7
- Xwindow and POSTSCRIPT O-5.1
- Plot.Labels
  - substitution codes O-4.5
- PLOTS.PER.PAGE
  - in BOXPLOT command O-6.4, O-6.12
  - in PLOT command O-5.2, O-5.14
- PMULT
  - in F.COEF command A-5.6
- POINT
  - in UNMAKE command F-2.11, F-2.17
- Point biserial correlation B-3.1, B-3.10
- Point size
  - in SURVEY command S-7.4
- POISSON
  - in NP.TEST command B-5.13
- Poisson distribution P-7.4, P-7.6, B-5.11
- POLY
  - in REGRESSION command B-4.12
- POLY.FIT **B-4.18**
  - identifiers
    - CHAR B-4.18, B-4.27
    - COEF B-4.18, B-4.27
    - DEGREE B-4.18, B-4.26
    - DEPENDENT B-4.18, B-4.26
    - INDEPENDENT B-4.18, B-4.27
    - NO FILL B-4.18, B-4.27
    - NO PLOT B-4.18, B-4.27
    - OUT B-4.18, B-4.27
    - USE B-4.18, B-4.27
  - summary B-4.26
- Polynomial distributed lag models
  - in REGRESSION command B-4.12
- POOLED
  - in TTEST command B-2.5
- POPULATION
  - in SURVEY command S-8.14, S-8.24
- PORTRAIT
  - in BOXPLOT command O-6.4, O-6.12
  - in PLOT command O-5.13
  - in POSTSCRIPT.SETUP command O-2.19
  - in SURVEY command S-7.2
  - in TEXTWRITER command P-11.20, P-11.36
  - orientation O-2.4, O-5.1
- POSITION
  - PPL function P-9.8, P-9.28
- POSITION LABELS

I=Introductory Manual

P=P-STAT Programming Language

F=File Management

S=Survey, Sample, Balance

B=Basic Statistics

A=Advanced Statistics

U=Utility commands

O=Plots and PostScript

W=PC/Windows

- in PLOT command O-5.6, O-5.15
- Positional notation, variables P-2.4, P-2.10, P-6.3
- Positive values mean
  - in COUNTS command I-7.1, I-7.12
- POSTSCRIPT O-2.6**
  - identifiers
    - BORDER O-2.8, O-2.19
    - CHARACTER.SET O-2.5, O-2.20
    - LEADING O-2.4
    - NEW.PAGE O-2.9, O-2.20
    - PR O-2.19
    - PRINT O-2.20
    - PUT.PAGE O-2.7, O-2.9, O-2.20
    - TITLES O-2.8, O-2.20
  - in BOXPLOT command O-6.12
  - in PLOT command O-2.1, O-5.1, O-5.13
  - in SURVEY command O-2.1, S-7.13
  - in TEXT.WRITER command O-2.1
  - in TEXTWRITER command P-11.20, P-11.36
  - orientation in PLOT command O-5.1
  - subcommands O-2.9
    - BORDER O-2.11, O-2.20
    - BOTTOM.EDGE O-2.10
    - BOX O-2.11, O-2.21
    - COLOR O-2.21
    - FONT O-2.10
    - LEFT.EDGE O-2.10
    - LINE.TYPE O-2.11, O-2.21
    - LINE.WIDTH O-2.11, O-2.22
    - LINETO O-2.11, O-2.21
    - LINEWIDTH O-2.11
    - MARGINS O-2.10, O-2.20
    - MOVETO O-2.11, O-2.22
    - NEW.PAGE O-2.20
    - NEXT O-2.11, O-2.22
    - PAPER.SIZE O-2.10
    - PUT O-2.12, O-2.22
    - PUT.PAGE O-2.21
    - RIGHT.EDGE O-2.10
    - RMOVETO O-2.11
    - SCALE O-2.12, O-2.22
    - SETFONT O-2.12, O-2.22
  - SKIP O-2.11, O-2.22
  - TITLES O-2.21
  - TOP.EDGE O-2.10
    - summary O-2.19
- PostScript
  - controls S-7.1
    - landscape orientation S-7.2
    - page description language O-2.1
    - point size of font S-7.4
    - portrait orientation S-7.2
    - title fonts S-7.6
    - underlining subtotals and nets S-7.11
  - PostScript block O-2.1, O-6.5
    - description O-2.6
    - ending with POSTSCRIPT.CLOSE O-2.7
  - POSTSCRIPT.CLOSE O-2.7**
    - identifiers
      - PRINT O-2.17
      - summary O-2.17
  - POSTSCRIPT.RESET O-2.2**
    - summary O-2.17
  - POSTSCRIPT.SETUP O-2.2, O-2.5, P-11.21, P-11.28, S-7.6, S-7.11**
    - identifiers
      - BOTTOM.EDGE O-2.4, O-2.18
      - CHARACTER.SET O-2.17
      - ENCAPSULATE O-2.6, O-2.18
      - FONT O-2.18
      - LANDSCAPE O-2.4, O-2.18
      - LEADING O-2.4, O-2.18
      - LEFT.EDGE O-2.4, O-2.18
      - MARGINS O-2.2, O-2.4, O-2.18
      - PAPER.SIZE O-2.4, O-2.19
      - PORTRAIT O-2.4, O-2.19
      - RIGHT.EDGE O-2.4, O-2.18
      - SHOWPAGE O-2.6, O-2.19
      - TOP.EDGE O-2.4, O-2.18
      - summary O-2.17
  - POSTSCRIPT.SETUP** identifiers
    - DELTA O-2.18
- POWER
  - in EDA command B-6.3
- PP
  - see PRINTER.SETTINGS

I=Introductory Manual

P=P-STAT Programming Language

F=File Management

S=Survey, Sample, Balance

B=Basic Statistics

A=Advanced Statistics

U=Utility commands

O=Plots and PostScript

W=PC/Windows

PPL I-10.14, P-1.1, P-2.1, P-3.1, P-4.1,  
 P-6.1, P-8.1, P-9.1  
 case, variable selection **P-2.1**  
 character variables P-9.1  
 comments P-3.20  
 concatenation, on-the-fly P-3.4  
 Date and time summary P-10.20  
 DO loops P-5.1– P-5.11, P-5.22  
 exact comparisons of characters P-2.14  
 function  
   COLLECT I-9.10  
   generating variables P-2.9  
   how it changes data F-1.1  
   IF tests P-3.7  
   introduction P-1.1  
   logical selection P-2.13, P-2.19  
   modifying variables P-2.9, P-3.1  
   order of numeric operators P-2.12  
   permanent vector P-8.5  
   phrases with PPL clauses P-2.1  
   scratch variables P-8.3  
   see P-STAT Programming Language  
   size constraints P-2.3  
   standalone I-8.10  
   standalone commands P-1.3, P-1.6,  
     P-3.12, P-3.17  
   summary P-1.5, P-2.23, P-3.16, P-4.14,  
     P-5.22, P-6.20, P-8.28, P-9.24  
   use in ANOVA A-6.18  
   variable selection  
     PC Windows W-3.3  
   wildcard notation P-2.8, P-8.15, P-8.24

PPL command P-1.6

PPL Functions P-2.12

  char and numeric

    COLLECT P-8.19– P-8.27

    COUNT.GOOD P-6.7, P-9.3

    EXPAND P-6.11

    FIRST P-8.2, P-8.10

    FIRST.GOOD P-6.7, P-9.3

    LAST P-8.2, P-8.10

    LAST.GOOD P-6.7, P-9.3

    RECODE P-4.3

    SPLIT P-8.12– P-8.19

SPLIT \* P-8.24

VARNAME P-3.11

XRECODE P-4.5

character P-9.6

  BLANK P-9.10

  CAPS P-9.7

  CENTER P-9.7

  CHANGE P-9.10

  CHARACTER P-9.14

  CHAREX P-9.14

  CLAG P-9.23

  COMPRESS P-9.11

  CVAL P-9.14

  IVAL P-9.14

  LENGTH P-9.8

  LOWER P-9.7

  LPAD P-9.12

  LRPAD P-9.12

  LRTRIM P-9.12

  LTOKEN P-9.10

  LTRIM P-9.12

  NTOKEN P-9.10

  NUMBER P-9.13

  NUMBER.E P-9.13

  NUMBER.W P-9.13

  PAD P-9.12

  POSITION P-9.8

  RIGHT P-9.7

  RPAD P-9.12

  RTOKEN P-9.10

  RTRIM P-9.12

  SIZE P-9.8

  SUBSTRING P-9.9

  TOKEN P-9.9

  TRIM P-9.12

  UPPER P-9.7

  VARNAME P-9.17

  VERIFY P-9.8

  XBLANK P-9.10

  XCHANGE P-9.10

  XPOSITION P-9.9

complex, nested P-9.16

Date/time

  ADD dates and times P-10.9, P-10.21

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- CHANGE dates and times P-10.11,  
     P-10.22
- CURRENT.DATE P-10.4
- DAY.MONTH.YEAR P-10.3,  
     P-10.20
- DAY.WITHIN.WEEK P-10.7,  
     P-10.21
- DAY.WITHIN.YEAR P-10.7,  
     P-10.21
- DAY.YEAR.MONTH P-10.3,  
     P-10.20
- DAYS P-10.5
- DIF - compare dates and times P-10.23
- Difference between dates/times  
     P-10.12
- EXTRACT dates and times P-10.10,  
     P-10.22
- FISCAL.QUARTER P-10.6, P-10.21
- FISCAL.YEAR P-10.6, P-10.21
- MAKE.DATE P-10.4, P-10.20
- MONTH.DAY.YEAR P-10.20
- MONTH.YEAR.DAY P-10.3,  
     P-10.4, P-10.20
- QUARTER P-10.7, P-10.21
- REFORMAT.DATE P-10.5, P-10.20
- SECONDS P-10.6, P-10.21
- SECONDS.MIDNIGHT P-10.6,  
     P-10.21
- STATUS.DATE P-10.5, P-10.20
- SUBTRACT dates and times P-10.9
- UNDO.DAYS P-10.6, P-10.21
- UNDO.SECONDS P-10.6, P-10.21
- WEEK.WITHIN.YEAR P-10.7
- YEAR.DAY.MONTH P-10.4,  
     P-10.20
- YEAR.MONTH.DAY P-10.4,  
     P-10.20
- numeric
- ABS P-6.2
- ACOS P-6.3
- ASIN P-6.3
- ATAN P-6.3
- CEIL P-6.2
- COMBINATIONS W-5.10, P-6.11
- COS P-6.3
- DIF P-6.8
- EXP P-6.3
- FACTORIAL P-6.3
- FLOOR P-6.2
- FRAC P-6.2
- HEX P-7.7, P-7.11
- INT P-6.2
- INVBIN P-7.5
- INVCHI P-7.5
- INVF P-7.5
- INVNORM P-7.6
- INVPOIS P-7.6
- INVT P-7.6
- LAG P-6.8
- LOC P-6.3
- LOG P-6.3
- LOG10 P-6.3
- MOD P-3.6, P-6.9
- NCOT P-4.1
- NUMEX P-6.10
- PLACES P-6.10
- PROBCHI P-7.4
- PROBF P-7.4
- PROBIN P-7.4
- PROBIT P-7.6
- PROBNORM P-7.4
- PROBPOIS P-7.4
- PROBT P-7.5
- RANBIN P-7.1
- RANNORM P-3.7, P-7.1
- RANTABLE P-7.1
- RANUNI P-7.1
- ROUND P-6.2
- SIN P-6.3
- SQRT P-6.3
- STEP.DOWN P-7.7, P-7.12
- STEP.UP P-7.7, P-7.11
- STEPS P-7.7, P-7.12
- TAN P-6.3
- PPL Instructions
- BRANCH F-12.2
- CASES P-2.1, P-2.3  
         using ranges, TO P-2.6



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- with MASK P-2.8
  - CURRENT I-10.4, I-10.14, P-1.4, P-1.6
  - DECREASE P-2.10
  - DELETE P-2.14
  - DO loops P-5.1– P-5.11, P-5.22
  - DROP P-2.1, P-2.3
    - using ranges, TO P-2.4
    - with MASK P-2.8
    - with wildcard P-2.8
  - ENDDO P-5.23
  - EXITDO P-5.22
  - GENERATE P-2.1, P-2.11, P-5.23, P-9.1
  - GOTO P-3.7
  - IF P-2.1, P-2.13, P-2.19, P-3.7, P-9.2
    - missing data P-2.20
    - T F M prefixes P-2.21
  - IF-THEN-ELSE P-5.24
  - INCREASE P-2.10
  - KEEP P-2.1, P-2.3, P-2.8
    - using ranges, TO P-2.4
    - with MASK P-2.8
    - with wildcard P-2.8
  - NEXTDO P-5.23
  - PREVIOUS I-10.4, I-10.14, P-1.4, P-1.7
  - PUT P-3.8, P-3.9, P-11.2
  - PUTL P-3.11, P-11.2
  - QUITCOMMAND P-3.14
  - QUITFILE P-3.14
  - QUITRUN P-3.14
  - RENAME P-2.22, P-2.26, P-5.23
  - REPEAT P-3.6, P-7.2
  - RETAIN P-2.14
  - SET P-2.1, P-2.9, P-9.2
- PPL Operators
- character P-9.3
    - CONTAINS P-9.4
    - MATCHES P-9.18
    - XAMONG P-2.18
    - XCONTAINS P-9.4
    - XEQ P-2.14, P-9.5
    - XMATCHES P-9.18
    - XNOTAMONG P-2.18
    - // concatenate P-9.4
    - /// squeeze concatenate P-9.5
    - && concatenation of character constants P-9.23
  - logical P-2.14
    - ALL P-2.19
    - AMONG P-2.18
    - AND P-2.15
    - ANY P-2.19
    - DATE.EQ P-10.16
    - DATE.GE P-10.16
    - DATE.GT P-10.16
    - DATE.LE P-10.16
    - DATE.LT P-10.16
    - DATE.NE P-10.16
    - EQ P-2.14, P-7.7
    - fuzzy P-7.8
    - GE P-7.7
    - GOOD P-2.14
    - GT P-2.14, P-7.7
    - INRANGE P-2.19
    - LE P-2.14, P-7.7
    - LT P-2.14, P-7.7
    - MISSING P-2.14
    - NE P-2.14, P-7.7
    - NEAR P-7.8, P-7.12
    - NOTAMONG P-2.18
    - NOTNEAR P-7.8, P-7.12
    - OR P-2.15
    - OUTRANGE P-2.19
    - numeric P-2.12
      - P-2.12
      - \* P-2.12
      - \*\* P-2.12
      - / P-2.12
      - + P-2.12
- PPL System Variables
- .ALL. P-3.8, P-3.11, P-11.14, P-11.34
  - .CHARACTER. P-2.8, P-6.17
  - .DATE. P-6.19
  - .e. P-6.14
  - .FILE. P-6.18, P-8.2
  - .G. P-2.14, P-6.14
  - .HERE. P-3.6, P-6.16
  - .M1., .M2., .M3. P-6.15

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- .M. P-2.14, P-6.15
- .N. P-3.6, P-6.16
- .NDATE. P-6.19
- .NEW. P-2.8, P-6.5
- .NUMERIC. P-2.8, P-6.17
- .NV. P-6.15
- .ON. P-2.3
- .OTHERS. P-2.8, P-6.15
- .PAGE. P-6.19
- .PI. P-6.14
- .PUT. P-3.9, P-6.18, P-8.11
- .REPEAT. P-6.19
- .RESPONSE. P-12.21
- .SUBFILECASES. P-12.26
- .SUBFILEMAX. P-12.26
- .SUBFILEPASS> P-12.26
- .TIME. P-6.19
- .USED. P-6.16
- .XINQUIRE. P-12.22
  - in TITLES command I-5.12, S-11.5
- PP, see PRINTER.SETTINGS
- PR I-9.2, I-9.10, **U-2.4**, U-2.17
  - general identifier U-2.4, U-2.20
  - in BOXPLOT command O-6.1, O-6.12
  - in COUNTS command I-7.4
  - in LIST command I-6.21, I-6.27
  - in PLOT command O-5.13, O-3.4
  - in POSTSCRIPT command O-2.19
  - in REGRESSION command B-4.8
  - in SURVEY command S-1.19, S-1.29, S-7.1
  - in SURVIVAL command A-7.19
- PRE.POST B-4.1, B-4.2, **B-4.25**
  - identifiers
    - COR.N B-4.25
    - OUT B-4.25
    - POST B-4.25
    - PRE B-4.25
    - SI.IN B-4.26
    - SI.OUT B-4.26
- Precision
  - in SURVEY command S-8.1
- PREFIX
  - in AGGREGATE command F-10.8, F-10.23
  - in CANONICAL.COR command A-2.7
  - in DUPLICATES command F-10.17, F-10.26
- PRESENT
  - in UPDATE command F-11.3, F-11.5, F-11.12
- PRESERVE.ORDER
  - in EDA command B-6.3
- PREVIOUS
  - PPL instruction I-10.4, P-1.4, P-1.7
  - system file I-3.9
  - version of P-STAT system file I-10.14
- PRINT I-2.12, I-6.22, I-7.4, S-1.20, **U-2.4**, U-2.17
  - in POSTSCRIPT command O-2.20
  - in POSTSCRIPT.CLOSE command O-2.17
  - printing a file U-2.4
  - to a disk file W-2.11
- Print
  - changing destination W-2.2, U-2.4
  - defining the destination U-2.2
  - destination U-2.2
  - set attributes of print destination W-2.2
- PRINT command O-2.7
- Print Manager W-1.5
- PRINT.INPUT U-4.5, **U-4.6**
- PRINT.PARAMETERS see PRINTER.SETTINGS
- PRINT.POSITIONS
  - in LIST command I-6.4
- PRINTER.SETTINGS I-9.3, S-1.20, **U-2.2**, U-2.8, U-2.17, U-3.2
  - identifiers
    - ECHO U-2.2, U-2.17
    - LINES U-2.2, U-2.17
    - OUTPUT.WIDTH U-2.2, U-2.17
    - PAGE.CHARACTER U-2.2, U-2.17
    - UNDERLINE U-2.2, U-2.18
    - VBAR U-2.2, U-2.18
- Printing
  - a file during the run O-2.7
  - from PC/Windows W-3.9

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- SURVEY tables S-1.19
- Printing a correlation matrix
  - BPRINT B-3.6
- Printing your output I-2.4
- PRIOR
  - in DISCRIM command A-4.4
- Prior probabilities
  - in DISCRIM command A-4.4
- Probability functions P-7.4
- Probability level
  - in ANOVA command A-6.5
  - in REGRESSION command B-4.6
- PROBBIN
  - PPL function P-7.4, P-7.10
- PROBCHI
  - PPL function P-7.4, P-7.10
- PROBF
  - PPL function P-7.4, P-7.10
- PROBIT
  - PPL function P-7.6
- Probit distribution P-7.6
- PROBNORM
  - PPL function P-7.4, P-7.10
- PROBPOIS
  - PPL function P-7.4, P-7.10
- PROBT
  - PPL function P-7.5, P-7.10
- PROCESS I-9.4, I-9.7, P-1.3, P-1.6, P-3.9,
  - P-3.13**
  - summary P-3.17
- Product-limit estimation
  - in SURVIVAL command A-7.7
- PROGRESS
  - in TURF command I-8.29
- PROMAX **A-5.5**
  - identifiers
    - COR A-5.5
    - COSINE A-5.5
    - INFAC A-5.5
    - OUTFAC A-5.5
    - TRANS A-5.5
  - summary A-5.10
- PROMPT **U-3.8**
  - arguments
- LONG U-5.3
- SHORT U-5.3
- messages U-5.2
- Prompts
  - command entry I-2.5
  - data entry I-2.11
  - editor I-2.10
- Proportional fonts O-2.3
- PSAUTO I-1.8, I-1.10, **I-10.7**, I-10.13,
  - W-1.8, W-1.10, W-2.3, W-2.13, W-2.16, U-2.11
- PSDATA I-1.8, I-1.10, I-10.13, W-1.8,
  - W-1.10, W-2.3, W-2.16, U-2.11
- PSFILES I-1.8, I-1.10, I-2.2, I-10.13,
  - W-1.7, W-1.10, W-2.3, W-2.13, W-2.16, W-3.1, W-5.15, U-2.8, U-2.11
- PSHELP I-1.7, I-1.10, I-10.13, W-1.7,
  - W-1.10
- PSKEY I-1.7, I-1.10, W-1.7, W-1.10
- PSTART I-1.8, I-1.10, W-1.8, W-1.10,
  - U-2.10
  - summary W-1.10
- P-STAT commands W-1.5
- P-STAT editor W-4.1
  - control window W-4.2
  - delete W-4.4
  - edit or change W-4.4
  - execute W-4.4
  - full screen example W-4.8
  - input W-4.4
  - moving the pointer W-4.3
  - quit W-4.4
  - saving W-4.2
  - syntax W-4.4
  - type W-4.4
- P-STAT Programming Language
  - see PPL
- P-STAT system file W-1.5, W-5.3
  - check the status W-2.2
  - comparing W-2.2
  - erasing W-2.3
  - format W-2.4, W-2.5
  - legal names W-2.6

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- limits W-2.5
- listing W-2.11
- locating W-2.3
- missing data W-2.6
- names of available files W-2.1
- previous or current version P-1.3
- show contents W-2.2
- P-STAT system Files I-2.2
- PSTAT.FILE
  - in CHECK.LABELS command I-5.9, S-11.11
  - in SAVE.LABELS command I-5.9, S-11.10
- PSTAT.INI
  - PC/Windows installation file I-1.10
- PSTATDIR
  - alternate windows folder I-1.10
- PSTEMP I-1.8, I-1.11, I-3.2, **I-10.9**, I-10.14, W-1.8, W-1.10
- Punctuation
  - in commands I-3.2
- PUT
  - in POSTSCRIPT command O-2.12, O-2.22
  - in TEXTWRITER command P-11.2
  - PPL instruction P-3.8, P-3.9, P-3.19
- PUT.PAGE
  - in POSTSCRIPT command O-2.7, O-2.20, O-2.21
- PUTL
  - in TEXTWRITER command P-11.2
  - PPL instruction P-3.11
- PUTL.CHARS
  - in TEXTWRITER command P-11.32
- Q**
- Q1 I-9.2
- Q.CLUSTER A-3.1**
  - identifiers
    - ANOVA A-3.4, A-3.10
    - CARRY A-3.3, A-3.10
    - CONVERGE A-3.8, A-3.10
    - DRIFT A-3.8, A-3.11
    - EUCLIDEAN A-3.8, A-3.11
    - FIXED A-3.8, A-3.11
    - MAX.MISSING A-3.4, A-3.11
    - OUT A-3.3, A-3.11
    - SAVE.CENTERS A-3.3, A-3.11
    - SHOW.CENTERS A-3.6, A-3.11
    - SHOW.NS A-3.7, A-3.11
    - SQ.EUCLIDEAN A-3.8, A-3.12
    - STANDARDIZE A-3.3, A-3.12
    - TRY A-3.3, A-3.10
    - WEIGHT A-3.4, A-3.12
- large files A-3.8
- summary A-3.10
- QF
  - in ROTATE command A-5.3
- QFONT
  - in SURVEY command S-7.6, S-7.14
- QTR
  - in ROTATE command A-5.3
- Qualitative data B-5.3
- Quantile plots B-6.4
- Quantiles B-1.1
- Quantitative data B-5.4
- Quantities
  - in banner variables S-3.9
- QUARTER function P-10.7, P-10.21
- Quartile range
  - in COUNTS command I-7.1
- QUARTILES
  - in PERCENTILES command B-1.10
  - in SURVEY command S-5.20, S-8.21, S-8.26
- QUESTION
  - combining with LABELS S-5.4
  - in SURVEY command S-1.7, S-5.4, S-5.25
- Questionnaire data S-1.1
- QUIT
  - EDITOR instruction U-5.4
  - in UPDATE command F-11.6
  - output U-3.2
- QUITCOMMAND
  - PPL instruction P-3.14, P-3.18
- QUITFILE
  - PPL instruction P-3.14, P-3.18

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- QUITRUN  
 PPL instruction P-3.14, P-3.18
- QUOTES  
 in SPREADSHEET output S-6.16, S-6.24  
 in UNMAKE command F-2.11, F-2.17
- Q2 I-9.2  
 quit command U-3.2
- Q3 I-9.2  
 quit macro U-3.2
- R**
- R squared B-3.4
- R squared, multiple  
 in INVERT command A-1.7  
 in REGRESSION command B-4.5
- RANBIN  
 PPL function P-7.1, P-7.9
- Random  
 assignment P-7.3  
 data generation P-7.1  
 number functions P-7.1  
 sampling P-7.2  
 with replacement P-7.2
- RANGE  
 in BOXPLOT command O-6.9, O-6.13  
 in HIST command O-7.3  
 in PLOT command O-3.4  
 in SURVEY command S-5.20
- Ranges  
 for columns in SURVEY S-3.3  
 for rows  
 in SURVEY S-2.21  
 for rows in SURVEY S-2.1  
 in COUNTS command I-7.1
- RANK F-7.8, F-7.12  
 identifiers  
 CARRY F-7.9, F-7.13  
 DOWN F-7.13  
 OUT F-7.9  
 USE F-7.9, F-7.13  
 in SURVEY command S-2.3, S-2.22  
 partial S-2.5  
 tied values F-7.8
- Rank and subtotals  
 interactions S-4.10, S-4.23
- RANK COLUMNS  
 in SURVEY command S-3.4, S-3.29
- RANK CONTROLS NETS  
 in SURVEY command S-4.11, S-4.12,  
 S-4.23
- RANK CONTROLS SUBTOTALS  
 in SURVEY command S-4.11, S-4.12,  
 S-4.23
- Rank correlation B-5.41, B-5.44
- RANK SUMMARY  
 in SURVEY command S-2.11, S-2.23
- RANK WITHIN NETS  
 in SURVEY command S-4.10, S-4.23
- RANK WITHIN SUBTOTALS  
 in SURVEY command S-4.10, S-4.23
- RANK.CONTROL  
 in SURVEY command S-2.4, S-2.23
- RANNORM  
 PPL function P-3.7, P-7.1, P-7.9
- RANTABLE  
 PPL function P-7.1, P-7.9
- RANUNI  
 PPL function P-7.1, P-7.9
- Rao's approximate F  
 in CANONICAL.COR command A-2.4
- Ratings tables S-3.24
- Ratio data B-5.4
- RAW  
 in CANONICAL.COR command A-2.8
- RE.IDENTIFY  
 in LIST command I-6.17
- REACH.RESULTS  
 in TURF command W-3.6, W-5.10
- REACH.STATS  
 in TURF command I-8.28
- READ  
 in TABFILE.IN command F-2.13
- RECIP.ROOT  
 in EDA command B-6.3
- RECIP.SQUARE  
 in EDA command B-6.3
- RECIPROCAL  
 in EDA command B-6.3

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

## RECODE

arguments P-4.6  
 complex P-4.6  
 exact matches with XRECODE P-4.12  
 PPL function P-4.3, P-4.14, P-6.24  
 tests P-4.6

## REFERENCES A-7.17

## REFORMAT I-1.2, W-1.2, W-2.2, U-1.12

### identifiers

AFTER U-1.7, U-1.12  
 ANYWHERE U-1.7, U-1.12  
 BYTES U-1.7, U-1.12  
 FIRST U-1.7, U-1.12  
 INSERT U-1.6, U-1.12  
 LAST U-1.7, U-1.12  
 OUT U-1.6, U-1.12  
 REMOVE U-1.6, U-1.13  
 VALUES U-1.7, U-1.13

## REFORMAT.DATE function P-10.5, P-10.20

## REGRESSION W-2.3, B-4.1, **B-4.2**

adjusted R squared B-4.5  
 all-possible subsets B-4.14  
 analysis of variance B-4.5  
 coefficient B-4.1, B-4.6  
 constant, Y-intercept B-4.1, B-4.5  
 degrees of freedom B-4.5  
 F value B-4.5  
 identifiers  
   BY B-4.8, B-4.20  
   COR B-4.20  
   DES B-4.20  
   TRANSFORM B-4.10, B-4.21  
   WEIGHT B-4.10, B-4.21  
 interpreting output B-4.5  
 LAG of independent variables B-4.11  
 Log transformations B-4.10  
 mean square B-4.5  
 missing data B-4.9, B-4.16  
 multiple R B-4.5  
 multiple R squared B-4.5  
 polynomial distributed lags B-4.12  
 pre and post variables B-4.1  
 probability level B-4.6

## regression equation B-4.6

size constraints B-4.2  
 standard error of B B-4.6  
 standard error of estimate B-4.5  
 standardized coefficient B-4.6  
 subcommands

  AGAIN B-4.7, B-4.21  
   ALL.POSSIBLE B-4.14, B-4.21  
   ATLEAST B-4.16, B-4.21  
   ATMOST B-4.16, B-4.21  
   COEF B-4.8, B-4.21  
   COMPLETE B-4.9, B-4.21  
   DEPENDENT B-4.2, B-4.7  
   F.DELETE B-4.17, B-4.21  
   F.ENTER B-4.17, B-4.21  
   INDEPENDENT B-4.7, B-4.22  
   MAX B-4.14, B-4.22  
   MISSING B-4.9, B-4.22  
   NO DELETE B-4.22  
   NO REPORT B-4.23  
   NO STEP B-4.22  
   NODELETE B-4.16  
   NOSTEP B-4.2, B-4.16  
   ORDER B-4.17, B-4.22  
   ORIGIN B-4.10, B-4.22  
   OUT B-4.8, B-4.22  
   P.DELETE B-4.17, B-4.23  
   P.ENTER B-4.17, B-4.23  
   PR B-4.8, B-4.23  
   REPORT B-4.8, B-4.16  
   RESET B-4.8, B-4.23  
   STAND.COEF B-4.8, B-4.23  
   START B-4.17, B-4.23  
   STATS B-4.23  
   STEP B-4.23  
   SUMMARY B-4.8, B-4.16, B-4.23  
   TEST B-4.14, B-4.23  
   TOL B-4.16, B-4.24  
   USE.MEAN B-4.9, B-4.24

### summary B-4.20

## Regression equation B-4.6

## Relational files I-10.2

## RENAME

  in CONCAT command F-8.2

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- PPL instruction P-2.25, P-5.23
- variables P-2.22, P-2.26
- REORDER
  - in TURF command I-8.22
- REPEAT
  - in COLLATE command F-9.10, F-9.21
  - PPL instruction P-3.6, P-3.18, P-7.2
- Repeating a run I-3.8
- REPLACE **I-10.5**
  - EDITOR instruction U-6.20
  - in UPDATE command F-11.5
  - in UPDATE command F-11.6
- Replace
  - text in full screen command editor U-5.7
- REPLACE.QUOTES
  - in UNMAKE command F-2.11, F-2.17
- Replacing missing values with mean
  - STANDARDIZE B-1.14
- REPORT
  - in DUPLICATES command F-10.12, F-10.23
  - in REGRESSION command B-4.8, B-4.16
  - in RESISTANT.LINE B-6.15
- REPORT ALL RESULTS
  - in SURVEY command S-8.23, S-8.26, S-9.10
- Report writing I-1.3, W-1.2, P-3.9
- REQUIRE
  - in SURVEY command S-8.26, S-9.9
- RESCALE
  - in PLOT command O-5.15, O-4.6
  - in PLOT commands O-4.5
- Reserved words
  - TO I-3.2
- RESET
  - COUNTS identifier I-7.10
  - Counts identifier I-7.1
  - in BOXPLOT command O-6.15
  - in CHECK command F-12.16
  - in EDA command B-6.3
  - in PLOT command O-3.6
  - in REGRESSION command B-4.8
  - in SURVEY command S-1.25, S-10.1, S-10.29
- in TITLES command I-5.12, S-11.5
- RESET RANGE
  - in BOXPLOT command O-6.9
- RESET SUBTOTALS S-4.5
  - in SURVEY command S-4.23
- RESET TICKS
  - in BOXPLOT command O-6.6
- Residual variance
  - in ANOVA command A-6.2, A-6.7, A-6.24
- RESIDUALS B-4.1, **B-4.24**
  - identifiers
    - COEF B-4.24
    - DES B-4.24
    - PRED B-4.24
    - RES B-4.25
    - USE.MEAN B-4.25
  - in MEDIAN.POLISH B-6.23
  - in RESISTANT.LINE B-6.15
  - in ROOTOGRAM B-6.11
- RESISTANT.LINE
  - EDA subcommand B-6.15
  - summary B-6.29
- RESISTANT.SMOOTH
  - EDA subcommand B-6.17
  - summary B-6.30
- RESPONSE
  - in ANOVA command A-6.44
- RESPONSE.WEIGHTS
  - in TURF command I-8.29
- RESTART
  - in SURVEY command S-10.1, S-10.29
- RESTORE
  - EDITOR instruction U-3.5, U-6.16
- RETAIN
  - PPL instruction P-2.14, P-2.25
- RETURN U-2.8, U-3.1
  - EDITOR instruction U-7.6
  - identifiers
    - HOLD U-2.9
    - in transfer file U-2.9
- REVERSE
  - in PLOT command O-3.11

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

**RIGHT**

in CANONICAL.COR command A-2.2  
 in TITLES command I-5.10, S-11.3  
 PPL function P-9.7, P-9.28

**RIGHT.EDGE**

in BOXPLOT command O-6.12  
 in PLOT command O-5.1  
 in POSTSCRIPT.SETUP command  
 O-2.4, O-2.18  
 in SURVEY command S-7.3, S-7.8,  
 S-7.15

**RIGHT.EXTRA**

in COLLATE command F-9.7, F-9.21

**RMOVETO**

in POSTSCRIPT command O-2.11

**ROOTOGRAM**

EDA subcommand B-6.10  
 summary B-6.30

**ROOTS**

in EIGEN command A-1.8  
 in FACTOR command A-5.3

**ROTATE A-5.3**

canonical structure coefficients A-2.6  
 identifiers  
 EF A-5.3  
 ETR A-5.3  
 MAX A-5.4  
 QF A-5.3  
 QTR A-5.3  
 VF A-5.3  
 VTR A-5.3  
 size constraints A-5.4  
 summary A-5.11

**ROUGH.OUT**

in RESISTANT.SMOOTH B-6.19

**ROUND**

in SAMPLE command S-12.15, S-12.20  
 PPL function P-6.2, P-6.21

Rounding function P-6.2

Row labels I-10.2

Row variables

in SURVEY command S-1.1

**ROW.TOTALS**

in SURVEY command S-1.11, S-1.29

**ROW.TOTALS BASED RESPONSES**

in SURVEY command S-3.16, S-3.29

**ROW.VARIABLE**

in CODED.TABLE B-6.20  
 in MEDIAN.POLISH B-6.22

**ROWS**

in CORRELATE command B-3.8

**RSQ**

in INVERT command A-1.7

**RTOKEN**

PPL function P-9.10, P-9.29

**RTRIM**

PPL function P-9.12

**RUN P-12.2, P-12.11, P-12.28**

a macro with arguments W-5.16  
 Executing a macro W-2.3  
 using a macro S-10.11

**RUN.PAGE.NUMBER**

in LIST command I-6.16, I-6.27  
 in SURVEY command S-5.23  
 in TITLES command I-5.13, S-11.5

**RUNS**

in NP.TEST command B-5.19  
 summary B-5.51

Runs test B-5.19

R, multiple

in INVERT command A-1.7  
 in REGRESSION command B-4.5

r, Pearson product-moment B-3.2

**S****SAME**

in CONCAT command F-8.3, F-8.10

**SAMPLE I-1.3, W-1.3, S-12.10**

generating random samples S-12.10  
 identifiers

BY S-12.11, S-12.19

CASES S-12.11, S-12.19

CEILING S-12.14, S-12.20

FLOOR S-12.15, S-12.20

MAX.GROUP S-12.13, S-12.19

MIN.GROUP S-12.13, S-12.19

OTHERS S-12.10, S-12.19

OUT S-12.10, S-12.19



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- PERCENT S-12.11, S-12.19
- ROUND S-12.15, S-12.20
- USE.WEIGHTS S-12.19
- WEIGHT S-12.12, S-12.20
- in SURVEY command
  - standard deviation S-8.26
- limitations S-12.16
- summary S-12.18
- Sample balance S-1.21, S-12.1
- SAVE.CENTERS
  - in Q.CLUSTER command A-3.3
- SAVE.LABELS I-5.1, **I-5.7**, W-2.2, S-11.1, S-11.9
  - checking label format I-5.8, S-11.10
  - identifiers
    - CHECK I-5.8, I-5.15, S-11.10, S-11.14
    - PSTAT.FILE I-5.9, I-5.15, S-11.10, S-11.14
  - summary I-5.15, S-11.13
- Saving a P-STAT system file W-2.12
  - autosave I-2.13
- SCALE
  - in BOXPLOT command O-6.8, O-6.13
  - in PLOT command O-5.3, O-5.15, O-3.12
  - in POSTSCRIPT command O-2.12, O-2.22
  - in STEM.AND.LEAF B-6.9
  - in SURVEY command S-7.16
- SEPARATE
  - in BOXPLOT command O-6.2, O-6.9, O-6.13
- TOGETHER
  - in BOXPLOT command O-6.9, O-6.13
- Scaling symbols O-2.12
- Scatter plots O-3.1
  - correlation B-3.2
- SCHEFFE test A-6.36
- Scratch variable names
  - rules for I-3.14
- Scratch variables W-2.6, P-1.2, P-3.12, P-8.3
  - in SUBFILES command P-12.23
- SCREEN I-9.2, I-9.10, **U-3.2**, U-3.3, **U-3.8**, U-3.8
  - setting the size S-11.1
- SDATA
  - in F.COEF command A-5.5
  - in STANDARDIZE command B-1.14
- SDEV
  - in AGGREGATE command F-10.4, F-10.7, F-10.22
  - PPL function P-6.21
- SDEV.GOOD
  - PPL function P-6.22
- SECONDS function P-10.6, P-10.21
- SECONDS.MIDNIGHT function P-10.6, P-10.21
- Semicolon I-2.15, I-3.4
  - in ANOVA command A-6.18, A-6.20
- SEPARATE **F-6.8**
  - data cleaning F-6.8
  - identifiers
    - BY F-6.8
    - EXTRA F-6.10
  - in TTEST command B-2.5
- SEQUENCE
  - in DUPLICATES command F-10.13, F-10.24
- SET
  - PPL instruction P-2.1, P-2.9, P-2.25, P-9.2
- SET.LABELS S-1.2
  - in SURVEY command S-1.2
  - in the SURVEY command S-2.23
- SET.MISS.TO.ZERO
  - in TURF command I-8.10, I-8.29
- SETFONT
  - in POSTSCRIPT command O-2.12, O-2.22
- SF
  - in FACTOR command A-5.2
- Shapiro-Wilk test of normality I-7.1, I-7.13
- SHARED RANGES
  - in SURVEY command S-2.3, S-2.23
- SHORT I-5.18
  - general identifier I-5.18

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in PAIRED.TTEST command B-2.7
- used in LIST command I-3.11
- SHORT.16
  - general identifier I-3.15, I-5.18, I-6.28, U-2.6
- SHORT.OLD
  - general identifier I-3.15, I-5.18, I-6.28, U-2.6
- SHORT.ONLY
  - general identifier
  - SHOW command only I-5.18
- SHORT.TAGS
  - general identifier I-5.18, I-6.28, U-2.6
- SHOW F-12.13, **U-2.7**
  - general identifiers
  - TAGS I-5.2
  - TEXT I-5.2
  - identifiers
    - ACROSS U-1.13
    - COLUMNS U-1.13
    - NO BREAK U-1.13
    - NO HEAD U-1.13
    - SINGLE U-1.13
    - SORT U-1.13
  - in SURVEY command S-1.29
  - in TITLES command I-5.11, S-11.4
  - in TURF command I-8.30
  - summary U-1.13
- SHOW DESIGN
  - in ANOVA command A-6.20, A-6.44
- SHOW NAMES
  - in PLOT command O-3.3
- SHOW SETTINGS
  - in PLOT command O-3.3
- SHOW VARIABLES
  - in ANOVA command A-6.22, A-6.44
  - in PLOT command O-3.3
- SHOW.ARRAYS **P-8.7**, P-8.28
- SHOW.CENTERS
  - in Q.CLUSTER command A-3.6
- SHOW.ENV.VARS **U-2.18**
- SHOW.KEY **U-2.18**
- SHOW.MACROS **P-12.11**, P-12.28, P-12.29
  - identifiers
- FILE P-12.11, P-12.29
- NAMES P-12.28
- SHOW.NS
  - in Q.CLUSTER command A-3.7
- SHOW.VARIABLES
  - in EDA command B-6.3
- SHOWBYTES I-1.2, W-1.2, W-2.2, **U-1.4**, U-1.14
  - identifiers
    - BREAK and NO BREAK U-1.6, U-1.14
    - CHUNK U-1.6, U-1.14
    - COLUMNS U-1.6, U-1.14
    - FIND U-1.5, U-1.14
    - FIRST U-1.5, U-1.14
    - GAP U-1.6, U-1.14, U-2.18
    - HEAD and NO HEAD U-1.14
    - HEAD and NO HEAD, U-1.6
    - LAST U-1.5, U-1.14
    - MAX U-1.5, U-1.14
    - PREVIOUS U-1.14
    - ZERO U-1.6, U-1.14
- SHOWPAGE
  - in BOXPLOT command O-6.4, O-6.12
  - in PLOT command O-5.2, O-5.15
  - in POSTSCRIPT.SETUP command O-2.6, O-2.19
  - in SURVEY command S-7.9, S-7.16
  - in TEXTWRITER command P-11.21, P-11.37
- SIGN
  - in NP.TEST command B-5.24
  - summary B-5.53
- Sign test B-5.24
- Significance tests
  - and missing data S-9.11
  - and weights S-9.10
  - MARK ALL TESTS S-9.12
  - of cells S-9.6, S-9.19
  - with multiple test values S-9.8
- Simple PPL IF statement W-5.6
- Simultaneous equations, solving A-1.7
- SIN
  - PPL function P-6.3, P-6.21

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

Sine function P-6.3

**SINGLE**

in **DUPLICATES** command F-10.24  
 in **PLOT** command O-3.15

**SIZE**

in **DUPLICATES** command F-10.13,  
 F-10.24  
 in **TURF** command I-8.28, W-5.12  
 PPL function P-9.8, P-9.28

Size constraints

in **COUNTS** command with frequency ordering I-7.17  
 in **DISCRIM** command A-4.1  
 in **F.COEF** command A-5.6  
 in **NEWFAC** command A-5.6  
 in **OVERALL.DES** command B-1.4  
 in **RANK** command F-7.9  
 PPL modifications P-2.3  
 value labels in **LIST** command I-6.7

**SJOIN A-1.8**

identifiers  
 A11 A-1.8  
 A12 A-1.8  
 A22 A-1.8  
 OUT A-1.8  
 summary A-1.14

Skewness

in **COUNTS** command I-7.1, I-7.12  
 in **PERCENTILES** command B-1.9

**SKIP**

in **LIST** command I-6.5  
 in **POSTSCRIPT** command O-2.11,  
 O-2.22  
 in **SURVEY** command S-1.13, S-1.29  
 in **UPDATE** command F-11.6  
 use with nested rows S-2.6

**SKIP.COUNTER**

in **LIST** command I-6.5, I-6.14

**SKIP.OMIT**

in **LIST** command I-6.14

**SKIP.RULES S-6.18**

in **SURVEY** command S-6.18, S-6.24

**SKIP.VARS**

in **LIST** command I-6.13, I-6.14

Slash

division operator P-2.12  
 in **ANOVA** command A-6.11, A-6.41

Slash, back

in **MATCHES** operator P-9.21

Slash, double

in **ANOVA** command A-6.41  
 PPL operator P-9.4

Slash, triple

PPL operator P-9.5

**SLEEP U-2.18**

**SMOOTH.OUT**

in **RESISTANT.SMOOTH B-6.19**

**SNK**

Student-Neuman-Keuls test A-6.36

**SORT W-2.4, F-7.1, F-7.10**

checking sort order F-7.6

identifiers

BY F-7.2, F-7.10

DOWN F-7.3, F-7.10

EXACT F-7.2, F-7.10

OUT F-7.10

UP F-7.3, F-7.10

WITHIN F-7.4, F-7.10

in **COLLECT** function P-8.21

in **MEDIAN.POLISH B-6.23**

merging sorted files F-7.4

order F-7.1

preserving sequences F-7.4

specifying direction F-7.3

summary F-7.10

**SPACE**

in **BOXPLOT** command O-6.5, O-6.12

in **PLOT** command O-5.5, O-5.15

Space

between plots O-5.6

for legend O-5.6

for Y axis labels O-5.6

in plot corners O-5.6

Sparse data values S-10.17

Spearman rank correlation F-7.1, B-3.1,  
 B-5.41

**SPLIT**

example P-9.18

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in TET command B-3.11
- PPL function P-8.30
  - CARRY option P-8.13
  - CREATE option P-8.14
  - CYCLE option P-8.17
  - INDEX option P-8.16
  - SPLIT \* P-8.24
  - STEP option P-8.17
  - USE option P-8.14
- SPREAD
  - in SURVEY command S-1.13, S-6.12, S-6.24
  - in TEXTWRITER command P-11.7, P-11.32
- SPREADSHEET
  - in SURVEY command S-6.16, S-6.22
- SPSS W-3.13
  - files, reading and writing W-2.4
- SPSS.IN **I-4.3**, I-4.12, W-2.3, **F-2.5**, F-2.14, F-2.15, P-1.1
  - identifiers
    - BREAK F-2.15
    - FILE I-4.3, F-2.5
    - LABELS I-4.3, F-2.5, F-2.14
    - SYSTEM.MISSING I-4.3, F-2.5
- SPSS.OUT W-2.4, **F-2.8**, F-2.15
  - identifiers
    - BREAK F-2.8
    - FILE F-2.8, F-2.15
    - LABELS F-2.8, F-2.15
    - M1 F-2.9
    - M1, M2 and M3 F-2.16
    - MAX.PLACES F-2.8
    - MAX.STRING F-2.9, F-2.15
    - MAX.VALUE.LABEL F-2.9, F-2.15
    - MAX.VAR.LABEL F-2.9, F-2.15
    - MISSING F-2.9, F-2.15
    - M2 F-2.9
    - M3 F-2.9
- SQ.EUCLIDEAN
  - in Q.CLUSTER command A-3.8
- SQRT
  - PPL function P-6.3, P-6.21
- SQUARE
  - in EDA command B-6.3
- Square root function P-6.3
- SQUARE.ROOT
  - in EDA command B-6.3
- Squared multiple correlations A-1.7
- Squared ranks test B-5.21, B-5.34
- SQUARED.RANKS
  - in NP.TEST command B-5.21, B-5.34
  - summary B-5.52, B-5.57
- SQUEEZE
  - EDITOR instruction U-6.18
  - in SUBSTITUTE.VL command F-12.19
- SQUEEZE COLUMNS
  - in SURVEY command S-3.3, S-3.29
- SQUEEZE ROWS
  - in SURVEY command S-2.23
- SQUEEZE SUBTOTALS
  - in SURVEY command S-4.13, S-4.23
- STAND.COEF
  - in REGRESSION command B-4.8
- Standalone PPL commands P-1.3, P-1.6, P-3.12, P-3.17
- Standard deviation
  - computation of S-8.14
  - in COUNTS command I-7.1
  - in description file B-1.2
  - in SURVEY command S-1.8, S-5.20
- Standard Error
  - in SURVEY command S-5.20
- Standard error of B
  - in REGRESSION command B-4.6
- Standard error of mean
  - in COUNTS command I-7.1
- STANDARD.DEV
  - in SURVEY command S-1.30
- STANDARD.ERROR
  - in SURVEY command S-8.13
- STANDARDIZE **B-1.14**
  - identifiers
    - CARRY B-1.14, B-1.18
    - DES B-1.14, B-1.18
    - MDATA B-1.14, B-1.19
    - SDATA B-1.14
    - STAY.MISSING B-1.19

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- WEIGHT B-1.14, B-1.19
  - in Q.CLUSTER command A-3.3
  - replacing missing scores with mean B-1.14
  - summary B-1.18
- Standardized coefficient
  - in REGRESSION command B-4.6
- START
  - in MEDIAN.POLISH B-6.21
  - in REGRESSION command B-4.17
- STATIONARY TITLES
  - in SURVEY command S-10.27, S-10.29
- Statistical analysis I-1.4, W-1.3
- Statistics
  - in SURVEY command S-5.20
- Statistics, descriptive B-1.1
- Statistics, summary
  - in COUNTS command I-7.1
- STATS
  - in CANONICAL.COR command A-2.5
  - in CORRELATE command B-3.14
  - in COUNTS command I-7.1, I-7.10
- STATUS **U-3.9**
  - identifier in SURVIVAL command A-7.2
  - of system attributes W-2.2
- STATUS.DATE function P-10.5, P-10.20
- STAY.MISSING
  - in STANDARDIZE command B-1.14
- Std. Error of Est.
  - in REGRESSION command B-4.5
- STEM.AND.LEAF
  - EDA subcommand B-6.8
  - summary B-6.31
- STEP
  - in DISCRIM command A-4.1
  - in SPLIT function P-8.17
  - in TURF command I-8.10, I-8.28
- STEP.DOWN
  - PPL function P-7.7, P-7.12
- STEP.UP
  - PPL function P-7.7, P-7.11
- STEPS
  - in MEDIAN.POLISH B-6.21
  - in RESISTANT.LINE B-6.15
- PPL function P-7.7, P-7.12
- Stepwise regression B-4.2, B-4.16
- Stopping a run I-2.5
- STRATA
  - in SURVIVAL command A-7.2
- Stratum
  - in ANOVA command A-6.7, A-6.8
- STREAM
  - in TEXTWRITER command P-11.7, P-11.32
- STRING.BOUNDARY
  - in MAKE command I-4.10, F-3.9, F-3.13
  - in MAKE.FIXED command F-4.7
  - in TEXTFILE.IN I-4.2, I-4.13
- STRIP
  - in MAKE command I-4.10, F-3.9, F-3.13
  - in MAKE.FIXED command F-4.4
- Structure coefficients
  - in CANONICAL.COR command A-2.6
- STUB
  - in LIST command I-6.15
- STUBS
  - in SURVEY command S-1.1, S-1.2, S-1.27, S-2.21
- SUB
  - in FREQ command B-1.7
  - in HIST command O-7.4
- Subcommand
  - buffer size S-10.13
- Subcommand records I-2.5
- SUBFILES W-1.4, **P-12.23**, P-12.23, S-10.9
  - identifiers
    - BY P-12.23, P-12.29
    - DOWN P-12.23, P-12.29
    - EXACT P-12.29
    - FREQUENCIES P-12.24, P-12.29
    - GROUPS P-12.25, P-12.29
    - UP P-12.23, P-12.29
  - use of scratch variables P-12.23
  - used in TURF macro W-5.15
- Subgroups, creating F-1.2
- SUBSET
  - in COLLATE command F-9.9, F-9.21
- Subsets, all-possible in REGRESSION B-4.14

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- Subsets, creating F-1.2
- SUBSTITUTE.VL **F-12.8**, S-10.9
  - identifiers
    - LABELS F-12.8, F-12.19
    - OUT F-1.6, F-12.8, F-12.19
    - SQUEEZE F-12.19
    - VARIABLES F-12.9, F-12.19
    - VL.ONLY F-12.19
  - summary F-12.18
- SUBSTITUTE.XL **F-12.11**, F-12.19, U-2.8
  - identifiers
    - LABELS F-12.20
    - NO SPREAD F-12.20
    - OUT F-12.20
    - USE.ALL F-12.13, F-12.20
    - VARIABLE F-12.13, F-12.20
    - XL.ONLY F-12.20
- SUBSTRING
  - PPL function P-9.9, P-9.28
- SUBTOTALS
  - in SURVEY command S-1.7, S-4.23, S-5.25
  - indenting S-5.13
  - indenting levels S-5.14
  - position in table S-4.9
- Subtotals for banner variables S-9.5
- SUBTRACT
  - in SURVEY command S-9.1
- SUBTRACT dates and times P-10.21
- Subtraction operator - P-2.12
- Subtraction sign
  - in ANOVA command A-6.41
  - in MATCHES operator P-9.21
- SUFFIX
  - in AGGREGATE command F-10.5, F-10.9, F-10.23
  - in DUPLICATES command F-10.17, F-10.26
- SUM
  - in AGGREGATE command F-10.4, F-10.22
  - in DUPLICATES command F-10.17, F-10.25
  - PPL function P-6.22
- Sum
  - in COUNTS command I-7.1
- Sum of squares
  - corrected
    - in COUNTS command I-7.13
  - in COUNTS command I-7.1
  - in REGRESSION command B-4.5
  - normalizing A-1.4
  - uncorrected
    - in COUNTS command I-7.13
- SUM.G
  - in DUPLICATES command F-10.17, F-10.25
- SUM.GOOD
  - PPL function P-6.22
- SUMMARY F-8.9, B-3.13
  - in MAKE command F-3.5, F-3.13
  - in MAKE.FIXED command F-4.2, F-4.9
  - in MAP command F-12.5, F-12.8, F-12.18
  - in REGRESSION command B-4.8, B-4.16
  - in RESISTANT.LINE B-6.15
  - in SURVEY command S-1.7, S-5.18, S-5.25
- Summary statistics
  - using AGGREGATE W-2.4
- Summary statistics, table of S-3.20, S-3.25
- Summary tables
  - group stubs S-2.10
- SUMS
  - in SURVEY command S-1.30, S-5.20
  - using another variable S-1.22, S-1.30
- SURVEY I-1.3, W-1.2, W-2.2, **S-1.1**, S-2.10, S-2.11, S-6.1
  - 1-way tables S-1.6
  - abbreviations S-1.6
  - columns S-1.2
  - custom labeling S-6.1
  - data types S-1.4
  - display percents S-3.8
  - identifiers
    - BY S-10.7, S-10.28
    - CHARACTER.SET S-7.1, S-7.3

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- CONTENTS S-10.28  
 DECIMAL.COMMA S-6.22  
 DEF S-10.1, S-10.28  
 DOUBLE S-8.24  
 ECHO S-1.27  
 MEDIAN S-8.15  
 NO LEAD.BLANK S-6.21, S-6.22  
 OUTPUT.WIDTH S-7.2  
 PAGE.NUMBER S-5.3, S-5.23,  
     S-10.4  
 POPULATION S-8.14, S-8.24  
 POSTSCRIPT O-2.1  
 RUN.PAGE.NUMBER S-5.23  
 SPREADSHEET S-6.16, S-6.22  
 TABLE.NUMBER S-10.4, S-10.28  
 TABS S-6.14, S-6.22  
 TITLES S-1.26  
 UNDERLINE S-6.11  
 WEIGHT S-1.21, S-1.27, S-12.6  
 multiple response variables S-3.14  
 nesting rows S-2.6  
 printing the tables S-1.19  
 ranges for rows S-2.21  
 ratings tables S-3.24  
 rows S-1.2  
 statistics S-3.20, S-3.25  
     in SUMMARY section S-5.18  
 subcommands S-1.6, S-6.18  
   ABBREVIATION S-1.27  
   ADD S-3.6, S-9.1, S-9.18  
   AGAIN S-2.22  
   ASSIGN S-10.23, S-10.28  
   BANNERS S-1.4, S-1.27, S-3.1,  
     S-3.7, S-3.27  
   BASE S-1.27  
   BFONT S-7.5, S-7.14  
   BODY S-1.9, S-1.27, S-5.12, S-5.24  
   BORDER S-7.8, S-7.15  
   BOTTOM.EDGE S-6.24, S-7.3,  
     S-7.11, S-7.15  
   BREAK S-5.1, S-5.23  
   BVAR.LABELS S-5.21, S-5.26  
   BVAR.PER.PAGE S-3.1, S-3.28  
   CELL.CHI S-5.13, S-5.23, S-8.12  
   CELL.WIDTH S-1.13, S-1.27  
   CENTER LABELS S-5.24  
   CHARACTER S-6.22  
     BREAK S-1.16, S-1.27, S-6.23  
     NEWLINE S-6.7  
     PERCENTS S-6.8, S-6.23  
     SUBTOTALS S-6.4, S-6.23,  
       S-7.11  
     TEST S-8.24  
     UNDERLINE S-6.10, S-6.23  
     VALUE.LABELS S-5.7  
     VARIABLE.LABELS S-6.6,  
       S-6.23  
     ZERO S-5.12, S-6.6, S-6.22  
   CHI S-8.11, S-8.24  
   COMBINE S-4.14, S-4.21  
   COMMAS S-6.11, S-6.23  
   COMPACT S-1.13, S-6.12, S-6.23  
   COMPRESS FORMAT S-7.12,  
     S-7.15  
   COMPUTE S-8.2, S-8.24  
   CONTENTS S-10.4, S-10.28  
   CONTROL COLUMN  
     ORDER  
       OFF S-3.27  
       USING LABELS S-3.4,  
         S-3.27  
       RANK S-3.5, S-3.27  
   CONTROL ROW  
     ORDER  
       OFF S-2.6  
       USING LABELS S-2.6,  
         S-2.22  
       RANK S-2.6, S-2.22  
   COUNT S-2.22, S-3.15  
   CRAMER.V S-8.13  
   CREATE S-3.14, S-3.27  
   CROSS.COMPARE S-3.19, S-3.28  
   DEFINE S-4.2, S-4.5, S-4.21, S-6.4  
   DEFINE.NET S-4.2, S-4.22  
   DIVIDE S-9.1, S-9.18  
   ECHO S-1.28  
   EMPTY.TABLES S-6.1, S-6.20,  
     S-6.24

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- EXCEPT S-4.15, S-4.22  
 EXCLUDE ALL STUB VALUES  
   S-2.2  
 EXCLUDE MISSING MEANS VAL-  
   UES S-1.23, S-1.28  
 EXCLUDE SMALL SUBTOTALS  
   S-4.18, S-4.22  
 EXCLUDE SOME STUB VALUES  
   S-2.22  
 EXPECTED.VALUE S-5.13, S-5.23,  
   S-8.12  
 F.TEST S-8.8, S-8.25  
 FILL S-2.1  
 FILL COLUMNS S-3.3, S-3.28  
 FILL ROWS S-2.22  
 FILL SUBTOTALS S-4.13, S-4.22  
 FLOATING TITLES S-10.27,  
   S-10.28  
 FONT S-7.2, S-7.3, S-7.14  
 FORMAT S-7.2, S-7.3, S-7.13  
 GAP S-1.13, S-1.28  
 GET.PERCENTILES S-8.21, S-8.25  
 GR.IDENTIFY S-2.10, S-2.22  
 GROUP.STUBS S-2.9, S-2.21,  
   S-3.19, S-3.28  
 INCLUDE S-10.2, S-10.29  
 INCLUDE ALL STUB VALUES  
   S-2.2, S-2.22  
 INCLUDE ALL SUBTOTALS  
   S-4.18, S-4.22  
 INCLUDE MISSING MEANS VAL-  
   UES S-1.22, S-1.28, S-3.7  
 INDENT S-4.22  
 INDENT DEFINED VALUES S-4.13  
 INDEX S-5.12, S-5.23  
 JOIN S-6.20, S-6.24, S-7.6, S-7.15  
 LABELS S-1.13, S-5.6  
 LAYOUT S-1.7, S-1.28  
 LEFT JUSTIFY LABELS S-5.24  
 LEFT.EDGE S-6.16, S-6.24, S-7.3,  
   S-7.15  
 LFONT S-7.6, S-7.14  
 LINE.WIDTH S-7.8, S-7.15  
 MARGIN S-1.28, S-7.15  
 MARK ALL TESTS S-8.25, S-9.12  
 MAX.INDEX S-5.12, S-5.23  
 MEANS S-1.21, S-1.28, S-8.21,  
   S-8.23, S-8.25  
 MEDIAN S-1.22, S-8.17, S-8.25  
 METHOD.DEFAULT S-8.19, S-8.25  
 METHOD.FIRST S-8.19, S-8.25  
 METHOD.GROUPED S-8.19, S-8.26  
 MISSING S-5.16, S-5.24  
 MQ.STUBS S-2.18, S-2.19, S-2.21  
 MR.BANNERS S-3.28  
 MR.STUBS S-2.14, S-2.21  
 MULTIPLY S-9.1, S-9.18  
 NETS S-4.22  
 NEVER SKIP S-1.13, S-1.29, S-6.15  
 NO S-1.29  
 NO COUNTS S-1.9  
 NO PERCENTS S-1.9  
 NO VARIABLE LABELS S-5.7,  
   S-5.24  
 NO.PRINT S-10.12  
 OMIT.PERCENTS S-8.4, S-8.26  
 OPTION LABEL COMBINED SUB-  
   TOTALS S-4.18, S-4.22  
 OPTION TEST COMBINED SUBTO-  
   TALS S-4.16  
 OPTION TEST SUBTOTALS S-4.18,  
   S-4.23  
 ORDER S-2.3, S-2.22  
 ORDER COLUMNS S-3.4, S-3.28  
 OUT S-10.12, S-10.29  
 OUTPUT.WIDTH S-1.12, S-1.29,  
   S-1.30  
 OVERALL.TOTALS S-10.7, S-10.29  
 PAGE S-5.1, S-5.24  
 PAGE.NUMBER S-10.28  
 PAIRED S-3.14, S-3.28  
 PERCENTS S-1.9, S-1.29, S-8.26  
 PLACES S-3.7, S-5.12, S-6.16,  
   S-6.24, S-8.1, S-8.26  
 POSTSCRIPT S-7.1, S-7.13  
 PR S-1.19, S-1.29, S-7.1  
 QFONT S-7.6, S-7.14  
 QUARTILES S-8.21, S-8.26



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- QUESTION S-5.4, S-5.25  
 QUESTION IN LABELS.AREA  
     S-5.4, S-5.25  
 QUOTES S-6.16, S-6.24  
 RANK S-2.3, S-2.4, S-2.5, S-2.22,  
     S-4.10, S-4.11  
 RANK COLUMNS S-3.4, S-3.29  
 RANK CONTROLS NETS S-4.11,  
     S-4.23  
 RANK CONTROLS SUBTOTALS  
     S-4.11, S-4.23  
 RANK SUMMARY S-2.11, S-2.23  
 RANK WITHIN NETS S-4.10,  
     S-4.23  
 RANK WITHIN SUBTOTALS  
     S-4.10, S-4.23  
 RANK.CONTROL S-2.23  
 REPORT ALL RESULTS S-8.23,  
     S-8.26, S-9.10  
 REQUIRE S-8.26, S-9.9, S-9.18  
 REQUIRE INDEPENDENCE S-9.6  
 REQUIRE PROPORTION S-9.6  
 RESET S-1.25, S-10.1, S-10.29  
 RESET SUBTOTALS S-4.5, S-4.23  
 RESTART S-10.1, S-10.29  
 RIGHT JUSTIFY LABELS S-5.24  
 RIGHT.EDGE S-7.3, S-7.8, S-7.15  
 ROW.TOTALS S-1.11, S-1.29  
 ROW.TOTALSBASEDRESPONSES  
     S-3.16, S-3.29  
 SAMPLE S-8.14, S-8.26  
 SCALE S-7.16  
 SET.LABELS S-1.2, S-2.23  
 SHARED RANGES S-2.3, S-2.23  
 SHOW S-1.29  
 SHOWPAGE S-7.9, S-7.16  
 SKIP S-1.13, S-1.29, S-2.6, S-2.7  
 SKIP.RULES S-1.13, S-6.24  
 SPREAD S-1.13, S-6.12, S-6.24  
 SQUEEZE COLUMNS S-3.3, S-3.29  
 SQUEEZE ROWS S-2.23  
 SQUEEZE SUBTOTALS S-4.13,  
     S-4.23  
 STANDARD.DEV S-1.30  
 STANDARD.ERROR S-8.13  
 STATIONARY TITLES S-10.27,  
     S-10.29  
 STUBS S-1.27, S-2.21  
 SUBTOTALS S-4.23, S-5.13, S-5.25  
 SUBTRACT S-9.1, S-9.18  
 SUMMARY S-5.18, S-5.25  
 SUMS S-1.22, S-1.30  
 SVAR.LABELS S-5.21, S-5.26  
 SVAR.PER.PAGE S-2.8, S-2.23  
 TABLE.NUMBER S-10.29  
 TABLE.TITLES S-2.11, S-5.3,  
     S-7.6, S-10.5, S-10.29  
 TABNUM S-10.5  
 TEST S-9.19  
 TEST MEANS S-9.18  
 TEST TREND S-9.14, S-9.19  
 TFONT S-7.6, S-7.14  
 TITLES S-1.13, S-1.16, S-1.30  
 TOP.EDGE S-6.16, S-6.24, S-7.3,  
     S-7.11, S-7.15  
 TOTALS.AREA S-5.8, S-5.25  
 TRANSPPOSE S-3.19, S-3.29  
 UNPAIRED S-3.16, S-3.29  
 USE S-4.10, S-4.24  
 USE PERCENTS S-9.11, S-9.20  
 USE POSITIONS S-2.23, S-4.5  
 USE RESPONSES S-9.11, S-9.20  
 USE TITLES S-5.3, S-5.24  
 USE TOTAL.N S-9.11  
 USE UNWEIGHTED.BASE S-9.10,  
     S-9.19  
 USE VALUES S-2.23, S-4.5  
 VARIABLE.LABELS-on/off S-5.7  
 WEIGHT S-1.30  
 subtotals for banner variables S-9.5  
 Summary S-1.26, S-2.21, S-3.27, S-4.21,  
     S-5.23, S-6.22, S-7.13, S-8.24,  
     S-9.18, S-10.28  
 SURVEY subcommands  
     SUMMARY S-5.18  
 SURVEY.LABELS  
     codes S-3.8, S-3.10, S-6.1, S-6.24,  
     S-9.10

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

custom labelling S-6.1, S-8.23  
**SURVIVAL A-7.1**  
 actuarial method  
   see LIFE.TABLE  
 identifiers  
   BY A-7.12  
   COVARIATES A-7.9  
   DOWN A-7.9  
   EXACT A-7.19  
   NO LIST A-7.8  
   NO PLOT A-7.8  
   OUT A-7.7  
   PR A-7.19  
   STATUS A-7.2  
   STRATA A-7.2  
   TIME A-7.2  
   UP A-7.12  
 product-limit estimates A-7.7  
 Survival analysis A-7.1  
**SVAR.LABELS**  
   in SURVEY command S-5.21, S-5.26  
**SVAR.PER.PAGE**  
   in SURVEY command S-2.8, S-2.23  
**SYMBOL**  
   in BOXPLOT command O-6.8, O-6.13  
   in PLOT command O-5.3, O-5.15  
 Synonyms  
   in ANOVA command A-6.44  
**SYNTAX**  
   EDITOR instruction U-6.8, U-7.4  
 Syntax  
   of command I-2.15, I-3.1, I-3.14  
**SYSTEM U-3.9**  
   introduction for new users I-2.13  
**SYSTEM command O-2.7**  
 System files I-10.1  
   defined W-2.4  
   format of I-10.1  
   hierarchical I-10.2, F-9.10  
   moving F-2.1  
   naming I-2.9, I-10.6  
   packing I-10.3  
   previous or current version P-1.3  
   template F-6.2, P-3.3

temporary I-10.8  
 System variables **P-6.1**  
   .DATE. W-2.6  
   .M. P-2.27  
**SYSTEM.EDIT.FILE U-3.4**  
   summary U-3.9  
**SYSTEM.MISSING**  
   in SPSS.IN command I-4.3, F-2.5  
**T**  
 t distribution P-7.5  
   inverse P-7.6  
 T1 to T9  
   in TITLES command I-5.10, S-11.2  
 Tab delimited file W-3.1  
   as input W-2.3  
   as output W-2.4  
   importing W-3.2  
 Tab delimited input I-4.2, I-10.3  
**TABFILE.IN W-2.3, W-2.16, F-2.1, F-2.3**  
   identifiers  
     CHARACTER F-2.13  
     DECIMAL.COMMA F-2.13  
     DELIMITER F-2.13  
     LABELS F-2.13  
     NUMERIC F-2.13  
     READ F-2.13  
   import tab delimited file W-3.2  
**TABFILE.IN. See TEXTFILE.IN**  
**TABFILE.OUT I-9.3, W-2.4, F-2.7, F-2.7**  
   identifiers  
     CR F-2.14  
     CRLF F-2.14  
     CR, LF and CRLF F-2.8  
     DECIMAL.COMMA F-2.14  
     DELIMITER F-2.8, F-2.14  
     EOF F-2.8  
     LABELS F-2.8, F-2.14  
     LF F-2.14  
     NL F-2.14  
     NO LABELS F-2.14  
     WRITE F-2.14  
**TABLE**  
   in LOOKUP command F-9.12, F-9.22

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- Table  
   with totals  
     quantity banner variables S-3.9
- Table of Contents S-10.4  
   DISPLAY keyword S-10.4
- Table of means S-2.10
- TABLE.NUMBER  
   in SURVEY command S-10.4, S-10.28,  
     S-10.29
- TABLE.TITLES  
   in SURVEY command S-2.11, S-10.5,  
     S-10.29  
   printing S-5.3  
   selecting a font S-7.6
- Tabled random number P-7.1
- Tables A-7.1  
   creating W-2.2  
   multiple per page S-7.9  
   produced by SURVEY command S-1.1  
   single statistic only S-2.10
- TABNUM  
   in SURVEY command S-10.5
- TABS  
   in SURVEY command S-6.14, S-6.22
- TAG in variable names I-3.8
- TAGS W-1.6  
   general identifier I-5.18, U-2.6  
   labels in SURVEY command S-1.2  
   use in SURVEY command S-2.13
- TAN  
   PPL function P-6.3, P-6.21
- Tangent function P-6.3
- TEMP  
   general identifier U-2.6, U-3.4  
   summary U-3.9
- TEMPLATE  
   in CONCAT command F-8.3, F-8.10  
   in MAKE command I-4.5, I-4.11, F-3.3,  
     F-3.12  
   in MODIFY command F-6.2, F-6.12,  
     P-3.3, P-3.16  
   TURF identifier I-8.30
- Temporary files I-10.6, I-10.8
- Temporary modifications W-5.3
- Term  
   in ANOVA command A-6.19
- TEST  
   in FACTOR command A-5.2  
   in REGRESSION command B-4.14
- TEST MEANS  
   in SURVEY command S-9.18
- test of B-5.11
- Test runs  
   designing S-10.26
- Tests of Independence S-9.9
- TET **B-3.10**, A-1.8  
   identifiers  
     CROSS B-3.11, B-3.17  
     CTET B-3.11, B-3.16  
     OUT B-3.10, B-3.17  
     SPLIT B-3.11, B-3.17  
     ZERO B-3.11, B-3.17  
   maximum number of variables B-3.11  
   summary B-3.16
- TEXT **U-2.18**  
   general identifier I-3.15, I-5.18, I-6.28,  
     U-2.6  
   in variable names I-3.8  
   labels in SURVEY command S-1.2
- TEXT.ONLY  
   general identifier  
     SHOW command only I-5.18
- TEXT.WRITER S-10.23  
   FONT5-FONT29 O-2.2  
   identifier  
     POSTSCRIPT O-2.1
- TEXTFILE.IN I-1.2, I-2.2, I-2.15, **I-4.2**,  
   I-4.2, I-4.12, W-1.5, W-2.3, W-2.16,  
   F-2.13, P-1.1  
   identifiers I-4.13  
     CHARACTER I-4.2, I-4.13  
     DECIMAL.COMMA I-4.13  
     DELIMITER I-4.2, I-4.13  
     EXTENDED.LABELS I-4.3, I-4.13  
     FILE I-4.2, I-4.13  
     HONOR.STRINGS I-4.13  
     IGNORE.STRINGS I-4.2, I-4.13  
     LABEL.CHANGES I-4.3

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- LABELS I-4.3, I-4.13  
 NO LABELS I-4.13  
 NUMERIC I-4.2, I-4.13  
 STRING.BOUNDARY I-4.2, I-4.13  
 importing data I-2.1  
 see TABFILE.IN F-2.1  
 string variables I-4.2  
 TEXTFILE.OUT W-2.3, F-2.13  
 TEXTWRITER P-1.3, P-1.6, **P-11.1**  
 comments P-11.6  
 control words P-11.8  
 @ P-11.9, P-11.33  
 @BEFORE P-11.10, P-11.33  
 @BLACK P-11.28  
 @BLUE P-11.28  
 @BOTTOM P-11.27  
 @CINCH P-11.24  
 @CINCH.U P-11.25  
 @COMMAS P-11.11, P-11.34  
 @DOWN P-11.27  
 @DRAW.BOX P-11.26  
 @DRAW.H P-11.26  
 @DRAW.U P-11.26, P-11.38  
 @DRAW.V P-11.26  
 @EQUAL P-11.13, P-11.34  
 @FLUSH P-11.26  
 @FONT1-@FONT9 P-11.22,  
 P-11.37  
 @GREEN P-11.28  
 @INDENT P-11.10, P-11.34  
 @JUST P-11.10, P-11.34  
 @L.MARGIN P-11.27  
 @LABEL P-11.14  
 @LEADING P-11.27  
 @LINCH P-11.25  
 @LINCH.U P-11.25  
 @LINEWIDTH P-11.27  
 @MINUS P-11.9, P-11.35  
 @MISS P-11.14, P-11.34  
 @MOVETO P-11.26  
 @NEXT P-11.10, P-11.35  
 @NOCOLOR P-11.28  
 @NOUNDERLINE P-11.29  
 @ORANGE P-11.28  
 @PAGE P-11.10, P-11.35  
 @PARA P-11.10, P-11.35  
 @PINCH P-11.25  
 @PINCH.CHAR P-11.26  
 @PINCH.U P-11.26  
 @PLACES P-11.12, P-11.35  
 @PLUS P-11.8, P-11.9, P-11.35  
 @R.MARGIN P-11.27  
 @RED P-11.28  
 @RINCH P-11.25  
 @RINCH.U P-11.25  
 @SKIP P-11.8, P-11.35  
 @SPREAD P-11.13, P-11.35  
 @TOP P-11.27  
 @TRIM P-11.10, P-11.35  
 @UNDERLINE P-11.29  
 @UP P-11.27  
 @VIOLET P-11.28  
 @WIDTH P-11.10, P-11.36  
 @X1 P-11.26  
 @X2 P-11.26  
 @Y1 P-11.26  
 @YELLOW P-11.28  
 @Y2 P-11.26  
 identifiers  
 BLANKS P-11.7, P-11.32  
 BOTTOM.EDGE P-11.21, P-11.36  
 CASE P-11.6, P-11.32  
 FONT P-11.21, P-11.36  
 FONT1-FONT9 P-11.21, P-11.36  
 JUSTIFY P-11.7, P-11.32  
 LABELS P-11.8, P-11.32  
 LANDSCAPE P-11.21, P-11.36  
 LEADBLANK P-11.7, P-11.32  
 LEFT.EDGE P-11.21, P-11.36  
 MARGIN P-11.7, P-11.32  
 NO LEADBLANK P-11.7  
 NO SHWPAGE P-11.21  
 NO SPREAD P-11.7  
 OUT P-11.8, P-11.32  
 PORTRAIT P-11.20, P-11.36  
 POSTSCRIPT P-11.20, P-11.36  
 PUTL.CHARS P-11.32  
 RIGHT.EDGE P-11.21

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- SHOWPAGE P-11.21, P-11.37
- SPREAD P-11.7, P-11.32
- STREAM P-11.7, P-11.32
- TOP.EDGE P-11.21, P-11.37
- WIDTH P-11.8, P-11.33, P-11.36
- justification P-11.2
- no-break character P-11.2
- PUT instructions P-11.2
- summary P-11.31
- TEXTWRITER.SETUP
  - identifiers
    - DELTA O-2.6
- TFONT
  - in SURVEY command S-7.6, S-7.14
- THRESHOLD
  - in BALANCE command S-12.5
  - in BPRINT command B-3.6
  - in CLEANCOR command A-5.3
  - in TTEST command B-2.5
- TICK.LABELS
  - in PLOT command O-5.6, O-5.15, O-3.8
- TICKS
  - in BOXPLOT command O-6.6, O-6.14
  - in PLOT command O-3.8
- TIES
  - in LOOKUP command F-9.19, F-9.23
- TIME
  - in SURVIVAL command A-7.2
- Time functions P-10.1– P-10.13
- Time series
  - polynomial distributed lag models B-4.12
- Time trend models
  - in REGRESSION command B-4.11
- TITLES I-5.1, **I-5.9**, I-5.16, **S-11.1**, S-11.1
  - bottom titles I-5.9, S-11.1
  - control in SURVEY command S-5.3
  - controlling fonts S-7.6
  - defining I-5.9, S-11.1
  - defining in POSTSCRIPT O-2.10
  - identifiers
    - B1 to B3 I-5.10, I-5.17, S-11.2, S-11.12
    - BLANK I-5.10, I-5.17, S-11.2, S-11.12
  - CENTER I-5.11, I-5.17, S-11.3, S-11.12
  - FILL I-5.11, I-5.17, S-11.3, S-11.13
  - LEFT I-5.11, I-5.17, S-11.3, S-11.13
  - OFF I-5.12, I-5.17, S-11.4, S-11.13
  - ON I-5.12, I-5.17, S-11.4, S-11.13
  - PAGE.NUMBER I-5.13, S-11.5
  - RESET I-5.12, I-5.17, S-11.4, S-11.13
  - RIGHT I-5.10, I-5.17, S-11.3, S-11.13
  - RUN.PAGE.NUMBER I-5.13, S-11.5
  - SHOW I-5.11, I-5.17, S-11.4, S-11.13
  - T1 to T9 I-5.10, I-5.17, S-11.2, S-11.13
  - in BOXPLOT command O-6.8, O-6.11, O-6.15
  - in COUNTS command I-7.4
  - in LIST command I-6.5
  - in PLOT command O-4.1
  - in POSTSCRIPT command O-2.8, O-2.20, O-2.21
  - in SURVEY command S-1.13, S-1.16, S-1.26, S-1.30, S-5.3
  - summary I-5.15, S-11.12
  - system variables, use of I-5.13, P-6.26, S-11.5
  - top titles I-5.9, S-11.1
  - turning on and off I-5.9, S-11.1
  - use of FONT3 O-2.3, O-2.12
- Titles W-2.2
  - joining to make longer titles S-6.24
- TO
  - reserved word I-3.2
- TOKEN
  - PPL function P-9.9, P-9.10, P-9.29
- TOL
  - in COLLATE command F-9.9, F-9.21
  - in REGRESSION command B-4.16
- TOP
  - EDITOR instruction U-6.7, U-7.4
- Top titles
  - in TITLES command I-5.9, S-11.1

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

## TOP.EDGE

in BOXPLOT command O-6.12  
 in PLOT command O-5.1, O-5.16  
 in POSTSCRIPT.SETUP command  
 O-2.4, O-2.18  
 in SURVEY command S-6.16, S-6.24,  
 S-7.3, S-7.15  
 in TEXTWRITER command P-11.37

## TOTAL

in PLOT command O-3.14

## TOTALS

in LIST command I-6.21

Totals of banner variables S-3.6

## TOTALS.AREA

in SURVEY command S-1.7, S-5.8,  
 S-5.25

## TRANS

in PROMAX command A-5.5  
 in UPDATE command F-11.1, F-11.11

TRANSFER I-3.7, W-2.3, **U-2.8**, U-2.19,  
 U-3.1

command files W-5.13

identifiers

EXIT U-2.9, U-2.19

## TRANSFORM

in REGRESSION command B-4.10

## TRANSPOSE **A-1.1**

identifiers

OUT A-1.1

in SURVEY command S-3.19, S-3.29

summary A-1.14

## TREATMENT

in ANOVA command A-6.10, A-6.24,  
 A-6.44

## Trend statistic

in SURVEY command S-9.14, S-9.19

## TRIAL.FACTOR

in ANOVA command A-6.44

## TRIM

PPL function P-9.29

## TRIM.ZEROS

in LIST command I-6.10

## Triple slash

PPL operator P-9.5

## TRUE

in FREQ command B-1.6

## TRY

in Q.CLUSTER command A-3.3

## TTEST W-2.3, **B-2.1**

identifiers

BOTH B-2.5, B-2.8

DES.1 B-2.5, B-2.8

DES.2 B-2.5, B-2.9

NO.MATCH B-2.5, B-2.9

OUT B-2.3, B-2.8

POOLED B-2.5, B-2.9

SEPARATE B-2.5, B-2.9

THRESHOLD B-2.5, B-2.9

WEIGHT B-2.9

paired t test **B-2.6**

summary B-2.8

## t-test

in SURVEY command S-8.25

## Tukey

tests A-6.36

## Tukey method

in BOXPLOT command O-6.3

## TURF I-1.3, W-1.3, W-3.1, W-3.3, W-5.1

cascading step I-8.21

features I-8.1

greedy method I-8.18

identifiers

CASE.WEIGHTS I-8.12, I-8.29,  
 W-3.11, W-5.10

CONSTRAIN W-3.12

FILTER I-8.29

FORCE I-8.11, I-8.29, W-3.12

FREQ.RESULTS I-8.17, I-8.28,  
 W-3.11, W-5.12

FREQ.STATS I-8.29, W-3.11

FREQ.SUMMARY I-8.23, W-3.11

FULL.OUTPUT I-8.23, W-3.12

FULL.REPORT I-8.11

ITEM.WEIGHTS I-8.12, I-8.29,  
 W-3.11

OMIT I-8.15, I-8.29, W-3.11

PROGRESS I-8.10, I-8.29, W-3.12

REACH.RESULTS I-8.13, I-8.28,

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- W-3.6, W-3.11, W-5.10
- REACH.STATS I-8.17, I-8.28,  
W-3.11
- REACH.SUMMARY I-8.22, W-3.11
- REACH.THRESHOLD I-8.10,  
I-8.28, W-3.11
- REORDER I-8.22
- RESPONSE WEIGHTS W-3.11
- RESPONSE.WEIGHTS I-8.12,  
I-8.29
- SET.MISS.TO.ZERO I-8.10, I-8.29
- SHOW I-8.15, I-8.30, W-3.11
- SIZE I-8.28, W-5.12
- STEP I-8.10, **I-8.17**, W-3.12, W-5.12
- USE.NAMES I-8.24, W-3.12
- limitations I-8.26
- processing speed I-8.25
- reach versus frequency I-8.1
- summary I-8.28
- Total Unduplicated Reach and Frequency  
W-2.3
- TURF.SCORES I-1.3, I-8.30, W-1.3,  
W-5.12
- Two-tailed tests  
in nonparametric statistics B-5.3
- TYPE  
EDITOR instruction U-6.8, U-7.6
- U**
- U  
in NP.TEST command B-5.16
- Uncorrected sum of squares  
in COUNTS command I-7.1
- UNDERLINE **U-2.19**  
in PRINT.SETTINGS command U-2.2  
in SURVEY command S-6.9, S-6.11
- Underline  
variable labels S-6.11
- UNDO.DAYS function P-10.6, P-10.21
- UNDO.SECONDS function P-10.6, P-10.21
- UNIFORM  
in NP.TEST command B-5.13
- Uniform distribution, test of B-5.11
- Uniform random number P-7.1
- Unique contribution  
in TURF command I-8.3
- Univariate statistics W-5.1
- UNMAKE **F-2.9, F-2.16**  
identifiers F-2.17  
COMMAND F-2.10, F-2.16  
DATA F-2.10, F-2.16  
DELIMITER F-2.11, F-2.16  
END.OF.CASE F-2.11, F-2.16  
MISSING F-2.11  
NO DELIMITER F-2.11, F-2.16  
NO END.OF.CASE F-2.11, F-2.16  
NO MISSING F-2.11  
NO QUOTES F-2.11  
NO SCIENTIFIC F-2.11, F-2.17  
POINT F-2.11, F-2.17  
QUOTES F-2.11, F-2.17  
REPLACE.QUOTES F-2.11, F-2.17  
UNMAKE F-2.16
- UNMATCHED  
in LOOKUP command F-9.19, F-9.23
- UNPAIRED  
in SURVEY command S-3.16, S-3.29
- Unweighted counts  
in SURVEY command S-1.11
- UP**  
EDITOR instruction U-6.8  
in COLLATE command F-9.6, F-9.21  
in COUNTS command I-7.15  
in MERGE command F-7.5, F-7.11  
in SORT command F-7.3, F-7.10  
in SUBFILES command P-12.23  
in SURVIVAL command A-7.12  
in UPDATE command F-11.12
- UPDATE **F-11.1**  
action codes F-11.12  
DELETE F-11.8  
DELETE.INSERT F-11.5  
GRUMBLE.INSERT F-11.6, F-11.7  
GRUMBLE.SKIP F-11.6, F-11.7  
INSERT F-11.6  
MULT.DELETE F-11.6  
MULT.DELETE.INS F-11.6  
MULT.OLD.MISS F-11.6

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- MULT.REPLACE F-11.6
- MULT.USE.ALL F-11.6
- OLD.MISSING F-11.5
- REPLACE F-11.5, F-11.6
- SKIP F-11.6
- USE.ALL F-11.5
- assumed action F-11.3
- delete file F-11.8
- grumble file F-11.4, F-11.6
- identifiers
  - ABSENT F-11.3, F-11.11
  - BY F-11.3, F-11.11
  - DELETE F-11.11
  - DOWN F-11.3
  - DOWn F-11.11
  - GRUMBLE F-11.4, F-11.6, F-11.11
  - OUT F-11.1, F-11.11
  - PRESENT F-11.3, F-11.5, F-11.12
  - TRANS F-11.1
  - UP F-11.12
  - UPDATE F-11.11
- multiple cases F-11.8
- summary F-11.11
- UPPER
  - PPL function P-9.7, P-9.30
- Upper case
  - data entry I-3.2
  - use of W-2.7
- USE
  - base for significance tests S-9.19
  - in CANONICAL.COR command A-2.6
  - in COUNTS command I-7.4
  - in RANK command F-7.9
  - in SPLIT function P-8.14
  - in SURVEY command S-4.10, S-4.24
- USE POSITIONS
  - in SURVEY command S-2.23, S-4.5
- USE TABLE.TITLES
  - font selection
    - in SURVEY command S-7.16
  - SURVEY subcommand S-7.16
- USE TITLES
  - in SURVEY command S-5.3
  - SURVEY subcommand S-5.24
- USE UNWEIGHTED.BASE
  - in SURVEY command S-9.10
- USE VALUES
  - in SURVEY command S-2.23, S-4.5
- USE.ALL
  - in SUBSTITUTE.XL command F-12.13, F-12.20
  - in UPDATE command F-11.5
- USE.MEAN
  - in REGRESSION command B-4.9
- USE.MISSING
  - in COLLATE command F-9.21
  - in DUPLICATES command F-10.15, F-10.24
- USE.WEIGHTS
  - in SAMPLE command S-12.19
- USE.XL
  - in LIST command I-6.8
  - extended variable labels I-5.8, S-11.10
- used in ANOVA command A-6.17
- USING
  - in RESISTANT.SMOOTH B-6.19
- using /\* and \*/ P-3.20
- Utility commands
  - interactive use U-3.1
- V**
- V**
  - see VERBOSITY
- V vector P-1.2
- VALIDATE
  - EDITOR instruction U-6.20
- Value labels I-5.3, S-11.6
  - centering S-5.24
  - checking I-5.8, S-11.10
  - for missing data I-6.10
  - in SURVEY command S-1.14
  - saving W-2.2
  - size constraints in LIST I-6.7
  - storage area
    - limitations S-10.13
  - SUBSTITUTE.VL command F-12.8
- VALUES



I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- in COUNTS command I-7.1, I-7.10
- VAR
  - in EDA subcommands B-6.2
- VARIABLE
  - in SUBSTITUTE.XL command F-12.13, F-12.20
- Variable
  - names W-1.6, W-2.15
- Variable labels
  - extended I-5.6, S-11.8
  - SUBSTITUTE.XL command F-12.11
  - underlining S-6.11
- Variable names W-2.15
  - rules for I-3.1, I-3.14
  - TAG I-3.8
  - TEXT I-3.8
- VARIABLE.LABELS
  - in SURVEY.command S-5.7
- VARIABLES
  - in SUBSTITUTE.VL command F-12.9, F-12.19
- Variables
  - accessing names P-3.11
  - across command (P Vector) P-8.5
  - across-case (scratch) P-8.3
  - adding to a file F-1.3
  - character, defining I-2.10
  - defined I-2.3, W-2.5
  - generating names P-5.8
  - in P-STAT file P-1.2, P-1.5
  - names I-2.3
  - naming W-2.6
  - positional notation P-2.4, P-2.10, P-6.3
  - P-STAT system I-3.2
  - reordering P-2.8
  - rules for names I-1.1, I-3.1, I-3.14
  - scratch I-3.2, P-1.2, P-1.5
  - system W-2.6, P-1.2, P-1.5
  - temporary W-2.6
  - 3 types P-1.2
- Variance
  - in ANOVA command
    - between-group A-6.1
    - mean square A-6.4, A-6.21
    - reduction of A-6.7, A-6.10
    - residual A-6.2
    - within-group A-6.2
  - in COUNTS command I-7.1
  - in SURVEY command S-5.20
  - stabilizing in REGRESSION command B-4.10
- Variance/covariance matrix, in CORRELATE command B-3.6
- VARNAME
  - PPL function P-9.17, P-9.30
- VARS
  - in MAKE command I-2.8, I-4.5, I-4.11, F-3.3, F-3.11
  - in MAKE.CHARACTER command F-12.17
  - in MAKE.FIXED command F-4.8
  - in MAKE.NUMERIC command F-12.14, F-12.17
- VBAR **U-2.3**, U-2.19
  - in DEFAULT.SETTINGS command U-2.2
  - in PRINTER.SETTINGS command U-2.2
  - vertical bar character I-9.2
- VEC
  - in FACTOR command A-5.3
- VECTORS
  - in EIGEN command A-1.8
- Vectors
  - dynamic P-1.3, P-1.5
  - P P-1.2, P-1.5
  - V P-1.2, P-1.5
- VERBOSE
  - in COUNTS command I-7.17
- VERBOSITY I-6.28, F-10.20, **U-2.19**
  - general identifier U-2.6
  - in COMPARE command F-6.5, F-6.11
  - in DISCRIM command A-4.5
  - in FREQ command B-1.7
  - in LIST command I-6.28
- VERIFY
  - PPL function P-9.8, P-9.30
- VERLAY
  - in PLOT command O-3.16

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

**VERSION U-2.19****VERTICAL**

in PLOT command O-3.10

**Vertical bar**

in ANOVA command A-6.6, A-6.41

**Vertical bar character U-2.3****VF**

in ROTATE command A-5.3

**VL.ONLY**

in SUBSTITUTE.VL command F-12.19

**VTR**

in ROTATE command A-5.3

**W****W.FREQUENCIES**

in COUNTS command I-7.15

**Wald-Wolfowitz Runs test B-5.19****WEEK.WITHIN.YEAR function P-10.7****WEEKDAY.CASE P-10.15, P-10.24****WEEKDAY.LENGTH P-10.24****WEEKDAY.NAMES P-10.15, P-10.24****WEIGHT**

in AGGREGATE command F-10.2,  
 F-10.21

in BALANCE command S-12.5

in CANONICAL.COR command A-2.4,  
 A-2.11

in CONCAT command F-8.7, F-8.10

in CORRELATE command B-3.7, B-3.14

in COUNTS command I-7.4

in FREQ command B-1.5

in MODIFY command F-6.2, F-6.12,  
 B-1.2, B-1.17

in NP.TEST command B-5.4, B-5.14,  
 B-5.23, B-5.36

in PERCENTILES command B-1.18

in Q.CLUSTER command A-3.4, A-3.12

in REGRESSION command B-4.10,  
 B-4.21

in SAMPLE command S-12.12, S-12.20

in STANDARDIZE command B-1.14,  
 B-1.19

in SURVEY command S-1.27, S-12.6

in TTEST command B-2.5, B-2.9

SURVEY subcommand S-1.30

**WEIGHT.NAME**

in BALANCE command S-12.5

**Weighted analysis W-5.1****Weighted counts**

in SURVEY command S-1.11

**Weighted tables**

with medians S-8.19

**Weighting**

creating weights with BALANCE S-1.21

description file F-8.7, B-1.2

in SURVEY command S-1.21

integer P-3.7

**Weights**

in TURF command I-8.12

**Weights and significance tests S-9.10****WHERE**

EDITOR instruction U-6.13, U-7.1

**WHISKERS**

in BOXPLOT command O-6.7, O-6.14

**WIDTH**

in TEXTWRITER command P-11.8,  
 P-11.33, P-11.36

**WILCOXON**

in NP.TEST command B-5.27

Matched-Pairs test B-5.27

rank sum test, t test approximation B-2.1

summary B-5.54

**Wildcard W-1.6**

? W-2.6

example I-7.7

in MATCHES meta-characters P-9.19

in PPL instructions P-8.15, P-8.24

in SPLIT instruction P-8.15

in variable selection P-2.8

in version 3 P-1.2

matching I-2.3, I-2.15

**Wildcard Examples P-2.5****WILDCARDS**

in SURVEY subcommand S-1.6

**Wilk's Lambda**

in CANONICAL.COR command A-2.4

in DISCRIM command A-4.1

**WINDIR**

I=Introductory Manual  
 P=P-STAT Programming Language  
 F=File Management

S=Survey, Sample, Balance  
 B=Basic Statistics  
 A=Advanced Statistics

U=Utility commands  
 O=Plots and PostScript  
 W=PC/Windows

- windows folder I-1.10
- WITHIN
  - in SORT command F-7.4, F-7.10
- Within-cells variance
  - in ANOVA command A-6.2
- WORK files I-10.8
- Workspace
  - limits S-10.13
- WRITE
  - in TABFILE.OUT command F-2.14
- X**
- X
  - in ANOVA command A-6.44
  - in RESISTANT.LINE B-6.15
  - in XY.PLOT B-6.13
- X.SUBSET
  - in ANOVA command A-6.44
- XAMONG
  - PPL operator P-2.18, P-2.27, P-9.3, P-9.32
- XBLANK
  - PPL function P-9.10, P-9.24
- XCHANGE
  - PPL function P-9.10, P-9.25
- XCONTAINS
  - PPL operator P-9.4, P-9.32
- XEQ
  - PPL operator P-2.14, P-2.26, P-9.2, P-9.5, P-9.32
- XGE
  - PPL operator P-9.3
- XGRAPH
  - summary O-7.7
- XGT
  - PPL operator P-9.3
- XL.ONLY
  - in SUBSTITUTE.XL command F-12.20
- XLE
  - PPL operator P-9.3
- XLT
  - PPL operator P-9.3
- XMATCHES
  - PPL operator P-9.18, P-9.33
- XNE
  - PPL operator P-2.26, P-9.3
- XNOTAMONG
  - PPL operator P-2.18, P-2.27, P-9.3, P-9.33
- XPOSITION
  - PPL function P-9.9, P-9.28
- XRECODE P-4.12
  - PPL function P-4.5, P-4.15
- XWindow and POSTSCRIPT
  - in PLOT command O-5.1
- XY.PLOT
  - EDA subcommand B-6.13
  - summary B-6.32
- XY.SUBSET
  - in ANOVA command A-6.44
- Y**
- Y
  - in ANOVA command A-6.22, A-6.44
  - in RESISTANT.LINE B-6.15
  - in XY.PLOT B-6.13
- Y1
  - EDITOR instruction U-6.15
- Y.SUBSET
  - in ANOVA command A-6.44
- Yates's correction for continuity S-8.12
- Y-intercept
  - in REGRESSION command B-4.5
- Y2
  - EDITOR instruction U-6.15
- Z**
- ŽCDATE. I-5.13
- ŽCTIME. I-5.13
- ZERO
  - in BISERIAL command B-3.9
  - in FACTOR command A-5.3
  - in TET command B-3.11
- ŽNDATE. I-5.13
- ŽNTIME. I-5.13
- ŽRDATE. I-5.13
- ŽRTIME. I-5.13
- ŽXDATE. I-5.13

I=Introductory Manual  
P=P-STAT Programming Language  
F=File Management

S=Survey, Sample, Balance  
B=Basic Statistics  
A=Advanced Statistics

U=Utility commands  
O=Plots and PostScript  
W=PC/Windows

ŽXTIME. I-5.13